


ABBREVIATIONS

NOTE: ABBREVIATIONS MAY HAVE PERIOD OR MAY NOT. ALSO SEE SPECIFICATIONS. ASK ARCHITECT ABOUT ANY ABBREVIATIONS WHICH ARE NOT STANDARD IN THE INDUSTRY OR WHICH YOU QUESTION, PRIOR TO BID. THE FOLLOWING ABBREVIATIONS ARE USED THROUGHOUT THE PLANS & SPECIFICATIONS AND SHALL BE DEFINED AS FOLLOWS:


ABBREV.	ABBREVIATE(D)	EXIST.	EXISTING	SPEC(S)	SPECIFICATION(S)
AFF.	ABOVE FINISH FLOOR	EXP. JT.	EXPANSION JOINT	SPEC.#	SPECIFICATION SECTION #
A/C	AIR CONDITIONING	FA	FRESH AIR	SPEC.D.	SPECIFIED
ACOUS.	ACOUSTICAL	FR	FIRE RATED	SS.	STAINLESS STEEL
ADA	AMERICAN DISABILITIES ACT	FD	FLOOR DRAIN	STD.	STANDARD
ADJ.	ADJACENT	FD	FIRE DAMPER	STD.DWG.	STANDARD DRAWING
AHJ	AUTHORITY HAVING JURISDICTION	FIN.	FINISH(ED)	STOR.	STORAGE
ALUM.	ALUMINUM	FLR.	FLOOR	STRUC.T.	STRUCTURE(AL)
ASB.	ASBESTOS	GALV.	GALVANIZED	SQ.	SQUARE
A.T.	ASBESTOS TILE	G.B.	GRAB BAR	T.B.	TELEPHONE BOARD
BD.	BOARD	LAV.	LAVATORY	T.B.	TACK BOARD
BLK.	BLOCK	L3	LAND 3 ARCHITECT INC.	TC.	TUBE COLUMN
BOT.	BOTTOM	MAT.	MATERIAL	TEMP.	TEMPORARY, TEMPERATURE
B.R.	BULLET RESISTANT	MAT'L.	MATERIAL	TIL.	TILE
CB.	CHALKBOARD	M.B.	MARKER BOARD	TOIL.	TOILET
CER.	CERAMIC	MBM.	METAL BUILDING MANUFACTURE	TYP.	TYPICAL
C.T.	CERAMIC TILE	MECH.	MECHANICAL	TYPICAL	TYPICAL (IN) ON ALL SIMILAR AREAS DETAILS OR CONDITIONS.
CLG.	CEILING	MEP.	MECH. ELECTRICAL, PLUMBING	GC. OR G.C.	GENERAL CONTRACTOR
COL.	COLUMN	MET.	METAL	GPC. OR G.P.C.	GLASCLAD POLYCARBONATE
CONC.	CONCRETE	MIN.	MINIMUM	GYP.BD.	GYP.SUM BOARD
CONT.	CONTINUOUS	M.O.	MASONRY OPENING	HC	HANDICAP(PED)
CONSTR.	CONSTRUCTION	MT.	MARBLE THRESHOLD	H.M.	HOLLOW METAL
CONTR.	CONTRACTOR	N.	NORTH	HP	HORSEPOWER
CMU.	CONC. MASONRY UNIT	NIC.	NOT IN CONTRACT	H.M.	HOLLOW METAL
C.R.	COLD ROLLED	NTS.	NOT TO SCALE	H.R.	HANDRAIL
CU.	CONDENSING UNIT	NO.	NUMBER	INSUL.	INSULATED(TION)
D.F.	DRINKING FOUNTAIN	O.C.	ON CENTER	LA.	LOUISIANA
DIAG.	DIAGONAL	OPNG.	OPENING	LAM.	LAMINATE
DIM.	DIMENSION	P.L.	PROPERTY LINE	UL.	UNDERWRITER'S LABORATORY
D.O.	DOOR OPENING	PLAS.	PLASTIC	UNL.	UNLESS OTHERWISE NOTED
DWG.	DRAWING	PLB.	PLUMBING	UNL.	UNLESS OTHERWISE NOTED
DRWG.	DRAWING(S)	PLYWD.	PLYWOOD	VERT.	VERTICAL
DS.	DOWNSPOUT	RE:	REFERENCE	W.	WEST
DWS.	DRY WALL STUD	REINF.	REINFORCEMENT	W/O	WITHOUT
E.	EAST	S.	SOUTH	W.C.	WATER CLOSET
EA.	EACH	SP.	SPLASHBLOCK	WD.	WOOD
E.J.	EXPANSION JOINT	S.C.	SOLID CORE	W/D	WALK DRAIN
ELEC.	ELECTRICAL	SCH.	SCHEDULE(D)	WWF.	WELDED WIRE FABRIC
E.O.B.	EDGE OF BUILDING	SHT.	SHEET	W.O.	WINDOW OPENING
ETR.	EXISTING TO REMAIN	SIM.	SIMILAR		
EQUIP.	EQUIPMENT	SP.	SPLASHPAN		

VICINITY MAP NOT TO SCALE



OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA
1000 OLIVER ROAD MONROE, LA 71201
FOR THE OUACHITA PARISH POLICE JURY
OUACHITA PARISH POLICE JURY

TONI BACON DISTRICT A
JIMMY TYSON DISTRICT B
LARRY BRATTON DISTRICT C
MICHEAL THOMPSON DISTRICT D
SHANE SMILEY DISTRICT E
LONNIE HUDSON DISTRICT F
BRAD CAMMACK PARISH TREASURER
JAY MITCHELL PARISH ATTORNEY



(THIS RENDERING IS FOR CONCEPTUAL PURPOSES ONLY)



A Professional Corporation
 1900 STUBBS AVE.
MONROE, LOUISIANA
 FIRM CONTACT: BILL LAND AIA, PROJECT ARCHITECT
 EMAIL: BILL@LAND3.COM
 PHONE: (318) 322-2694 (EXT. 2) Cell (318) 348-9753
AUGUST 2024
 PROJECT NO. 1963

LIST OF DRAWINGS

ARCHITECTURAL (LAND 3)		MECHANICAL & ELECTRICAL: EMA ENGINEERING & CONSULTING INC. 9441 STEVENS ROAD, Suite 200 SHREVEPORT, LOUISIANA 71106 PH. 318-425-4500 Email: purtle@purtle.net	
T1.1	TITLE SHEET	MECHANICAL	
SP1.0	ENGINEER BOUNDARY & TOPOGRAPHIC SURVEY	MP1.1	MECH./PLUMBING ROOF PLAN
SP1.1	SITE DEMOLITION PLAN	PD1.1	1st FLOOR PLUMBING DEMO
SP1.2	SITE IMPROVEMENT PLAN	P1.1	PARTIAL 1st FLOOR WASTE & VENT
SP2.1	SITE DETAILS	P1.2	PARTIAL 1st FLOOR WASTE & VENT
D1.1	1ST & 2ND FLOOR DEMOLITION PLANS	P1.3	PARTIAL 1st FLOOR DOMESTIC WATER & GAS
LS1.1	1ST & 2ND FLOOR LIFE SAFETY PLANS	P1.4	PARTIAL 1st FLOOR DOMESTIC WATER & GAS
A1.1	1ST & 2ND FLOOR PLANS	P2.1	2nd FLOOR WASTE & VENT
A1.2	NOTES AND SCHEDULES	P2.2	2nd FLOOR DOMESTIC WATER & GAS
A2.1	DOOR SCHEDULES	P3.1	PLUMBING SCHEDULES & GENERAL NOTES
A2.1a	ACCESS CONTROLLED DOOR SCH.	P4.1	PLUMBING DETAILS
A2.2	WINDOW SCHEDULE & DOOR HARDWARE SCH.	P4.2	PLUMBING DETAILS & RISERS
A3.1	EXTERIOR ELEVATIONS	FP1.1	1st & 2nd FLOOR FIRE PROTECTION PLANS
A4.1	CROSS SECTIONS	MD1.1	1st FLOOR HVAC DEMOLITION PLAN
A4.2	INTERIOR ELEVATIONS	MD2.1	2nd FLOOR HVAC DEMOLITION PLAN
A4.3	INTERIOR ELEVATIONS	M1.1	PARTIAL 1st FLOOR HVAC PLAN
A4.4	EXISTING INT. EXIT STAIR MODIFICATIONS	M1.2	PARTIAL 1st FLOOR HVAC PLAN
A4.5	ENLARGED ELEVATOR PLANS AND DETAILS	M2.1	2nd FLOOR HVAC PLAN
A4.6	ELEVATOR DETAILS, MOUNTING DETAILS, & ALUMINUM SUN SHADE DETAILS	M3.1	HVAC SCHEDULES
A5.1	EXTERIOR WALL SECTIONS	M3.2	HVAC DETAILS
A5.2	EXTERIOR ENLARGED WALL DETAILS & ENTRANCE CANOPY DETAILS	M3.3	HVAC DETAILS
A5.3	ELEVATOR PENTHOUSE WALL SECTIONS, MISC. DETAILS, & FURR-DOWN DETAILS	ELECTRICAL	
A5.4	MISC. DETAILS	ED1.1	1st FLOOR ELECTRICAL DEMOLITION PLAN
A5.5	FIRE BARRIER & FIRE RATING DETAILS	ED2.1	2nd FLOOR ELECTRICAL DEMOLITION PLAN
A5.6	FIRE BARRIER & FIRE RATING DETAILS	E1.1	PARTIAL 1st FLOOR POWER PLAN
A6.1	1ST & 2ND FLOOR PARTITION PLANS & PARTITION SECTIONS	E1.2	PARTIAL 1st FLOOR POWER PLAN
A7.1	DOOR DETAILS	E1.3	PARTIAL 1st FLOOR LIGHTING PLAN
A7.2	DOOR & WINDOW DETAILS	E1.4	PARTIAL 1st FLOOR LIGHTING PLAN
A7.3	DOOR & WINDOW DETAILS	E2.1	2nd FLOOR POWER PLAN
A7.4	DOOR & WINDOW DETAILS	E2.2	2nd FLOOR LIGHTING PLAN
A7.5	DOOR DETAILS	E3.1	ELECTRICAL SCHEDULES
A7.6	DOOR & WINDOW DETAILS	E3.2	ELECTRICAL DETAILS
A7.7	WINDOW DETAILS	E3.3	ELECTRICAL DETAILS
A8.1	MILLWORK		
A8.2	MILLWORK & DISPLAY CASE DETAILS		
A8.3	ADA SIGNAGE, LETTERING, & MISC. SIGNAGE		
A9.1	ENLARGED RESTROOM PLANS & INT. ELEV.		
A9.2	TYP. RESTROOM DETAILS & MOUNTING DIMENSIONS		
FL1.1	1ST & 2ND FLOOR - FLOORING PLANS		
F1.1	1ST & 2ND FLOOR FURNITURE PLANS		
RC1.1	1ST & 2ND FLOOR ACOUSTIC CEILING LAYOUT PLANS		
R1.1	ROOF PLAN		
R2.1	ROOF DETAILS		
ASF1.1	ARCHITECTURAL FRAMING PLANS FOR MAIN ENTRANCE ARCHED CANOPY		
STRUCTURAL: S.E. HUEY CO. 1111 NORTH 19th STREET MONROE, LOUISIANA 71201 PH. 318-325-1791			
S1.1	FOUNDATION PLAN AND DETAILS		
S1.2	EXTERIOR STAIR DETAILS & ROOF-TOP UNIT SUPPORT/FRAMING DETAILS		

CODES & DESIGN SPECIFICATIONS

CODE INFORMATION - ALSO SEE SECTION 01 15 00 IN SPECIFICATIONS.

LIFE SAFETY CODE 2015 INFORMATION

OCCUPANCY	BUSINESS
TOTAL SQUARE FOOTAGE	42,200 (1st flr) 5,896 (2nd flr)
AUTOMATIC SPRINKLER SYSTEM	(PROVIDED)
FIRE ALARM SYSTEM	(PROVIDED)
TRAVEL DISTANCE ALLOWED	200 FT.
COMMON PATH OF TRAVEL ALLOWED	75 FT.
DEAD END CORRIDOR LIMIT	20 FT.
NUMBER OF EXITS REQUIRED	2 REQUIRED
MIN. WIDTH OF CORRIDORS	44"
OCCUPANT LOAD	475

2021 INTERNATIONAL BUILDING CODE INFORMATION

OCCUPANCY	B
TOTAL SQUARE FOOTAGE	42,200 (1ST FLR) 5,896 (2ND FLR)
AUTOMATIC SPRINKLER SYSTEM	(PROVIDED)
FIRE ALARM SYSTEM	(PROVIDED)
EXIT ACCESS TRAVEL DISTANCE	200 FT.
COMMON PATH OF TRAVEL	75 FT.
DEAD END CORRIDOR LIMIT	20 FT.
NUMBER OF EXITS	2 REQUIRED
MIN. WIDTH OF CORRIDORS	44"
OCCUPANT LOAD	475
AREA LIMITATION	75,000 SQ. FT.
HEIGHT LIMITATION	3 STORIES
TYPE OF CONSTRUCTION	VII
RISK CATEGORY	III

REFER TO SECTION 01 23 00 IN SPECIFICATIONS FOR LIST AND DESCRIPTION OF ALTERNATE BIDS

****NOTE: THIS JOB CANNOT BE ACCURATELY BID WITHOUT SITE VERIFICATION BY ALL TRADES PRIOR TO BIDS. ALL SUPPLIER & SUB-CONTRACTORS ARE ENCOURAGED TO REVIEW ALL SHEETS IN PLANS AS SOME SHEETS WILL CONTAIN WORK BY MULTIPLE TRADES.**


GENERAL NOTES:

- The intent of these drawings and specifications is to include all labor, materials, and services necessary for completion of all work shown, prescribed, or reasonably implied but not limited to that explicitly indicated in the contract documents.
- All work shall conform to all applicable building codes, ordinances, and regulations as adopted by local authorities having jurisdiction.
- Structural, mechanical, electrical, plumbing, civil, and landscape drawings are supplemental to the architectural drawings. The sub-contractor shall review all plans and drawings prior to Bids or rely on the General Contractor to provide them with the drawing sheets affecting their trade. In the event of conflicting statements, insufficient information, or errors, the contractor shall immediately notify the architect and obtain clarification before Bidding and before any work has begun. During Bidding, Contractor shall comply with Sections 01 42 00 & 01 45 00. Work installed where conflicting conditions are not brought to the architect's attention prior to installation of the work shall be corrected at contractors expense. Note that there is some overlap between the Architectural and Structural Designs and where there is a conflict, the more stringent and more expensive of the two shall govern.
- Details noted as typical shall be applied to all like conditions unless specifically shown or noted otherwise. Where no specific detail is shown, the framing or construction shall be identical or similar to that indicated for like cases of construction in this project.
- The general contractor and all subcontractors shall verify all dimensions and conditions on the job site prior to beginning construction and report any discrepancies or identified conditions to the architect for resolution before any work is begun. The contractor shall be responsible for maintenance, methods, techniques and procedures employed in the performance of the work in, on, what about the job site; the contractor shall coordinate and verify all work performed by subcontractors.
- All contractors and subcontractors performing work on, or related to this project shall conduct their operations so that all employees are provided a safe place to work and the public is protected, and shall comply with the "occupational and safety health act" of the U.S. Department of Labor and with any and all other applicable state and/or local safety regulations. The contractor agrees to assume sole and complete responsibility for the jobsite safety conditions and that the contractor shall defend, indemnify, and hold harmless the owner and architect from any and all liability, real or alleged, in the connection with performance of work on the project.
- The Contractor is responsible for compliance with the Contract Documents and the Architect shall make periodic observations to the jobsite but the architect shall not be responsible for the Contractor's failure to carry out the work in accordance with the Contract Documents.
- The structure is designed as a stable unit after all components are in place. The contractor shall provide all shoring and bracing necessary to ensure the stability of any and all parts of the building during construction.
- Unless specifically shown or noted on the drawings, no structural member shall be cut, notched, bored, or otherwise modified without permission of the arch.
- The contractor is responsible for confirming location of all site utilities and to coordinate and avoid conflict in the locations of new underground in site utilities. The contractor shall include all necessary fees, exploration equipment, time, leaders, and connections in his bid.
- Notwithstanding anything to the contrary here in, all work must also comply with applicable local, state, and federal laws in building codes and the Owner standards, specifications, and requirements.
- In the event of a conflict, or perceived conflict between these plans, the codes, and/or specifications, see Section 01 42 00. The most stringent & expensive requirements shall take precedent in the event of a conflict.
- In the event of a drawing discrepancy or missing drawing symbol or wording, comply with Section 01 45 00.
- All Trades are required to visit the site and existing buildings prior to Bids.
- All Suppliers and sub-contractors are encouraged to review ALL Plan Sheets as some Sheets contain Work by Many different trades.


LAND DISTRICT NORTH OF RED RIVER
SECTION 30, T-18-N, R-4-E
OUACHITA PARISH, LOUISIANA

T.B.M. NO.1: ELEV.=73.72' (NAVD-88)
COTTON SPINDLE SET IN POWER POLE LOCATED APPROXIMATELY 200' NORTH OF THE SOUTHWEST CORNER OF THE SUBJECT PROPERTY AS SHOWN HEREON.

FLOOD ZONE DATA:
BASED ON FLOOD INSURANCE RATE MAP NO. 22073C0165F (JANUARY 20, 2016), FOR OUACHITA PARISH, LOUISIANA, THE ENTIRE PROPERTY SHOWN HEREON LIES IN ZONE "X-SHADED", WHICH ARE DETERMINED TO BE AN AREA OF 0.2% ANNUAL CHANCE FLOOD; AREAS OF 1% ANNUAL CHANCE FLOOD WITH AVERAGE DEPTHS OF LESS THAN 1 FOOT OR WITH DRAINAGE AREAS LESS THAN 1 SQUARE MILE; AND AREAS PROTECTED BY LEVES FROM 1% ANNUAL CHANCE FLOOD.



SCALE: 1" = 20'



LEGEND

	TREE		FOUND MONUMENTATION
	BUSH		RIGHT-OF-WAY
	BARRICADE POST		DITCH TOP
	POWER DROP		DITCH CENTERLINE
	GAS VALVE		HEDGE LINE
	PIPELINE UTILITY MARKER		FLOWER BED
	SEWER MANHOLE		FENCE LINE
	SEWER CLEANOUT		OVERHEAD POWER LINE
	TRAFFIC SIGN		UNDERGROUND GAS LINE
	TELEPHONE CROSS CONNECT BOX		UNDERGROUND TELEPHONE LINE
	TELEPHONE PEDESTAL		UNDERGROUND FIBER OPTIC LINE
	TELEPHONE UTILITY MARKER		UNDERGROUND WATER LINE
	WATER VALVE		CONTOUR LINE
	WATER METER		
	FIRE HYDRANT		
	LIGHT POLE		
	POWER POLE		
	GUY WIRE		
	P.O.B.		CONCRETE
	POINT OF BEGINNING		ASPHALT
	FINISHED FLOOR ELEVATION		
	RIGHT-OF-WAY		

SURVEYOR'S NOTES:

- THE BEARINGS SHOWN HEREON ARE GRID BEARINGS AND ARE BASED ON GPS OBSERVATIONS TAKEN AT THE SITE. THE GRID BEARINGS ARE BASED ON THE LOUISIANA COORDINATE SYSTEM OF 1983 NORTH ZONE. THE REFERENCE BEARING WAS TAKEN ALONG THE SOUTH LINE OF THE SUBJECT PROPERTY AS SHOWN HEREON.
- THE ELEVATIONS SHOWN HEREON ARE BASED ON CONTROL POINT LAZ 2 HAVING AN ELEVATION OF 79.71' (NAVD-88) AND WERE TRANSFERRED TO THE SITE USING GPS.
- THE EXISTING UTILITIES, BOTH ABOVE GROUND AND SUBSURFACE, ARE SHOWN ON THE PLAT AS DETERMINED FROM FIELD SURVEYS AND AVAILABLE FILES AND RECORDS. THE LOCATION, SIZE, EXISTENCE, OR NONEXISTENCE OF UTILITIES IS NOT WARRANTED BY THE SURVEYOR. THERE ARE ADDITIONAL UTILITIES LOCATED WITHIN THE LIMITS OF THE SUBJECT TRACT THAT ARE NOT SHOWN ON THIS PLAT.
- NO TITLE RESEARCH WAS REQUESTED OR PERFORMED TO LOCATE ANY EXISTING RIGHTS-OF-WAY, EASEMENTS, OR RESTRICTIONS THAT ENCLUMBER THE SUBJECT PROPERTY.
- THE PROPERTY IS SUBJECT TO MULTIPLE EASEMENTS AND CONTRACTS REGARDING ACCESS, MAINTENANCE, ETC. THAT ARE RECORDED IN CONVEYANCE BOOK 875 AT PAGE 148, CONVEYANCE BOOK 900 AT PAGE 337, AND CONVEYANCE BOOK 1548 AT PAGE 117.
- THE LOCATION OF THE WATER MAIN SHOWN IS APPROXIMATE AND WAS GRAPHICALLY PLOTTED FROM THE CITY OF MONROE GIS SYSTEM.
- THERE ARE MULTIPLE LOCATIONS THAT WILL REQUIRE CROSS ACCESS EASEMENTS FOR VEHICLES, UTILITIES AND DRAINAGE. SOME REQUIRED EASEMENTS WILL CROSS THE SUBJECT TRACT WHILE OTHER LOCATIONS ARE LOCATED ON ADJACENT TRACTS. THE AGREEMENT SHOULD ALSO ADDRESS FUTURE MAINTENANCE.

CERTIFICATION
I, RONALD J. RIGGIN, II, P.L.S., A LICENSED PROFESSIONAL SURVEYOR IN THE STATE OF LOUISIANA, DO HEREBY CERTIFY THAT I HAVE PERFORMED A CLASS "B" SURVEY IN ACCORDANCE WITH THE STANDARDS OF PRACTICE FOR PROPERTY BOUNDARY SURVEYS AS ESTABLISHED BY THE LOUISIANA PROFESSIONAL ENGINEERING AND LAND SURVEYING BOARD AND TO THE BEST OF MY KNOWLEDGE THIS IS A TRUE REPRESENTATION OF THAT SURVEY.
Ronald J. Riggins 1-27-23
RONALD J. RIGGIN, II, P.L.S. NO. 5119 DATE

BOUNDARY & TOPOGRAPHIC SURVEY
PROPOSED OUACHITA PARISH PUBLIC LIBRARY
1000 OLIVER ROAD, MONROE, LA 71201
SITUATED IN SECTION 30, T-18-N, R-4-E
LAND DISTRICT NORTH OF RED RIVER
OUACHITA PARISH, LOUISIANA

DESIGNED R.J.R.	CHECKED R.J.R.	CLIENT:
DRAWN B.A.M.	CHECKED R.J.R.	OUACHITA PARISH
APPROVED	DATE JAN., 2023	POLICE JURY
JOB NO. 225057.00	SCALE 1" = 20'	

OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA

LAND 3
Architect

LAND 3
ARCHITECT, INC.
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA.
71201-5766



DRAWN BY:
CHK'D BY:
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED

ORIGINAL
SITE SURVEY


SP1.0

SHEET SIZE: 24 X 36 SCALE: 1" = 20'-0"

LAND DISTRICT NORTH OF RED RIVER
SECTION 30, T-18-N, R-4-E
OUACHITA PARISH, LOUISIANA

T.B.M. NO. 1: ELEV.=73.72' (NAVD-88)

COTTON SPINDLE SET IN POWER POLE LOCATED APPROXIMATELY 200' NORTH OF THE SOUTHWEST CORNER OF THE SUBJECT PROPERTY AS SHOWN HEREON.



SITE DEMOLITION PLAN

SCALE: 1" = 20'
NORTH REF.

UTILITIES CONTACTED BY LA ONE CALL

TICKET NO. 220807030 DATE: NOVEMBER 30, 2022
LOCATION OF UTILITIES SHOWN WERE MARKED BY UTILITY COMPANIES BELOW:

- | | | |
|--|---|---|
| CITY OF MONROE (SEWER)
1200 GRAMMONT STREET
MONROE, LA 71201
CHARLES WESTROM
318-329-3363 | AT&T - TELEPHONE
301 CATALPA STREET
MONROE, LA 71201
STACY WELCH
318-398-1526 | CONTRERA BROADBAND
2528 LA 115
MANSURA, LA 71360
ZACKERY SANDERS
318-657-1051 |
| ENTERGY - ELECTRICITY
2901 CYPRESS STREET
WEST MONROE, LA 71291
MIKE WILSON
318-801-6253 | COMCAST CABLE COMMUNICATIONS - CABLEVISION
405 KIROLI ROAD
WEST MONROE, LA 71291
MARK CHASTAINE
318-235-6852 | NEWWAVE COMMUNICATIONS
7121 OLD STERLINGTON ROAD
MONROE, LA 71203
TROY BELL
318-329-3811 |
| UNITI FIBER - FIBER/COMMUNICATIONS
363 VENABLE LANE
MONROE, LA 71203
ROBERT BERGERON
318-372-8533 | CENTURYLINK COMMUNICATIONS
P.O. BOX 1250
JENA, LA 71342
BILL NORRIS
318-492-1084 | CITY OF MONROE (WATER)
2401 NORTH 10TH STREET
MONROE, LA 71203
TROY BELL
318-329-3811 |
| | | ATMOS ENERGY - GAS
800 DELTA DRIVE
MONROE, LA 71203
ARSHIELD CAREY
318-651-8338 |

SITE DEMOLITION PLAN REF. NOTES

1. EXISTING CONCRETE BASE FOR PLANTER, ROUND PLANTER ON BASE, ADJACENT CURVED RAMPS INCLUDING CURBS FOR THESE RAMPS TO BE REMOVED FROM ISLAND AT THIS AREA. (EXISTING CURB AROUND ISLAND SHALL REMAIN, PATCH EXISTING CURB WHERE DAMAGED DUE TO REMOVAL OF EXISTING CONSTRUCTION INDICATED.)
2. CAREFULLY REMOVE ALL EXISTING CONCRETE PAVING AND CONCRETE RAMP AT ASPHALT DRIVE SHOWN.
3. EXISTING HOSE BIBB AND DRAIN PIPE TO BE EXTENDED OUT TO NEW FACE BRICK FOR CANOPY AROUND ISLAND SHALL REMAIN. PATCH EXISTING CURB WHERE DAMAGED DUE TO REMOVAL OF EXISTING CONSTRUCTION INDICATED.
4. REMOVE EXISTING HANDICAPPED PARKING SIGNAGE. CLEARLY CUT OFF EXISTING POSTS LEVEL WITH FACE OF PAVING, FOOTING BELOW PAVING SHALL REMAIN.
5. CAREFULLY REMOVE AND RETAIN ALL PARKING LOT SIGNAGE INDICATED BY THIS REF. NOTE. ONCE ALL NEW PAVING WORK HAS BEEN COMPLETED RE-INSTALL SIGNAGE IN PARKING AREAS AS SHOWN ON SITE IMPROVEMENT PLAN ON SHEET SP.2

SITE DEMOLITION PLAN NOTES

- REFER TO SECTION 02 41 13.
- REFER TO SPECIFICATION SECTIONS AND DRAWING SHEETS WHICH MAY INDICATE NEW WORK TO REPLACE EXISTING WORK THAT IS NOT INDICATED ON THIS PLAN.
- REFER TO SITE PLAN DETAILS ON SHEET SP.2 FOR DESIGN OF NEW CONCRETE AND WALKWAY CONSTRUCTION WHICH WILL DICTATE EXTENTS OF SOIL/PAVING REMOVAL.
- REPLACE EXISTING MATERIALS WHERE DAMAGED DUE TO REMOVAL OF EXISTING MATERIALS TO ACCOMMODATE NEW WORK.
- GENERAL CONTRACTOR SHALL NOT BEGIN EXCAVATION OR DEMOLITION WITHOUT FIRST CONTACTING "LOUISIANA ONE CALL" (1-800-272-3020) AND REQUEST APPROXIMATE LOCATIONS OF EACH UNDERGROUND UTILITY.
- REFER TO MECHANICAL, ELECTRICAL, AND PLUMBING SHEETS FOR ADDITIONAL WORK THAT MAY REQUIRE SITE DEMOLITION.

THERE IS A STRONG POSSIBILITY THAT EXISTING U/G UTILITY LINES ARE PRESENT AND MAY NOT BE SHOWN ON SHEET. ALL UNDERGROUND UTILITIES THAT ARE IN USE BY SURROUNDING PROPERTIES MUST REMAIN OPERATIONAL DURING CONSTRUCTION. CONTRACTOR SHALL NOTIFY ARCHITECT AND PROMPTLY REPAIR ANY EXISTING MEP PIPING/CONDUITS THAT ARE ENCOUNTERED/DAMAGED DURING DEMOLITION WORK.

REFER TO ALL SHEETS MARKED SP. FOR BUILDING, PAVING, DRAINAGE, AND LANDSCAPING IMPROVEMENTS WHICH MAY REQUIRE ADDITIONAL DEMOLITION WORK.

GENERAL CONTRACTOR SHALL FILL ALL HOLES/VOIDS LEFT BY REMOVAL OF EXISTING MATERIALS WITH NEW MATERIALS TO MATCH EXISTING ADJACENT MATERIALS.

SAW-CUT AND PATCH EXISTING PAVING/WALKS WHERE REQUIRED FOR NEW SITE UTILITIES AT SCHEDULED MECHANICAL & ELECTRICAL EQUIPMENT.


GENERAL NOTES:

NOTIFY LA ONE CALL 48 HOURS PRIOR TO ANY DIGGING OR EXCAVATION WORK.

DIAL #811
OR GO ONLINE WWW.LAONECALL.COM

SOME OF THE SURVEY INFORMATION HAS BEEN DELETED FROM THIS SHEET FOR THE PURPOSE OF CLARITY. SEE ORIGINAL SITE SURVEY ON SHEET SP.0 FOR ALL EXISTING CONDITIONS AND EXISTING GRADES.

OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA



LAND 3 ARCHITECT, INC.
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA 71201-5786



DRAWN BY: LOH
CHKD BY: WAL
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED


SITE
DEMOLITION PLAN

SP1.1

LAND DISTRICT NORTH OF RED RIVER
SECTION 30, T-18-N, R-4-E
OUACHITA PARISH, LOUISIANA

T.B.M. NO. 1: ELEV.=73.72' (NAVD-88)

COTTON SPINDLE SET IN POWER POLE LOCATED APPROXIMATELY 200' NORTH OF THE SOUTHWEST CORNER OF THE SUBJECT PROPERTY AS SHOWN HEREON.



SITE IMPROVEMENT PLAN
SCALE: 1" = 20'-0"
NORTH REF.

FOUND 3/4" IRON PIPE AT THE SOUTHWEST CORNER OF LOT 4 OF SECTION 30, T-18-N, R-4-E, OUACHITA PARISH, LOUISIANA (P.B. & P. 53) (FOUND 8" REBAR 564'39.48'-E-0.72')

FOUND 12" REBAR AT THE INTERSECTION OF THE NORTH RIGHT-OF-WAY LINE OF LOUISVILLE AVENUE AND THE EAST RIGHT-OF-WAY LINE OF OLIVER ROAD

LOUISVILLE AVENUE (U.S. HWY. 80) (R.D.W.)

- SITE IMPROVEMENT PLAN REF. NOTES**
- EXISTING ASPHALT PARKING LOT SHALL BE REPAIRED, MILLED, AND FULLY OVERLAIN PER SECTION 32.12.16 OF SPECIFICATIONS AND LDDTD REQUIREMENTS. SEE DETAIL J/S22.1. (THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING ALL EXISTING CONDITIONS AND ALL DIMENSIONS/MEASUREMENTS. THIS INFORMATION PROVIDED IN THE BID DOCUMENTS IS FOR GENERAL INFORMATION PURPOSES ONLY. THE CONTRACTOR SHALL FIELD VERIFY ALL NECESSARY CONDITIONS AND DIMENSIONS PRIOR TO SUBMITTING A BID.)
 - UPON COMPLETION OF ASPHALT OVERLAY FOR EXISTING PARKING LOT PROVIDE NEW 4" WIDE WHITE PAINTED PARKING STRIPING, SYMBOLS, TRAFFIC DIRECTIONAL ARROWS, LETTERING, ETC... AT AREAS SHOWN ON PLAN. (SEE SECTION 09.90.00 IN SPECIFICATIONS.)
 - EXISTING MOBILE SIGNAGE WITH CONCRETE BASE TO BE RE-LOCATED TO AREAS SHOWN ON PLANS, VERIFY ORIENTATION WITH ARCHITECT PRIOR TO INSTALLATION. ALL POSTS FOR EACH SIGN SHALL BE PAINTED GREEN AND CONCRETE BASE FOR EACH SIGN SHALL BE PAINTED WITH TRAFFIC YELLOW PAINT PER SECTION 09.90.00.
 - EXISTING STOP SIGN
 - EXISTING PEDESTRIAN SIGN
 - EXISTING RESERVED SIGN
 - NEW CONCRETE PAVING/DRIVE AT AREAS SHOWN, SEE DETAIL J/S22.1
 - ALL LANDSCAPING, TREES, PLANTS, SOD, ETC... IN THIS EXISTING ISLAND SHALL REMAIN. (REPLACE ONLY WHERE DAMAGED DUE TO NEW CONSTRUCTION)
 - AT STAFF PARKING AREA SHOWN PROVIDE FIELD VERIFY ALL NECESSARY CONDITIONS AND DIMENSIONS PRIOR TO SUBMITTING A BID.
 - NEW FLAGS BY SECTION 10.10.00 INSTALLED ON EXISTING POLES IN PLANTER BOX
 - NEW 4" WIDE TRAFFIC YELLOW PAINT STRIPE AT RETAINING WALL & EDGES OF RAMP TO DETER TRIPPING HAZARD.
 - NEW 4" WIDE TRAFFIC YELLOW PAINT STRIPE AT PAVING TO WALK TRANSITION TO DETER TRIPPING HAZARD.
 - NEW SITE SIGN WITH GRAPHICS FACING OLIVER ROAD, VERIFY EXACT TO BE INSTALLED.
 - MODIFY/LOWER OR RE-LOCATE ALL ACTIVE UTILITY BOXES, TRANSITIONS, PIPING, CONDUIT, CLEAN-OUTS, METERS, ETC... AS NECESSARY TO PREVENT INTERFERENCE WITH NEW SCHEDULED WORK. VERIFY TOTAL VISIBLE NUMBER AND INCLUDE ALL COST IN BID FOR THIS WORK.
 - REFER TO DIVISIONS 31.32, & 33 IN SPECIFICATIONS.
 - REFER TO SHEET SP2.1 FOR SITE DETAILS.
 - REFER TO PLUMBING, MECHANICAL, AND ELEC. SHEETS FOR NEW UTILITY LOCATIONS VERIFY LOCATION, SIZE, DEPTH, ETC. OF ALL EXISTING UTILITIES PRIOR TO BIDDING AND INCLUDE COST IN BID TO WORK AROUND ALL EXISTING UTILITIES. NOTIFY ARCHITECT OF ALL CONFLICTS.
 - REFER TO FLOOR PLANS FOR DIMENSIONS OF NEW LANDINGS/RAMP AT EXTERIOR DOORS IF NOT INDICATED ON THIS PLAN.
 - GENERAL CONTRACTOR (GC) SHALL APPLY AND PAY FOR ALL REQUIRED BUILDING PERMITS AND IT SHALL BE THE BIDDERS RESPONSIBILITY TO VERIFY WHICH REGULATORY AGENCIES, DEPARTMENTS, ETC. REQUIRE BUILDING PERMITS AND THE AMOUNTS.
 - PROPERLY RE-LOCATE & CAP OFF ANY AND ALL EXISTING UTILITY LINES WHICH ARE LEFT AS A RESULT OF DEMOLITION WORK.
 - ALL VOIDS IN EXISTING GRADE LEFT BY THE REMOVAL OF EXISTING MATERIALS SHALL BE FILLED AND COMPACTED IN ACCORDANCE WITH SPECIFICATIONS.
 - ALL PAINTING SHOWN SHALL BE BY SECTION 09.90.00 IN SPECS.
 - PROVIDE POSITIVE FINISHED GRADING AROUND ALL NEW CONSTRUCTION TO SLOPE AWAY FROM BUILDINGS.
 - ALL EXISTING CONCRETE PAVING, SIDEWALKS, & LANDINGS SHALL BE PRESSURE WASHED.

- SITE IMPROVEMENT NOTES:**
- SITE VERIFY ALL EXISTING CONDITIONS PRIOR TO BIDDING.
 - MODIFY/LOWER OR RE-LOCATE ALL ACTIVE UTILITY BOXES, TRANSITIONS, PIPING, CONDUIT, CLEAN-OUTS, METERS, ETC... AS NECESSARY TO PREVENT INTERFERENCE WITH NEW SCHEDULED WORK. VERIFY TOTAL VISIBLE NUMBER AND INCLUDE ALL COST IN BID FOR THIS WORK.
 - REFER TO DIVISIONS 31.32, & 33 IN SPECIFICATIONS.
 - REFER TO SHEET SP2.1 FOR SITE DETAILS.
 - REFER TO PLUMBING, MECHANICAL, AND ELEC. SHEETS FOR NEW UTILITY LOCATIONS VERIFY LOCATION, SIZE, DEPTH, ETC. OF ALL EXISTING UTILITIES PRIOR TO BIDDING AND INCLUDE COST IN BID TO WORK AROUND ALL EXISTING UTILITIES. NOTIFY ARCHITECT OF ALL CONFLICTS.
 - REFER TO FLOOR PLANS FOR DIMENSIONS OF NEW LANDINGS/RAMP AT EXTERIOR DOORS IF NOT INDICATED ON THIS PLAN.
 - GENERAL CONTRACTOR (GC) SHALL APPLY AND PAY FOR ALL REQUIRED BUILDING PERMITS AND IT SHALL BE THE BIDDERS RESPONSIBILITY TO VERIFY WHICH REGULATORY AGENCIES, DEPARTMENTS, ETC. REQUIRE BUILDING PERMITS AND THE AMOUNTS.
 - PROPERLY RE-LOCATE & CAP OFF ANY AND ALL EXISTING UTILITY LINES WHICH ARE LEFT AS A RESULT OF DEMOLITION WORK.
 - ALL VOIDS IN EXISTING GRADE LEFT BY THE REMOVAL OF EXISTING MATERIALS SHALL BE FILLED AND COMPACTED IN ACCORDANCE WITH SPECIFICATIONS.
 - ALL PAINTING SHOWN SHALL BE BY SECTION 09.90.00 IN SPECS.
 - PROVIDE POSITIVE FINISHED GRADING AROUND ALL NEW CONSTRUCTION TO SLOPE AWAY FROM BUILDINGS.
 - ALL EXISTING CONCRETE PAVING, SIDEWALKS, & LANDINGS SHALL BE PRESSURE WASHED.

GENERAL NOTES:

NOTIFY LA ONE CALL 48 HOURS PRIOR TO ANY DIGGING OR EXCAVATION WORK.

DIAL #811
OR GO ONLINE WWW.LAONECALL.COM

SOME OF THE SURVEY INFORMATION HAS BEEN DELETED FROM THIS SHEET FOR THE PURPOSE OF CLARITY. SEE ORIGINAL SITE SURVEY ON SHEET SP1.0 FOR ALL EXISTING CONDITIONS AND EXISTING GRADES.

**OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA**


**LAND 3
Architect**

LAND 3 ARCHITECT, INC.
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA
71201-5786

WILLIAM A. P. NO. 4155
REGISTERED ARCHITECT
STATE OF LOUISIANA


DRAWN BY: LOH
CHK'D BY: WAL
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED

SITE IMPROVEMENT PLAN
SP1.2




A REPAVE ASPHALT (OVERLAY)

- SITE VERIFY EXISTING CONDITIONS AND DIMENSIONS SCALE: NTS
- SEE SECTION 32 12 16 FOR REQUIREMENTS




B NEW CONCRETE PAVING

- SITE VERIFY EXISTING CONDITIONS AND DIMENSIONS SCALE: NTS




C CONCRETE WALK PATCH AT NEW EXTERIOR UTILITIES

- SEE M.E.P. SHEETS FOR UTILITY LOCATIONS. SCALE: NTS




D CAUTION PAINT STRIPING

- APPLIES TO ALL WALKS AND LANDINGS THIS PROJECT
- SITE VERIFY TOTAL NUMBER OF TRANSITIONS SCALE: NTS




PLAN @ SINGLE DOOR SEE DOOR LANDINGS MARKED (LL)
PLAN @ DOUBLE DOOR SEE DOOR LANDINGS MARKED (LL)


E NEW LEVEL LANDING DETAIL




H PIPE BOLLARD DETAIL SCALE: NTS




I ALUMINUM CANOPY DETAIL SCALE: NTS




F HANDICAP PARKING SIGN & SYMBOL SCALE: NTS




G SOD DETAIL SCALE: NTS




K ACCESSIBLE RAMP DETAIL SCALE: NTS




L ASPHALT PAVEMENT REPAIR AT NEW EXTERIOR UTILITIES SCALE: NTS



N ASPHALT PATCH DETAIL SCALE: NTS



M SPEED BUMP SCALE: NTS



J PROJECT SIGN SCALE: NTS

SHEET SIZE: 24 X 36 SCALE: 1/8" = 1'-0"

**OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA**

**LAND 3
Architect**

**LAND 3
ARCHITECT, INC.**
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA.
71201-5786



DRAWN BY: LOH
CHK'D BY: WAL
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED

SITE DETAILS

SP2.1

DEMOLITION REFERENCE NOTES:

- THE FOLLOWING ITEMS ARE PROVIDED FOR GENERAL PURPOSES AND INDICATE THE TYPICAL TYPES OF DEMOLITION REQUIRED. THE CONTRACTOR SHALL REVIEW THE COMPLETE BID DOCUMENTS AND SITE VERIFY PRIOR TO BIDS ANY ADDITIONAL MATERIALS WHICH ARE IN CONFLICT WITH NEW WORK INDICATED IN THE BID DOCUMENTS. IT SHALL BE THE GENERAL CONTRACTOR'S RESPONSIBILITY TO REMOVE ALL DEMOLITION WORK NOT SPECIFICALLY INDICATED TO BE REMOVED BY A PARTICULAR SUB-CONTRACTOR.
- REMOVE PORTION OF EXISTING INT. WALL SHOWN INCLUDING ALL SHEET-ROCK, STUD FRAMING, DOORS, DOOR FRAMES, HEADERS FOR DOOR OPENINGS, OUTLETS, LIGHT SWITCHES, ETC.... UP TO 9'-0" IN HEIGHT. PATCH ALL ADJACENT EXISTING CONST. THAT IS TO REMAIN WHERE DAMAGED DUE TO DEMOLITION WORK. CAP ELEC. & RE-LOCATE LIGHT SWITCH TO NEAREST ADJ. WALL (UON ON ELEC. SHEETS. PROVIDE TEMPORARY SHORING/BRACING AS REQUIRED FOR SUPPORT OF REMAINING WALL ABOVE.)
 - REMOVE PORTION OF EXISTING EXTERIOR WALL PATCH SHOWN FOR NEW EXTERIOR DOORS/SIDELITES SCHEDULED FOR THIS AREA. PATCH ALL ADJACENT EXISTING CONSTRUCTION THAT IS TO REMAIN WHERE DAMAGED DUE TO DEMOLITION WORK.
 - REMOVE EXISTING EXTERIOR WINDOW AWNING SYSTEM INCLUDING ALL ALUMINUM FRAMING, CLIPS, ANCHORS, AND CANVAS AWNING. PATCH ALL ADJACENT EXISTING CONSTRUCTION THAT IS TO REMAIN WHERE DAMAGED DUE TO REMOVAL OF THE AWNING SYSTEM. FILL ALL HOLES IN MASONRY LEFT BY REMOVAL OF ANCHORING CLIPS WITH SEALANT.
 - EXISTING EXTERIOR WALL, ALUMINUM FRAMING, EXTERIOR ENTRANCE DOORS INCLUDING FRAMES, SIDE-LITES, TRANSOM, DOOR GLASS, ALL DOOR HARDWARE, THRESHOLDS, CHANNEL SPACERS, CLIP ANGLES, WOOD BLOCKING, MOLDINGS, PANELS, STOPS, FLASHING, TRIM, & EXTERIOR SIDE-LITES, SHALL BE REMOVED. REMOVE EXISTING INTERCOM BOX ADJ. TO DOOR & CAP EXISTING POWER/DATA TO BOX ABOVE CEILING. EXISTING STEEL COLUMNS, STEEL BEAMS, AND CONCRETE FLOOR SLAB SHALL REMAIN. PATCH ALL ADJACENT EXISTING CONSTRUCTION THAT IS TO REMAIN WHERE DAMAGED DUE TO THIS DEMOLITION WORK.
 - ALTERNATE BID** - CAREFULLY REMOVE PORTION OF EXISTING EXTERIOR MASONRY WALL SHOWN FOR INSTALLATION OF NEW SCH. EXT. WINDOW & STEEL LINTEL. SEE WINDOW SCHEDULE & FLOOR PLAN FOR EXTENT OF NEW WORK. PATCH ALL EXISTING CONSTRUCTION WHERE DAMAGED DUE TO DEMO WORK. PROVIDE TEMPORARY SHORING/BRACING WHERE REQUIRED FOR SUPPORT OF EXT. WALL.
 - CAREFULLY REMOVE PORTION OF EXISTING EXTERIOR MASONRY WALL SHOWN FOR INSTALLATION OF NEW SCH. EXT. DOOR & STEEL LINTEL. SEE DOOR SCHEDULE & FLOOR PLAN FOR EXTENT OF NEW WORK. PATCH ALL EXISTING CONSTRUCTION WHERE DAMAGED DUE TO DEMO WORK. PROVIDE TEMPORARY SHORING/BRACING WHERE REQUIRED FOR SUPPORT OF EXT. WALL.
 - EXISTING INTERIOR CONSTRUCTION SHOWN CONSISTING OF ALL WALLS, PANELING, WAINSCOT, DOORS, DOOR FRAMES, WOOD TRIM, WINDOWS, CURBS, MILLWORK, WALL MOUNTED GRILLES, CEILING TILE, CEILING GRID, ETC.... SHALL BE REMOVED FROM INTERIOR AREAS INDICATED. SEE M.E.P. SHEETS FOR EXTENT OF EXISTING ITEMS THAT ARE TO BE REMOVED OR RE-LOCATED FOR MECH., ELEC., AND PLUMBING. PROPERLY CAP ALL UTILITIES THAT WILL NOT BE RE-USED. SEE M.E.P. SHEETS. PATCH ALL ADJACENT EXISTING CONSTRUCTION THAT IS TO REMAIN WHERE DAMAGED DUE TO DEMOLITION WORK. (PROVIDE TEMPORARY SHORING/BRACING AS NECESSARY.)
 - EXISTING FREIGHT ELEVATOR INCLUDING ALL ASSOCIATED FRAMING, PISTONS, DOORS, DOOR FRAMES, GUIDE RAILS, CONTROLS, PUMP MOTOR, ASSOCIATED CONDUIT/WIRING, ALL SHAFT WALLS, ETC.... SHALL BE REMOVED TO ACCOMMODATE ELEVATOR SCH. FOR COMPLETE AND PATCH ALL ADJACENT EXISTING CONSTRUCTION THAT IS TO REMAIN WHERE DAMAGED DUE TO DEMOLITION WORK. (PROVIDE TEMPORARY SHORING/BRACING AS NECESSARY.)
 - EXISTING MILLWORK, SHELVING, BRACKETS, STANDARDS, ETC.... INCLUDING ALL RELATED ATTACHED MATERIALS SHALL BE REMOVED. PATCH ALL ADJACENT EXISTING CONSTRUCTION THAT IS TO REMAIN WHERE DAMAGED DUE TO DEMOLITION WORK.
 - THIS PORTION OF EXISTING PROJECTED CURVED BUILDING OVERHANG & ASSOCIATED ROOFING SHOWN SHALL BE REMOVED INCLUDING ALL FLASHING, PASCIA, SOFFIT, LIGHTING, FRAMING, & ALL RELATED MATERIALS. PATCH ALL ADJACENT EXISTING CONSTRUCTION THAT IS TO REMAIN WHERE DAMAGED DUE TO DEMOLITION WORK.
 - REMOVE ENTIRE EXISTING EXTERIOR DISPLAY WINDOW UNIT INCLUDING ROOF, ROOF FRAMING, ALUMINUM FRAMING SYSTEM, ALL GLASS, STUD WALLS, ELEC. OUTLETS, CONDUIT, PLATFORM, FRAMING FOR RAISED PLATFORM, FLOORING, BRICK BASE BELOW WINDOW, TO MAKE WAY FOR NEW SCHEDULED WORK THIS AREA. PROPERLY CAP ALL UTILITIES THAT WILL NOT BE RE-USED. PATCH ALL ADJACENT EXISTING CONSTRUCTION THAT IS TO REMAIN WHERE DAMAGED DUE TO DEMOLITION WORK.
 - REMOVE 4' WIDE X 7' HIGH PORTION OF EXISTING WALL SHOWN TO CREATE A NEW WALL OPENING AS SHOWN ON SHEET A1.1. PATCH ALL ADJ. CONST. WHERE DAMAGED DUE TO REMOVAL OF MATERIALS FOR OPENING.
 - AT OPENING INDICATED REMOVE ALL WOOD TRIM AND CASING FRAME FROM OPENING. REMAINING WALL OPENING SHALL BE PATCHED AS SHOWN ON SHEET A1.1. PATCH ALL ADJACENT EXISTING CONSTRUCTION THAT IS TO REMAIN WHERE DAMAGED DUE TO DEMOLITION WORK.
 - EXISTING EXTERIOR WINDOWS AT WEST WALL SHALL REMAIN UNDER BASE BID. UNDER ALTERNATE BID REMOVE EXISTING EXTERIOR WINDOW AND PORTION OF EXISTING MASONRY WALL BELOW WINDOW. SEE FLOOR PLAN, WINDOW SCH., AND EXT. ELEVATIONS FOR EXTENT OF DEMOLITION WORK REQUIRED. (UNDER ALTERNATE BID PATCH ALL ADJ. EXISTING CONSTRUCTION THAT IS TO REMAIN WHERE DAMAGED DUE TO DEMOLITION WORK THIS AREA.)
 - REMOVE PORTION OF EXISTING WALL INCLUDING ALL STUD FRAMING, DRYWALL, OUTLETS, CONDUIT, LIGHT SWITCHES, ETC.... TO ACCOMMODATE NEW SCHEDULED WALL OPENING AT THESE AREAS. PROPERLY CAP ALL UTILITIES THAT WILL NOT BE RE-USED AND PATCH ALL ADJACENT EXISTING CONSTRUCTION THAT IS TO REMAIN WHERE DAMAGED DUE TO THIS DEMOLITION WORK.
 - REMOVE EXISTING STAIR INCLUDING HANDRAILS, ALL FRAMING, FLOORING, & ALL ASSOCIATED MATERIALS TO STAIR. REMOVE ENTIRE ATTIC FOR THIS AREA INCLUDING ALL ASSOCIATED FLOOR JOISTS, FLOOR DECKING, ETC.... PATCH ALL ADJACENT EXISTING CONSTRUCTION THAT IS TO REMAIN WHERE DAMAGED DUE TO DEMOLITION WORK THIS AREA.
 - REMOVE BATHROOM INCLUDING ALL WALLS, CEILINGS, FIXTURES, ETC.... (EXISTING SEWER & WATER LINES SHALL REMAIN FOR NEW SINKS AND JANITOR CLOSET FOR THIS AREA, SEE ENGINEER'S M.E.P. SHEETS FOR EXTENT OF UTILITY WORK.)

DEMOLITION GENERAL NOTES

REFER TO SECTION 02 41 19 IN THE SPECIFICATIONS

DEMOLITION PLANS ARE PROVIDED TO INDICATE GENERAL TYPES OF DEMOLITION THAT IS REQUIRED TO BE PERFORMED BUT BY NO MEANS LIMITS THE REQUIRED DEMOLITION. THE GENERAL CONTRACTOR IS RESPONSIBLE FOR REMOVAL OF ALL EXISTING MATERIALS THAT WOULD OTHERWISE INTERFERE WITH ALL NEW WORK INDICATED IN PLANS.


- SITE VERIFY ALL VISIBLE CONDITIONS AT FACILITY PRIOR TO BIDS.**
- THE GENERAL CONTRACTOR SHALL VERIFY ALL EXISTING DIMENSIONS, CONDITIONS, AND AREAS AT PROJECT SITE PRIOR TO BIDDING.
 - REFER TO SITE PLAN SHEETS FOR ADDITIONAL SITE DEMOLITION WORK THAT MAY NOT BE INDICATED ON PLAN.
 - THE GENERAL CONTRACTOR SHALL PATCH ALL SURFACES WHERE DEMOLITION WORK OCCURS. PATCH/LEVEL CONCRETE SURFACES THAT ARE UNEVEN OR DAMAGED.
 - SEE M.E.P. DRAWINGS AND SPECS. FOR NEW ITEMS TO REPLACE EXISTING. THE GENERAL CONTRACTOR SHALL PATCH ALL HOLES WHERE EXISTING ELECTRICAL PIPING OR CONDUIT IS REMOVED. WHERE EXISTING M.E.P. ITEMS ARE REMOVED VOIDS SHALL BE PATCHED WITH MATCHING MATERIALS. IF OPENINGS ARE IN A RATED WALL THEY ARE TO BE FILLED WITH AN APPROPRIATE U.L. LISTED FIRE RATED MATCHING MATERIALS.
 - REMOVE ALL EXISTING CONSTRUCTION THAT WOULD OTHERWISE INTERFERE WITH NEW WORK OF ANY KIND OR INTERIOR AND EXTERIOR OF BUILDINGS.
 - ALL CERAMIC TILE OR EXPOSED FINISH MATERIAL REQUIRED TO BE REMOVED SHALL BE NEATLY CUT AT THE JOINT IN A STRAIGHT LINE. NO TOOTHING OR JAGGED EDGES ALLOWED. ANY CEILING TILE PIECES DAMAGED AS A RESULT OF THIS PROJECT SHALL BE COMPLETELY REPLACED.
 - REMOVE EXISTING BASE (RUBBER, WOOD, ETC) AT ALL AREAS WHERE NEW BASE IS INDICATED TO BE INSTALLED.
 - MOVE ALL REMAINING FURNITURE IN BUILDING NOW INTO A ROOM AS NEEDED UNTIL PROJECT IS COMPLETE. INSTALL THIS FURNITURE IN ROOMS WHERE DIRECTED BY OWNER.
 - SCRAPE, CLEAN, PREP, AND PRIME EXISTING TERRAZZO FLOORING AS NEEDED FOR PROPER INSTALLATION OF NEW FLOOR FINISHES. SITE VERIFY EXISTING CONDITIONS PRIOR TO BIDS.
 - AT ALL INTERIOR STUD PARTITIONS THAT ARE REMOVED, GRIND ALL EXPOSED ANCHOR BOLTS SMOOTH/FLUSH WITH TOP OF EXISTING SLAB. PATCH SLAB WHERE DAMAGED DUE TO WALL & SILL PLATE REMOVAL. AT INTERIOR CMU PARTITIONS THAT ARE REMOVED, EXISTING EXPOSED FASTENERS, RE-BAR, OR BOLTS AT SLAB LEFT BY REMOVAL OF CMU SHALL BE CUT-OFF SMOOTH/LEVEL WITH EXISTING FLOOR SLAB & GROUND OFF SMOOTH WITH SURFACE OF FINISHED FLOORING.
 - DURING DEMOLITION CARE SHALL BE TAKEN TO PROTECT ALL EXISTING ITEMS/MATERIALS THAT ARE TO REMAIN. REPLACE/REPAIR ALL DAMAGED MATERIALS AS A RESULT OF DEMOLITION THIS PROJECT.
 - PROVIDE TEMPORARY SHORING/BRACING WHERE REQUIRED TO SUPPORT EXISTING CONSTRUCTION FROM DEFLECTION, DAM MEMBRANES AND LEVELERS AS NEEDED FOR DOORS, OR WINDOWS ARE INDICATED TO BE REMOVED
 - ALL REMOVED ITEMS OF VALUE SHALL REMAIN THE PROPERTY OF THE OWNER. THE CONTRACTOR SHALL BE RESPONSIBLE FOR DISPOSING OF REMOVED ITEMS ONLY AFTER GIVING THE OWNER THE OPPORTUNITY TO RETAIN ALL WANTED ITEMS.
 - LEGALLY DISPOSE OF ALL EXISTING FLUORESCENT BULBS THAT ARE STORED IN BUILDING OR CURRENTLY INSTALLED IN LIGHT FIXTURES UNLESS OTHERWISE NOTED.
 - REMOVE ALL EXISTING FLOOR FILLER MATERIALS AND LEVELING MATERIALS FROM EXISTING SLAB. GRIND, SMOOTH, AND PREP FLOOR JOISTS FOR INSTALLATION OF NEW FLOORING. INSTALL CRACK ISOLATION MEMBRANES AND LEVELERS AS NEEDED FOR SMOOTH AND LEVEL INSTALLATION OF NEW FLOORING. SITE VERIFY EXISTING CONDITIONS PRIOR TO BIDS AND INCLUDE ALL COSTS IN BID.
 - REMOVE AND DISPOSE OF ALL REMAINING MECHANICAL EQUIPMENT, DUCTWORK, & PIPING THAT INTERFERES WITH NEW WORK.

PATCH
DEFINITION OF PATCH- REPLACE REMOVED MATERIALS WITH NEW MATERIALS SIMILAR TO ADJACENT SURROUNDING MATERIALS & AS REQUIRED BY DETAILS ON THIS AND OTHER SHEETS. PROVIDE CAULK, SEALANT, ETC. AS REQUIRED FOR SECURE INSTALLATION & SMOOTH TRANSITION.

NOTE:
SEE PLUMBING, MECH., & ELEC. SHEETS FOR ADDITIONAL AREAS THAT REQUIRE SELECTIVE DEMOLITION DUE TO NEW WORK OR MAY REQUIRE SAWCUTTING OF EXISTING CONC. SLAB FOR NEW PLUMBING OR UTILITIES.


THE DEMOLITION PLAN SHEETS INDICATE WORK BY MANY TRADES SUCH AS MECHANICAL, ELECTRICAL, PLUMBING, PAINTING, ETC.

****ALTERNATE BIDS**
SEE SECTION 01 23 00 IN SPECS. FOR COMPLETE LIST AND DESCRIPTION OF ALTERNATE BIDS



FIRST FLOOR DEMOLITION PLAN
SCALE: 1/16" = 1'-0"

SECOND FLOOR DEMOLITION PLAN
SCALE: 1/16" = 1'-0"




ENLARGED DEMO PLAN AT FRONT CANOPY
SCALE: 1/8" = 1'-0"

SHEET SIZE: 24 X 36 SCALE: 1/16" = 1'-0"

**OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA**

**LAND 3
Architect**

LAND 3 ARCHITECT, INC.
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA
71201-5786



DRAWN BY: AH
CHK'D BY: WAL
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED


1ST & 2ND FLOOR
DEMOLITION PLANS

D1.1

SHEET SIZE: 24 X 36 SCALE: 1/16" = 1'-0"

NFPA TABLE A7.6
ASSEMBLY SPRINKLED


TRAVEL DISTANCE LIMIT.....250 ft.
 DEAD END LIMIT.....20 ft.
 COMMON PATH LIMIT.....75 ft.



1st FLOOR
LIFE SAFETY PLAN

SCALE: 1/16" = 1'-0"

REF. NORTH




2nd FLOOR
LIFE SAFETY PLAN


SCALE: 1/16" = 1'-0"

REF. NORTH

OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
 MONROE, LOUISIANA




LAND 3
 ARCHITECT, INC.
 A PROFESSIONAL CORPORATION
 1900 STUBBS AVENUE
 MONROE, LA.
 71201-5786



DRAWN BY: AH
 CHK'D BY: WAL
 JOB # 1963
 DATE: 08/2024
 COPYRIGHT PROTECTED

1st & 2nd FLOOR
 LIFE SAFETY PLANS

LS1.1



1st FLOOR PLAN
SCALE: 3/32" = 1'-0"

2nd FLOOR PLAN
SCALE: 3/32" = 1'-0"

- DIMENSION NOTES:**
- ALL INTERIOR DIMENSIONS SHOWN ON FLOOR PLANS ARE COMPUTER GENERATED, TAKEN FROM FACE OF STUD, AND ROUNDED TO THE NEAREST 1/8" INCREMENT.
 - CONTRACTOR SHALL BRING ALL DISCREPANCIES IN DIMENSIONS STRINGS OVER 1" TO ARCHITECTS ATTENTION PRIOR TO ROUGH IN OF ANY WALLS AND CONFIRM PROPOSED LAYOUT WITH ARCHITECT.
 - REFERENCE ADA CLEARANCE REQUIREMENTS FOR DOORWAYS PRIOR TO ANY ROUGH IN.
 - ALL INTERIOR DOORS CLOSE TO ADJACENT GYP. BD. WALLS SHALL BE LOCATED WITH HINGE SIDE 6" MIN. FROM ADJACENT WALL UNLESS OTHERWISE DIMENSIONED OR NOTED.
 - DIMENSIONS ARE TAKEN FROM FACE OF STUD, OBJECTS, OR CABINETS UNLESS OTHERWISE NOTED.

****ALTERNATE BIDS**
SEE SECTION 01 23 00 IN SPECS. FOR COMPLETE LIST AND DESCRIPTION OF ALTERNATE BIDS


NOTE:
REFER TO SHEET A1.2 FOR THE FOLLOWING NOTES:

- PLAN LEGEND
- EQUIPMENT LEGEND
- EQUIPMENT TO BE INSTALLED
- PLAN REFERENCE NOTES
- ROOM FINISH SCHEDULE

REFER TO MOUNTING DIMENSIONS ON SHEET A9.2 FOR MOUNTING HEIGHT OF ALL EQUIPMENT, TOILET ACCESSORIES, TOILET FIXTURES, ETC....

USE AND INTERPRETATION OF THESE DRAWINGS:
THE CONTRACT DOCUMENTS INCLUDE NOT ONLY THE DRAWINGS BUT THE SPECIFICATIONS. THESE CONSTRUCTION DOCUMENTS ARE COMPLEMENTARY AND WHAT IS REQUIRED BY ANY PART SHALL BE AS BINDING AS IF REQUIRED BY ALL. WORK NOT COMPLETELY DELINEATED HEREIN SHALL BE CONSTRUCTED OF THE SAME MATERIALS AND DETAIL SIMILARLY AS WORK SHOWN MORE COMPLETELY ELSEWHERE IN THE CONTRACT DOCUMENTS. IF NO DETAIL IS PROVIDED, ASK THE ARCHITECT FOR DIRECTION OR INSTALL PER MANUFACTURER'S WRITTEN INSTRUCTIONS USING GOOD STANDARD INDUSTRY PRACTICE.

**OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA**



**LAND 3
ARCHITECT, INC.**
A PROFESSIONAL CORPORATION
1800 STUBBS AVENUE
MONROE, LA
71201-5786



DRAWN BY: RM
CHK'D BY: WAL
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED

1st & 2nd FLOOR PLANS

A1.1

DOOR NOTES:

NOTES APPLY TO ALL DOORS & ARE SUPPLEMENTARY TO THE SPECIFICATIONS.

• VERIFY EXACT SIZE OF ALL DOORS & FRAMES AT SITE PRIOR TO ORDERING OF ANY DOORS, FRAMES, OR RELATED DOOR HARDWARE.

• REFER TO SECTION 08 71 00 SPECIFICATIONS FOR ADDITIONAL HARDWARE INFORMATION AND APPROVED EQUALS TO MANUFACTURER'S LISTED IN HARDWARE SCHEDULE THIS SHEET.

• ALL GLASS IN NON-RATED DOORS OR ADJACENT SURFACES SHALL BE TEMPERED SAFETY GLASS.

• ALL EXTERIOR DOORS SHALL BE AIRTIGHT & WEATHER-TIGHT. PROVIDE DOOR SWEEPS AT SILL/THRESHOLD AND WEATHER-STRIPPING AT JAMB AND HEAD.

• PROVIDE 1/2" MAXIMUM HEIGHT ada COMPLIANT THRESHOLD AT ALL EXTERIOR DOORS. (CHANGES IN LEVEL FOR THRESHOLD NOT MORE THAN 1/2" IN HEIGHT & BEVELED IF OVER 1/4").

• PROVIDE APPROPRIATE LINTELS, HEADERS, & FLASHING OVER ALL EXTERIOR DOOR OPENINGS, REFER TO DOOR DETAILS.

• PROVIDE DOOR STOPS AT ALL INTERIOR DOORS. VERIFY EXACT LOCATIONS WITH ARCHITECT, PRIOR TO MOUNTING, IF A FLOOR MOUNT TYPE IS USED.

• FOR ALL INTERIOR DOORS INDICATED WITH A LOCK SET, VERIFY WITH OWNER, THE SPECIFIC SIDE OF THE DOOR THAT SHALL RECEIVE DOOR KEY.

• ALL HOLLOW METAL DOORS AND HOLLOW METAL FRAMES ARE TO BE PRIMED & PROPERLY PREPPED FOR PAINTING BY SECTION 09 90 00. (COLORS TO BE SELECTED BY ARCH.)

• AT ALL HOLLOW METAL DOORS SCHEDULED TO RECEIVE GLAZING, PROVIDE SLOPED/BEVELED TYPE METAL STOPS WITH SAME FINISH AS DOOR.

• ALL HOLLOW METAL DOORS ARE TO BE FACTORY PREPPED & PROPERLY REINFORCED TO RECEIVE ANY SCHEDULED SURFACE MOUNTED TYPE DOOR HARDWARE AND ANY SCHEDULED MORTISE TYPE LOCK HARDWARE. ALL SCHEDULED DOOR HARDWARE SHALL BE INSTALLED IN A NEAT AND FINISHED MANNER. **ANY FIELD CUTTING/MODIFICATION OF HOLLOW METAL FRAMES SHALL BE KEPT TO AN ABSOLUTE MINIMUM.**

• ALL NEW FIRE RATED LABEL DOORS SHALL HAVE APPROPRIATE RATED DOOR HARDWARE: LOCKSET, CLOSURE, ASTRAGAL/DOOR/ FRAME TAG ETC.... AND INSTALLED IN AN APPROPRIATE RATED FRAME.

• ALL INTERIOR DOORS IN FIRE BARRIERS SHALL CARRY A APPROPRIATE LABEL FOR RATINGS & MUST COMPLY WITH N.F.P.A. 101/ N.F.P.A. 80. CLEARANCES FOR THESE DOORS SHALL BE: 3/8" MAX. BETWEEN THE DOOR BOTTOM & FINISH FLOOR & 1/8" MAX. BETWEEN THE DOOR FRAME & SIDES OR TOP OF DOOR.

• UNDER-CUTTING OF ANY FIRE RATED DOOR IS NOT ALLOWED.

DOOR GLAZING NOTES:

SEE GLAZING TYPES LISTED IN DOOR ELEV. THIS SHEET AND SECTION 08 80 00 IN SPECS. FOR TYPES OF SCHEDULED GLAZING THAT SHALL BE PROVIDED IN EACH OPENING INDICATED.

typ. FOR ALL H.M. DOOR ELEV. SHOWN WITH GLAZING THIS SHEET BOTTOM OF DOOR GLASS SHALL BE NO MORE THAN 42" A.F.F. FOR ada ACCESSIBILITY.

DOOR SCHEDULE - 2ND FLOOR

DOOR No.	DOOR TYPE	DOOR SIZE			DOOR MATERIAL	DOOR FINISH	FRAME MATERIAL	FRAME FINISH	DETAILS	COMMENTS
		WIDTH	THICK	HEIGHT						
201		1 HOUR RATED STEEL ELEVATOR DOOR AND FRAME BY SECTION 14 21 00								
202	M/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	PNT.	H.M.	PNT.	A,B,C/A7.5	60 MIN. RATED DOOR AND FRAME
204		ALL DOOR HARDWARE SHALL REMAIN EXCEPT FOR LEVER-SET, SEE LH IN HARDWARE SCH. ON SHEET A2.2								
205		EXISTING PAIR OF DOORS AND FRAME SHALL REMAIN. ALL DOOR HARDWARE SHALL REMAIN.								
206	O/A2.1	3'-0"	1 3/8"	6'-8"	MASONITE	PNT.	WOOD	PNT.	G,H,I/A7.5	
207		ALL DOOR HARDWARE SHALL REMAIN EXCEPT FOR LEVER-SET, SEE LH IN HARDWARE SCH. ON SHEET A2.2								
208	O/A2.1	3'-0"	1 3/8"	6'-8"	MASONITE	PNT.	WOOD	PNT.	G,H,I/A7.5	
209	O/A2.1	3'-0"	1 3/8"	6'-8"	MASONITE	PNT.	WOOD	PNT.	G,H,I/A7.5	
210	O/A2.1	3'-0"	1 3/8"	6'-8"	MASONITE	PNT.	WOOD	PNT.	G,H,I/A7.5	
211	O/A2.1	3'-0"	1 3/8"	6'-8"	MASONITE	PNT.	WOOD	PNT.	G,H,I/A7.5	
212	P/A2.1	3'-0"	1 3/8"	6'-8"	MASONITE	PNT.	WOOD	PNT.	G,H,I/A7.5	
213	O/A2.1	3'-0"	1 3/8"	6'-8"	MASONITE	PNT.	WOOD	PNT.	G,H,I/A7.5	
214	P/A2.1	3'-0"	1 3/8"	6'-8"	MASONITE	PNT.	WOOD	PNT.	G,H,I/A7.5	
215	P/A2.1	3'-0"	1 3/8"	6'-8"	MASONITE	PNT.	WOOD	PNT.	G,H,I/A7.5	
215a	O/A2.1	3'-0"	1 3/8"	6'-8"	MASONITE	PNT.	WOOD	PNT.	G,H,I/A7.5	
216	O/A2.1	3'-0"	1 3/8"	6'-8"	MASONITE	PNT.	WOOD	PNT.	G,H,I/A7.5	
217	K/A2.1	3'-0"±	1 3/4"	6'-8"±	existing door and frame shall remain					DOOR SIZE MUST BE SITE VERIFIED
218	P/A2.1	3'-0"	1 3/8"	6'-8"	MASONITE	PNT.	WOOD	PNT.	G,H,I/A7.5	
219	O/A2.1	3'-0"	1 3/8"	6'-8"	MASONITE	PNT.	WOOD	PNT.	H/A5.3 & G/A7.5	
220	O/A2.1	3'-0"	1 3/8"	6'-8"	MASONITE	PNT.	WOOD	PNT.		TO BE INSTALLED IN EXISTING WALL OPENING. (VERIFY SIZE)
221		ALL DOOR HARDWARE SHALL REMAIN EXCEPT FOR LEVER-SET, SEE LH IN HARDWARE SCH. ON SHEET A2.2								
222		ALL DOOR HARDWARE SHALL REMAIN EXCEPT FOR LEVER-SET, SEE LH IN HARDWARE SCH. ON SHEET A2.2								
223	M/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	PNT.	H.M.	PNT.	A,B,C/A7.5	60 MIN. RATED DOOR AND FRAME

DOOR SCHEDULE - 1ST FLOOR

DOOR No.	DOOR TYPE	DOOR SIZE			DOOR MATERIAL	DOOR FINISH	FRAME MATERIAL	FRAME FINISH	DETAILS	COMMENTS
		WIDTH	THICK	HEIGHT						
100	A/A2.1	EXTERIOR AUTOMATIC ENTRANCE DOOR SYSTEM BY SECTION 08 46 00								A,B,C/A7.1
100a,100b	A/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		G,H,I/A7.1
101	Aa/A2.1	EXTERIOR AUTOMATIC ENTRANCE DOOR SYSTEM BY SECTION 08 46 00								A,B,C/A7.1
101a,101b	Aa/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		G,H,I/A7.1
*102	I/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
104	F/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3
109	F/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3
110	F/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3
111	G/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3
111a		EXISTING DOOR AND FRAME SHALL REMAIN. ALL DOOR HARDWARE SHALL REMAIN EXCEPT FOR LEVER-SET, SEE LH IN HARDWARE SCH. ON SHEET A2.2								
*112	Ee/A2.1	SEE ELEV.	1 3/4"	7'-0"	H.M.	PNT.	H.M.	PNT.		NEW DOORS BY SECTION 08 11 13 INSTALLED IN EXIST. H.M. FRAME
112a		EXISTING DOOR AND FRAME SHALL REMAIN. ALL DOOR HARDWARE SHALL REMAIN EXCEPT FOR LEVER-SET, SEE LH IN HARDWARE SCH. ON SHEET A2.2								
*113	M/A2.1	3'-0"	1 3/4"	7'-0"	H.M.	PNT.	H.M.	PNT.		60 MIN. RATED, SEE COMMENT NOTE 3
114	D/A2.1	3'-0"	1 3/4"	7'-0"	H.M.	PNT.	H.M.	PNT.		J,K,L/A7.1
114a	M/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		A,B,C/A7.5
115	L1/A2.1	EXISTING DOOR AND FRAME SHALL REMAIN. ALL DOOR HARDWARE SHALL REMAIN EXCEPT FOR LEVER-SET, SEE LH IN HARDWARE SCH. ON SHEET A2.2								
116	I/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
117	I/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
118	L/A2.1	(2) 3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
118a	D/A2.1	3'-0"	1 3/4"	7'-0"	H.M.	PNT.	H.M.	PNT.		J,K,L/A7.1
119	L/A2.1	(2) 3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
119a	D/A2.1	3'-0"	1 3/4"	7'-0"	H.M.	PNT.	H.M.	PNT.		J,K,L/A7.1
120	J/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
121	I/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
122	I/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
123	I/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
*124	H/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		G,H,I/A7.6
124a	R/A2.1	(2) 3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		G,H,I/A7.6
125	F/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3
126	F/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3
127	F/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3
128	F/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3
129	F/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3
130	F/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3
131	F/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3
*135	I/A2.1	3'-0"	1 3/4"	6'-8"	S.C.W.	STAIN	H.M.	PNT.		-----
*138	F/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3 B/A7.6
139	F/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3
140	N/A2.1	3'-0"	1 3/4"	6'-8"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5 L/A7.6
141	K/A2.1	3'-0"±	1 3/4"	6'-8"±	existing door and frame shall remain					-----
*143	J/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
144	K/A2.1	3'-0"±	1 3/4"	6'-8"±	existing door and frame shall remain					-----
145	K/A2.1	3'-0"±	1 3/4"	6'-8"±	existing door and frame shall remain					-----
146		EXIST. PAIR OF H.M. DOORS AND H.M. FRAME SHALL REMAIN, DOORS TO BE RE-KEYED. (DOORS AND FRAME TO BE PRIMED & PAINTED BY SECTION 09 90 00)								
*148	C/A2.1	(2) 3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		D,E,F/A7.1
149	R/A2.1	(2) 3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3 B/A7.6
149a	H/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3 B/A7.6
150,150A	I/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
151	H/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3 B/A7.6
152	I/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
153	G/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3
153a,156a	E/A2.1	3'-0"	1 3/4"	7'-0"	H.M.	PNT.	H.M.	PNT.		G,H,I/A7.4
154	B/A2.1	10'-0"	----	10'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.4
154a	B/A2.1	10'-0"	----	8'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		D,E,F/A7.4
154b	B/A2.1	10'-0"	----	8'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		D,E,F/A7.4
154c	A/A2.1	3'-0"	1 3/4"	7'-0"	H.M.	PNT.	H.M.	PNT.		J,K,L/A7.1
155	G/A2.2	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3
156	R/A2.1	(2) 3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3 B/A7.6
156b		EXIST. PAIR OF H.M. DOORS AND H.M. FRAME SHALL REMAIN, DOORS TO BE RE-KEYED. (DOORS AND FRAME TO BE PRIMED & PAINTED BY SECTION 09 90 00)								
157	I/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
158,158	I/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
159	H/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3 K/A7.6
160,161	K/A2.1	3'-0"±	1 3/4"	6'-8"±	existing door and frame shall remain					-----
162,163	K/A2.1	3'-0"±	1 3/4"	6'-8"±	existing door and frame shall remain					-----
164	I/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
165	J/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
168	F/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3
169	N/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
*170	F/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3
170a	I/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
171	N/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
172	M/A2.1	3'-0"	1 3/4"	7'-0"	H.M.	PNT.	H.M.	PNT.		A,B,C/A7.5
173	I/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
*174,179	I/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
175	I/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
176	F/A2.1	3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		A,B,C/A7.3
177	J/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
178	J/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
*179a		EXISTING DOOR AND FRAME SHALL REMAIN. SEE HARDWARE TYPE AC6 ON SHEET A2.1a FOR NEW ACCESS CONTROLLED HARDWARE AT THIS DOOR.								
180	Q/A2.1	(2) 3'-0"	----	7'-0"	ALUM.	PRE-FIN.	ALUM.	PRE-FIN.		DOOR & FRAME TO BE INSTALLED IN EXISTING WALL OPENING
181	I/A2.1	3'-0"	1 3/4"	7'-0"	S.C.W.	STAIN	H.M.	PNT.		D,E,F/A7.5
183a		EXISTING DOOR AND FRAME SHALL REMAIN. ALL DOOR HARDWARE SHALL REMAIN EXCEPT FOR LEVER-SET, SEE LH IN HARDWARE SCH. ON SHEET A2.2								
184	J/A2.1	3'-0"	1 3/4"	7						

ACCESS CONTROL NOTES:

DESIGN INTENT IS FOR ALL ACCESS CONTROLLED DOORS TO BE NORMALLY CLOSED, LATCHED & LOCKED. INGRESS INTO ROOM SHALL BE CONTROLLED EITHER BY A REMOTE RELEASE SWITCH OR A PROXIMITY CARD READER. FREE EGRESS FROM THESE DOORS SHALL BE ALLOWED AT ALL TIMES. REFER TO HARDWARE SCH. THIS SHEET AND ELECTRICAL SHEETS.

WHERE ACCESS CONTROLLED HARDWARE IS SCHEDULED AT AN EXISTING DOOR OPENING, PATCH EXISTING DOOR FRAME WHERE DAMAGED DUE TO REMOVAL OF EXISTING DOOR HARDWARE AND INSTALLATION OF NEW SCHEDULED ACCESS CONTROLLED HARDWARE. EXISTING FRAME BOTH SIDES SHALL BE PATCHED, CLEANED, SANDED, PRIME AND PAINTED BY SECTION 09 90 00.

ALL ACCESS CONTROL HARDWARE LISTED IN HARDWARE SCHEDULE ON THIS SHEET AND SHOWN IN DIAGRAMS THIS SHEET SHALL BE USED AS A BASIS FOR DESIGN OF DESIRED ABILITY TO CONTROL ACCESS TO DOORS INDICATED. OTHER MANUFACTURER'S PRODUCTS/COMPONENTS MAY BE SUBSTITUTED AND USED.


PROVIDE ANY ADDITIONAL COMPONENTS, WIRING, CONDUIT, CONDUCTORS, & HARDWARE THAT MAY BE NEEDED FOR A COMPLETE FUNCTIONING ACCESS CONTROLLED DOOR SYSTEM. ALL DIAGRAMS THIS SHEET ARE INTENDED TO INDICATE DESIRED ACCESS AT CONTROLLED DOORS & SHALL BE USED AS A BASIS FOR DESIGN. SITE VERIFY EXISTING CONDITIONS PRIOR TO BID & VERIFY SECURITY HARDWARE LISTED WITH OWNER TO DETERMINE IF ANY ADDITIONAL MODIFICATIONS OF DOOR HARDWARE WILL BE NEEDED & INCLUDE ALL COSTS FOR ADDITIONAL ITEMS/WORK NEEDED IN BID. (ALL SECURITY HARDWARE LISTED SHALL BE VERIFIED WITH OWNER FOR THEIR APPROVAL.)

ELECTRICAL CONTRACTOR IS RESPONSIBLE FOR AND SHALL PROVIDE JUNCTION BOX, CONDUIT, WIRING, ETC., AS NEEDED FOR POWER REQUIREMENTS OF ACCESS CONTROL HARDWARE. ACCESS CONTROL HARDWARE CONTRACTOR TO PROVIDE ALL LOW VOLTAGE WIRING & SCH. ACCESS CONTROL HARDWARE FOR A COMPLETE FUNCTIONING SYSTEM.

ACCESS CONTROL DOOR HARDWARE SCHEDULE
(by section 08 71 00) **SEE DOOR LOCATIONS ON FLOOR PLANS ON SHEETS A1.1 & A1.2 FOR REFERENCED ACCESS CONTROLLED HARDWARE LOCATIONS.


- AC1**
EXTERIOR SINGLE - ACCESS CONTROLLED (ALUMINUM STOREFRONT DOOR)
3070 1 1/4" AD X AF
NON-ACCESS CONTROLLED DOOR HARDWARE:
1 EACH FULL MORTISE CONT. GEARED HINGE 224HD 83" AL BY "IVES"
1 EACH CLOSER SC71 RW/PA TBWMS AL BY "FALCON"
1 EACH CYLINDER (VERIFY MANUF. & FINISH)
BALANCE OF REMAINING DOOR HARDWARE SHALL BE PROVIDED BY ALUMINUM STOREFRONT DOOR SUPPLIER, RE: SECTION 08 41 13 ACCESS CONTROL HARDWARE BY DIV.8:
1 EACH ELECTRIC DOOR STRIKE 9600 630 BY "HES"
1 EACH PSP (VERIFY 12V OR 24V) BY "SECURITRON"
1 EACH PROXIMITY CARD READER WITH CARD & KEY FOB CAPABILITY, "MINIPROX" SLIM MULLION MOUNT BY "HID" WITH BLACK FINISH (PROVIDE ALL ADDITIONAL EQUIPMENT AS REQUIRED FOR A COMPLETE FUNCTIONING SYSTEM)
- AC1a**
EXTERIOR PAIR - ACCESS CONTROLLED (ALUMINUM STOREFRONT DOOR)
6070 1 1/4" AD X AF
NON-ACCESS CONTROLLED DOOR HARDWARE:
2 EACH FULL MORTISE CONT. GEARED HINGE 224HD 83" AL BY "IVES"
3 EACH FRAME SILENCER SR64 GREY BY "IVES"
ACCESS CONTROL HARDWARE BY DIV.8:
1 EACH ELECTRIC DOOR STRIKE 9600 630 BY "HES"
1 EACH PSP (VERIFY 12V OR 24V) BY "SECURITRON"
1 EACH 300 SERIES DOOR MULLION BY "FIRST CHOICE"
1 EACH PROXIMITY CARD READER WITH CARD & KEY FOB CAPABILITY, "MINIPROX" SLIM MULLION MOUNT BY "HID" WITH BLACK FINISH (PROVIDE ALL ADDITIONAL EQUIPMENT AS REQUIRED FOR A COMPLETE FUNCTIONING SYSTEM)
- AC2**
EXTERIOR UNEQUAL PAIR - MECHANICAL CLOSET
30/24 70 1 1/4" MD X EMF (ACTIVE LEAF ACCESS CONTROLLED)
NON-ACCESS CONTROLLED DOOR HARDWARE:
2 EACH FULL MORTISE CONT. GEARED HINGES 224HD 83" AL BY "IVES" (verify door height)
2 EACH CLOSER SC71 RW/PA TBWMS AL BY "FALCON"
1 EACH FLUSH BOLT (inactive leaf-top) F456 12" 26D BY "IVES"
1 EACH FLUSH BOLT (inactive leaf-bottom) F858 26D BY "IVES"
2 EACH WEATHER-STRIP 155V (door width varies) X 84" BY "NGP"
1 EACH SWEEP 101V (door width varies) BY "NGP"
1 EACH (side completion) THRESHOLD 896V 60" RW/PA MULL FINISH BY "NGP"
1 EACH DRIP CAP 16A 66" BY "NGP"
ACCESS CONTROL HARDWARE BY DIV.8:
1 EACH ELECTRIC DOOR STRIKE 9600 630 BY "HES"
1 EACH PSP (VERIFY 12V OR 24V) BY "SECURITRON"
1 EACH RIM LATCHING PANIC DEVICE 3790 BY "FIRST CHOICE"
1 EACH RIM LATCHING PANIC DEVICE 3790 BY "FIRST CHOICE"
1 EACH PROXIMITY CARD READER WITH CARD & KEY FOB PROXPOINT PLUS (black finish, to be located adj. to door on strike side in corridors, site verify existing conditions and location to be mounted.)
(PROVIDE ALL ADDITIONAL EQUIPMENT AS REQUIRED FOR A COMPLETE FUNCTIONING SYSTEM)
- AC3**
INTERIOR SINGLE - ACCESS CONTROLLED (ALUMINUM STOREFRONT DOOR)
3070 1 1/4" AD X AF
NON-ACCESS CONTROLLED DOOR HARDWARE:
1 EACH CYLINDER FOR KEYED LOCK (VERIFY MANUF. & FINISH)
BALANCE OF REMAINING DOOR HARDWARE SHALL BE PROVIDED BY ALUMINUM STOREFRONT DOOR SUPPLIER, RE: SECTION 08 41 13 ACCESS CONTROL HARDWARE BY DIV.8:
1 EACH ELECTRIC DOOR STRIKE 9600 630 BY "HES"
1 EACH PSP (VERIFY 12V OR 24V) BY "SECURITRON"
1 EACH RIM LATCHING PANIC DEVICE 3790 BY "FIRST CHOICE"
1 EACH PROXIMITY CARD READER WITH CARD & KEY FOB CAPABILITY, "MINIPROX" SLIM MULLION MOUNT BY "HID" WITH BLACK FINISH (PROVIDE ALL ADDITIONAL EQUIPMENT AS REQUIRED FOR A COMPLETE FUNCTIONING SYSTEM)
- AC3a**
INTERIOR SINGLE - ACCESS CONTROLLED (ALUMINUM STOREFRONT DOOR)
3070 1 1/4" AD X AF
NON-ACCESS CONTROLLED DOOR HARDWARE:
1 EACH CYLINDER FOR KEYED LOCK (VERIFY MANUF. & FINISH)
BALANCE OF REMAINING DOOR HARDWARE SHALL BE PROVIDED BY ALUMINUM STOREFRONT DOOR SUPPLIER, RE: SECTION 08 41 13 ACCESS CONTROL HARDWARE BY DIV.8:
1 EACH ELECTRIC DOOR STRIKE 9600 630 BY "HES"
1 EACH PSP (VERIFY 12V OR 24V) BY "SECURITRON"
1 EACH 155V BUZZER 20089 BY "HES"
1 EACH MAGNETIC LOCK M62 MAGNALOCK BY "SECURITRON"
1 EACH RRB - REMOTE RELEASE BUTTON N.O. CONTACT FOR DOOR RELEASE, VERIFY LOW VOLTAGE W/ OWNER
1 EACH RIM LATCHING PANIC DEVICE 3790 BY "FIRST CHOICE"
1 EACH PROXIMITY CARD READER WITH CARD & KEY FOB CAPABILITY, "MINIPROX" SLIM MULLION MOUNT BY "HID" WITH BLACK FINISH (PROVIDE ALL ADDITIONAL EQUIPMENT AS REQUIRED FOR A COMPLETE FUNCTIONING SYSTEM)
- AC4**
INTERIOR SINGLE - ACCESS CONTROLLED (ALUMINUM STOREFRONT DOOR)
3070 1 1/4" MD X MF
NON-ACCESS CONTROLLED DOOR HARDWARE:
1 EACH FULL MORTISE CONT. GEARED HINGE 224HD 83" AL BY "IVES"
1 EACH CLOSER SC71 RW/PA TBWMS AL BY "FALCON"
1 EACH CYLINDER (VERIFY MANUF. & FINISH)
1 EACH FRAME SILENCER SR64 GREY BY "IVES"
ACCESS CONTROL HARDWARE BY DIV.8:
1 EACH ELECTRIC DOOR STRIKE 9600 630 BY "HES"
1 EACH PSP (VERIFY 12V OR 24V) BY "SECURITRON"
1 EACH PROXIMITY CARD READER WITH CARD & KEY FOB PROXPOINT PLUS (black finish, to be located adj. to door on strike side in corridors, site verify existing conditions and location to be mounted.)
(PROVIDE ALL ADDITIONAL EQUIPMENT AS REQUIRED FOR A COMPLETE FUNCTIONING SYSTEM)
- AC4a**
INTERIOR SINGLE - ACCESS CONTROLLED (CORRIDOR PASSAGE W/PANIC)
3070 1 1/4" MD X MF
NON-ACCESS CONTROLLED DOOR HARDWARE:
1 EACH FULL MORTISE CONT. GEARED HINGES 224HD 83" AL BY "IVES"
1 EACH CLOSER SC71 RW/PA TBWMS AL BY "FALCON"
1 EACH CYLINDER - MANUF. & FINISH TO BE VERIFIED
3 EACH FRAME SILENCER SR64 GREY BY "IVES"
ACCESS CONTROL HARDWARE BY DIV.8:
1 EACH ELECTRIC DOOR STRIKE 9600 630 BY "HES"
1 EACH PSP (VERIFY 12V OR 24V) BY "SECURITRON"
1 EACH RIM LATCHING PANIC DEVICE 3790 BY "FIRST CHOICE"
1 EACH PROXIMITY CARD READER WITH CARD & KEY FOB PROXPOINT PLUS (black finish, to be located adj. to door on strike side in corridors, site verify existing conditions and location to be mounted.)
(PROVIDE ALL ADDITIONAL EQUIPMENT AS REQUIRED FOR A COMPLETE FUNCTIONING SYSTEM)
- AC5**
INTERIOR SINGLE - STAIRS/EGRESS CORRIDOR ACCESS CONTROLLED (60 MIN. FIRE RATING)
3070 1 1/4" MD X MF
NON-ACCESS CONTROLLED DOOR HARDWARE:
1 EACH FULL MORTISE CONT. GEARED HINGES 224HD 83" AL BY "IVES"
1 EACH RATED CLOSER SC71 RW/PA TBWMS AL BY "FALCON"
1 EACH RATED RIM EXIT DEVICE F-25R-L 510L QUAN 626 BY "FALCON"
1 EACH CYLINDER (VERIFY MANUF. & FINISH)
1 EACH INTUMESCENT FIRE SEAL 9450C X 96" BY "NGP"
1 EACH SMOKE CONTROL SWEEP 97V 36" BY "NGP"
1 EACH FLOOR STOP PS410 BLK BY "IVES"
3 EACH FRAME SILENCER SR64 GREY BY "IVES"
ACCESS CONTROL HARDWARE BY DIV.8:
1 EACH ELECTRIC DOOR STRIKE 9600 630 BY "HES"
1 EACH PSP (VERIFY 12V OR 24V) BY "SECURITRON"
1 EACH PROXIMITY CARD READER & KEY FOB PROXPOINT PLUS (BLACK FINISH, TO BE LOCATED ADJ. TO DOOR ON STRIKE SIDE IN CORRIDOR, SITE VERIFY EXISTING CONDITIONS AND LOCATION TO BE MOUNTED.)
(PROVIDE ALL ADDITIONAL EQUIPMENT AS REQUIRED FOR A COMPLETE FUNCTIONING SYSTEM)
- AC6**
EXTERIOR SINGLE - EXIT/ENTRANCE ACCESS CONTROLLED EXISTING 3070 1 1/4" MD X MF
NON-ACCESS CONTROLLED DOOR HARDWARE:
REMOVE & REPLACE EXISTING DOOR HINGES WITH 1 EACH FULL MORTISE CONT. GEARED HINGE 224HD 83" AL BY "IVES" (patch existing h.m. door frame)
REMOVE & REPLACE EXISTING EXIT DEVICE WITH 1 EACH RIM EXIT DEVICE 25R-L 510L QUAN 626 BY "FALCON"
1 EACH CYLINDER (VERIFY MANUF. & FINISH)
REMOVE & REPLACE EXISTING WEATHER-STRIPPING WITH 1 EACH WEATHER-STRIP 155V 36" X 84" BY "NGP"
(BALANCE OF REMAINING NON-ACCESS CONTROLLED DOOR HARDWARE SHALL REMAIN, CONTRACTOR SHALL SITE VERIFY EXISTING CONDITIONS AT EACH DOOR SCH. TO RECEIVE NEW HARDWARE TO DETERMINE IF ANY ADDITIONAL DOOR HARDWARE WILL BE NEEDED OR REPLACED TO ACCOMMODATE NEW SCH. ACCESS HARDWARE FOR THESE EXISTING DOORS)
ACCESS CONTROL HARDWARE BY DIV.8:
1 EACH ELECTRIC DOOR STRIKE 9600 630 BY "HES"
1 EACH PSP (VERIFY 12V OR 24V) BY "SECURITRON"
1 EACH RIM LATCHING PANIC DEVICE 3790 BY "SECURITRON"
1 EACH PROXIMITY CARD READER & KEY FOB PROXPOINT PLUS BY "HID" (BLACK FINISH, TO BE LOCATED ADJ. TO DOORS ON EXTERIOR SIDE MOUNTED TO EXTERIOR WALL, SITE VERIFY EXISTING CONDITIONS AND LOCATION TO BE MOUNTED.)
(PROVIDE ALL ADDITIONAL EQUIPMENT AS REQUIRED FOR A COMPLETE FUNCTIONING SYSTEM)
- AC7**
INTERIOR SINGLE - ACCESS CONTROLLED (ALUMINUM STOREFRONT DOOR)
3070 1 1/4" AD X AF
NON-ACCESS CONTROLLED DOOR HARDWARE:
1 EACH CYLINDER FOR KEYED LOCK (VERIFY MANUF. & FINISH)
BALANCE OF REMAINING DOOR HARDWARE SHALL BE PROVIDED BY ALUMINUM STOREFRONT DOOR SUPPLIER, RE: SECTION 08 41 13 ACCESS CONTROL HARDWARE BY DIV.8:
1 EACH ELECTRIC DOOR STRIKE 9600 630 BY "HES"
1 EACH PSP (VERIFY 12V OR 24V) BY "SECURITRON"
1 EACH RIM LATCHING PANIC DEVICE 3790 BY "FIRST CHOICE"
1 EACH PROXIMITY CARD READER & KEY FOB PROXPOINT PLUS BY "HID" (BLACK FINISH, TO BE LOCATED ADJ. TO DOORS ON EXTERIOR SIDE MOUNTED TO EXTERIOR WALL, SITE VERIFY EXISTING CONDITIONS AND LOCATION TO BE MOUNTED.)
(PROVIDE ALL ADDITIONAL EQUIPMENT AS REQUIRED FOR A COMPLETE FUNCTIONING SYSTEM)

(SEE ELECTRICAL SHEETS FOR POWER REQUIREMENTS AND ASSOCIATED WORK TO ACCESS CONTROL SYSTEM INCLUDE ALL CONDUIT & CONDUCTORS FOR ACCESS SYSTEM CONNECTED TO NEAREST AVAILABLE ADEQUATE NON-SWITCHED CIRCUIT)




ACCESS CONTROLLED DOOR ELEVATIONS
SCALE: 1/4" = 1'-0"

SHEET SIZE: 24 X 36 SCALE: 1/4" = 1'-0"



SHEET SIZE: 24 X 36 SCALE: 3/32" = 1'-0"



SCALE FOR ALL INTERIOR ELEVATIONS THIS SHEET: 1/4" = 1'-0"

GENERAL NOTES:
FOR CASEWORK BY SECTION 06 41 00

NOTE: NUMBERS SHOWN FOR EACH TYPE OF CASEWORK ON INT. ELEV. THIS SHEET IS BASED ON PRODUCTS BY "CASE SYSTEMS" TO ESTABLISH SIZING & TYPE OF CABINETS DESIRED. OTHER CASEWORK MANUF. MAY BE SUBSTITUTED & USED.

- REFER TO SECTION 06 41 00 IN SPECIFICATIONS FOR A LIST OF APPROVED CASEWORK MANUFACTURERS.
- DIMENSIONS SHOWN ON CASEWORK ELEVATIONS INDICATE HEIGHT X DEPTH X WIDTH OF EACH CASEWORK TYPE SHOWN.
- PROVIDE PLY-WOOD UNDER-LAYMENT FOR COUNTER-TOPS WHERE INDICATED ON CASEWORK ELEVATIONS. THIS REQUIREMENT IS INTENTIONALLY MORE STRINGENT THAN CASEWORK SPECS. INDICATE DUE TO HIGH ABUSE OR WET LOCATIONS.
- APPLY SCHEDULED WALL BASE TO THE TOE SPACE & EXPOSED SIDES OF ALL BASE CABINETS.
- ALL FILLER PANELS AT CASEWORK SHALL BE ABSOLUTE MINIMUM IN SIZE & QUANTITY.
- ALL CABINETS SHALL HAVE FULLY CONCEALED SELF-CLOSING HINGES; SEE SECTION 06 41 00 IN SPECS.
- ALL OUTSIDE CORNERS OF CASEWORK COUNTER-TOPS SHALL BE EITHER ROUNDED OR CHAMFERED TO PREVENT AN UNATTRACTIVE SHARP END.
- RECESS ALL FASTENERS AT CASEWORK THAT IS SECURED TO WALLS. ALL FASTENERS SHALL NOT BE VISIBLE. FULLY FILL Voids AT EACH FASTENER WITH A PRE-FINISHED CAP TO MATCH FINISH OF CABINET BACK. CAP SHALL BE FLUSH WITH ADJACENT MATERIAL OF CABINET BACK.

GENERAL NOTES:
 GENERAL CONTRACTOR SHALL PROVIDE SOLID BLOCKING IN WALLS BEHIND ALL CABINETS SHOWN ON INT. ELEV. THIS SHEET AS REQUIRED TO ENSURE SECURE ATTACHMENT OF ALL WALL CABINETS.

REFER TO APPLIANCE SCHEDULE ON SHEET A1.2 FOR EXTENT OF APPLIANCES THAT ARE TO BE PROVIDED AND INSTALLED BY G.C.

SK - TYPICAL FOR ALL NEW ADA ACCESSIBLE SINKS SHOWN ON INT. ELEVATIONS THIS SHEET. SINKS SHALL BE 34" MAX. HEIGHT TO TOP RIM OF SINK. ADJUST HEIGHT OF END PANELS & COUNTER-TOP AS REQUIRED TO MAINTAIN A MAX. 34" HEIGHT.

****** CASEWORK SINK CABINET SHOWN ON INTERIOR ELEVATIONS WITH THIS MARK ARE WHEELCHAIR ACCESSIBLE WITH NO BOTTOM AND POCKET DOORS THAT SLIDE INTO CABINET FOR ADA ACCESSIBILITY. WHEN CABINET DOORS ARE OPENED & RE-TRACTED, OPEN KNEE SPACE HAS REQUIRED MIN. CLEARANCES OF 27"H X 30"W FOR ADA ACCESSIBILITY.

ALTERNATE BIDS:
 SEE SECTION 01 23 00 IN SPECS. FOR COMPLETE LIST AND DESCRIPTION OF ALTERNATE BIDS.

SHEET SIZE: 24 X 36 SCALE: 1/4" = 1'-0"

GENERAL NOTES:
FOR CASEWORK BY SECTION 06 41 00
NOTE: NUMBERS SHOWN FOR EACH TYPE OF CASEWORK ON INT. ELEV. THIS SHEET IS BASED ON PRODUCTS BY "CASE SYSTEMS" TO ESTABLISH SIZING & TYPE OF CABINETRY DESIRED. OTHER CASEWORK MANUF. MAY BE SUBSTITUTED & USED.
• REFER TO SECTION 06 41 00 IN SPECIFICATIONS FOR A LIST OF APPROVED CASEWORK MANUFACTURERS.
• DIMENSIONS SHOWN ON CASEWORK ELEVATIONS INDICATE HEIGHT X DEPTH X WIDTH OF EACH CASEWORK TYPE SHOWN.
• PROVIDE PLY-WOOD UNDER-LAYMENT FOR COUNTER-TOPS WHERE INDICATED ON CASEWORK ELEVATIONS. THIS REQUIREMENT IS INTENTIONALLY MORE STRINGENT THAN CASEWORK SPECS. INDICATE DUE TO HIGH ABUSE OR WET LOCATIONS.
• APPLY SCHEDULED WALL BASE TO THE TOE SPACE & EXPOSED SIDES OF ALL BASE CABINETS.
• ALL FILLER PANELS AT CASEWORK SHALL BE ABSOLUTE MINIMUM IN SIZE & QUANTITY.
• ALL CABINETS SHALL HAVE FULLY CONCEALED SELF CLOSING HINGES, SEE SECTION 06 41 00 IN SPECS.
• ALL OUTSIDE CORNERS OF CASEWORK COUNTER-TOPS SHALL BE EITHER ROUNDED OR CHAMFERED TO PREVENT AN ABRUPT SHARP END.
• RECESS ALL FASTENERS AT CASEWORK THAT IS SECURED TO WALLS, ALL FASTENERS SHALL NOT BE VISIBLE. FULLY FILL VOIDS AT EACH FASTENER WITH A PRE-FINISHED CAP TO MATCH FINISH OF CABINET BACK. CAP SHALL BE FLUSH WITH ADJACENT MATERIAL OF CABINET BACK.

SCALE FOR ALL INTERIOR ELEVATIONS THIS SHEET: 1/4" = 1'-0"

GENERAL NOTES:
GENERAL CONTRACTOR SHALL PROVIDE SOLID BLOCKING IN WALLS BEHIND ALL CABINETS SHOWN ON INT. ELEV. THIS SHEET AS REQUIRED TO ENSURE SECURE ATTACHMENT OF ALL WALL CABINETS.
REFER TO APPLIANCE SCHEDULE ON SHEET A1.2 FOR EXTENT OF APPLIANCES THAT ARE TO BE PROVIDED AND INSTALLED BY G.C.
SK- TYPICAL FOR ALL NEW ADA ACCESSIBLE SINKS SHOWN ON INT. ELEVATIONS THIS SHEET. SINKS SHALL BE 34" MAX. HEIGHT TO TOP RIM OF SINK. ADJUST HEIGHT OF END PANELS & COUNTER-TOP AS REQUIRED TO MAINTAIN A MAX. 34" HEIGHT.)
** CASEWORK SINK CABINET SHOWN ON INTERIOR ELEVATIONS WITH THIS MARK ARE WHEEL CHAIR ACCESSIBLE WITH NO BOTTOM AND POCKET DOORS THAT SLIDE INTO CABINET FOR ADA ACCESSIBILITY. WHEN CABINET DOORS ARE OPENED & RE-TRACTED, OPEN KNEE SPACE HAS REQUIRED MIN. CLEARANCES OF 27"H X 30"W FOR ADA ACCESSIBILITY.
ALTERNATE BIDS:
SEE SECTION 01 23 00 IN SPECS. FOR COMPLETE LIST AND DESCRIPTION OF ALTERNATE BIDS.

RELOCATED BOOKCASE SECTION - n.t.s.


INTERIOR ELEV. AREA 170 - south wall
INTERIOR ELEV. AREA 170 - east wall
PARTIAL INTERIOR ELEV. AREA 170 - west wall
INTERIOR ELEV. AREA 172 - south wall
INTERIOR ELEV. AREA 180 - south wall
INTERIOR ELEV. AREA 181 - north wall
PARTIAL INT. ELEV. AREA 183
INTERIOR ELEV. AREA 183
INTERIOR ELEV. AREA 191
INTERIOR ELEV. AREA 208
INTERIOR ELEV. AREA 213 - north wall
INTERIOR ELEV. AREA 213 - west wall
INTERIOR ELEV. AREA 218
COLUMN FURRING ELEVATION

GENERAL NOTES:
ALL EXISTING WALLS THIS AREA SHALL BE PATCHED/REPAIRED. (FIELD VERIFY MATERIALS) PREP ALL WALLS TO RECEIVE NEW PAINT BY SECTION 09 90 00.
EXISTING SINK SHALL REMAIN. SEE PLUMBING SHEETS FOR EXTENT OF NEW WORK REQUIRED TO MAKE SINK FULLY SERVICEABLE.
EXISTING COUNTER-TOP & BACK-SPLASH SHALL REMAIN.
NEW UNDER-MOUNT ADA COMPLIANT SINK BY DIV. 22. SEE PLUMBING SHEETS. PROVIDE INSUL. KIT OVER ALL EXPOSED PIPING.
ALL EXISTING CABINETS SHALL BE CLEANED, ALL HARDWARE RE-SECURED, ALL SAGGING DOORS RE-ALIGNED, & ENSURE THAT ALL DRAWERS OPEN/SLIDE SMOOTHLY WITHOUT ANY BINDING.
ALL DIMENSIONS ARE APPROXIMATE


GENERAL NOTES:
EXISTING BACK PANEL SHALL BE RE-USED IF SALVAGEABLE. ASSUMED THAT PANEL IS FASTENED OR POSSIBLY GLUED DIRECTLY TO EXISTING WALL AND NOT ATTACHED TO SHELVING UNIT. FIELD VERIFY EXISTING CONDITIONS & IF PANEL IS NOT ABLE TO BE RE-USED REPLACE WITH NEW 1/2" OAK PLYWOOD TO CLOSELY MATCH. SECURELY FASTEN PLYWOOD TO EXISTING STILES & BLOCKING AT BACK OF UNITS.
STILE BETWEEN EACH UNIT CONTAINS STANDARDS EACH SIDE FOR SHELVES
TOP, MIDDLE, AND BOTTOM RAILS ARE APPROX. 2 3/4" WIDE AT EACH UNIT

SHEET SIZE: 24 X 36 SCALE: 1/4" = 1'-0"


SHEET SIZE: 24 X 36 SCALE: 1/16" = 1'-0"




1st FLOOR PLAN
SCALE: 3/32" = 1'-0"
REF. NORTH




2nd FLOOR PLAN
SCALE: 3/32" = 1'-0"
REF. NORTH




A4.4 EXISTING STAIR 113 SECTION
SCALE: 1/4" = 1'-0"




B HANDRAIL (HR) RETURN DETAILS



C HANDRAIL SECTION AT EXISTING STAIRS
NOT TO SCALE



D EXISTING STAIR 193 SECTION




ENLARGED PLAN AT STAIR 113 UPPER LANDING
SCALE: 1/4" = 1'-0"
REF. NORTH

OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA




LAND 3 ARCHITECT, INC.
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA.
71201-5786



DRAWN BY: LOH
CHK'D BY: WAL
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED

EXISTING INTERIOR STAIR MODIFICATIONS

A4.4



IMPACT LOADS

VERTICAL LOADS AT PIT (BUFFER IMPACT)		VERTICAL LOADS AT PIT UNDER GUIDE RAILS (INCLUDING IMPACT LOAD DUE TO SAFETIES APPLICATION, GOVERNOR LOAD AND EQUIPMENT ON RAILS)			
F9	F10	F8	F16	F17	F18
6305 LBF	8319 LBF	8983 LBF	11864 LBF	2833 LBF	2833 LBF
[28.0 KN]	[37.0 KN]	[40.0 KN]	[52.8 KN]	[12.6 KN]	[12.6 KN]

CAR RAIL LOADS

NON-SEISMIC		SEISMIC	
F	P	F	P
161 LBF	97 LBF	544 LBF	286 LBF
[715 N]	[432 N]	[2416 N]	[1269 N]


CWT-RAIL LOADS

NON-SEISMIC		SEISMIC	
F	P	F	P
64 LBF	5 LBF	575 LBF	267 LBF
[285 N]	[22 N]	[2554 N]	[1186 N]

STATIC RAIL LOADS FROM EQUIPMENT SUPPORTED

F8	F16	F17	F18
3632 LBF	6139 LBF	1823 LBF	1823 LBF
[16.2 KN]	[27.3 KN]	[8.1 KN]	[8.1 KN]

NOTE: F9 & F10 Do not occur simultaneously with F8 & F16



ELEVATOR GENERAL NOTES:
THE GENERAL CONTRACTOR SHALL PROVIDE THE FOLLOWING REQUIREMENTS:

SEE SPECIFICATIONS SECTION 14 21 00. GENERAL CONTRACTOR SHALL REVIEW REQUIRED WORK AND DIMENSIONS WITH ELEVATOR CONTRACTOR PRIOR TO PIT & SHAFT CONSTRUCTION.




RULES REFERENCED ARE TAKEN FROM THE AMERICAN NATIONAL STANDARD ELEVATOR SAFETY CODE ASME A17.1; WHEN THE APPLICABLE LOCAL CODES INCLUDE OTHER REQUIREMENTS OR CONFLICTS WITH ASME 17.1, THE LOCAL CODES SHALL PREVAIL.

- HOISTWAY ENCLOSURE SHALL BE FIRE RATED, (RULE 100.1)
- VENTING OF THE HOISTWAY (RULE 100.4)
- DRY PIT REINFORCED TO SUSTAIN VERTICAL FORCES FROM RAILS & BUFFERS. (RULES 108.1b, 100.2a, & 1308.2)
- CONVENIENCE OUTLET AND LIGHT FIXTURE IN PIT. (RULE 106.1E)
- PIT LADDER FOR ELEVATOR EXTENDING NO LESS THAN 3'-6" ABOVE BOTTOM LANDING AND ALL WALK-IN PITS. (RULE 108.1D)
- ACCESS TO MACHINE ROOM AND MACHINERY SPACE. (RULE 101.3)
- LIGHTING, VENTILATION, & HEATING OF MACHINE ROOM & MACHINERY SPACE (RULE 101.3) MACHINE ROOM TEMPERATURE TO BE MAINTAINED BETWEEN 55°F & 90°F.
- A FUSED DISCONNECT SWITCH OR CIRCUIT BREAKER FOR ELEVATOR. LOCATE PER NATIONAL ELECTRICAL CODE (N.E.C. A NO. 70 RULE 620-51A & 620-51B1) WHERE PRACTICABLE LOCATE INSIDE MACHINE ROOM ADJACENT TO DOOR.

TYPICAL ABBREVIATIONS:

BGS - DISTANCE BETWEEN CWT GUIDE RAILS
BK - CAR WIDTH (INSIDE)
BKS - DISTANCE BETWEEN CAR GUIDE RAILS
BS - HOISTWAY WIDTH
BT - ENTRANCE OPENING WIDTH (HOISTWAY)
DCL - DOOR CENTERLINE
HK - CAR HEIGHT TO UNDERSIDE OF CANOPY
HSG - PIT DEPTH
HSK - OVERHEAD HEIGHT
HT - ENTRANCE OPENING HEIGHT
RHD - RAIL HEAD DEPTH
RO - ROUGH OPENING
SG - CENTER LINE CWT RAIL
SKO - TOP RUN BY
SKU - BOTTOM RUN BY
TCRW - TOP OF CWT RAIL
TK - CAR DEPTH (INSIDE)
TKS - RUNNING CLEARANCE
TKSW - FRONT H/W WALL TO C/L RAILS
TS - HOISTWAY DEPTH
TSW - ENTRANCE SILL DEPTH

F4.5 ELEVATOR LOAD TABLES
NOT TO SCALE



E4.5 DIMENSIONS AT ELEVATOR SHAFT
NOT TO SCALE

I4.5 ENLARGED PLAN AT ELEVATOR
SCALE: 1/2" = 1'-0"

SHEET SIZE: 24 X 36 SCALE: 3/8" = 1'-0"

**OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA**

**LAND 3
Architect**


LAND 3 ARCHITECT, INC.
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA.
71201-5786




DRAWN BY: GWM
CHK'D BY: WAL
JOB #: 1963
DATE: 08/2024
COPYRIGHT PROTECTED

ENLARGED ELEVATOR PLAN & DETAILS


A4.5



C ELEVATOR RAIL
A4.6 DETAIL SCALE: 1 1/2" = 1'-0"




B ELEVATOR SILL OPENING
A4.6 AT SECOND FLOOR SCALE: 1 1/2" = 1'-0"




A ELEVATOR DOOR OPNG.
A4.6 DETAILS SCALE: 1 1/2" = 1'-0"


F DELETED
A4.6




E PROJECTION SCREEN
A4.6 DETAIL EAST WALL AT AREA 119 NOT TO SCALE




D PROJECTOR MOUNT
A4.6 DETAIL FOR AREA 119 NOT TO SCALE




DETAIL 2 ANCHOR AT JAMB SCALE: 1 1/2" = 1'-0"
DETAIL 3 ANCHOR AT INTERMEDIATE SCALE: 1 1/2" = 1'-0"




DETAIL 4 OUTRIGGER AT JAMB SCALE: 3" = 1'-0"
DETAIL 5 OUTRIGGER AT INTERMEDIATE SCALE: 3" = 1'-0"




EXAMPLE OF LONG ANCHOR FOR SCREW SPLINE FRAMING NOT TO SCALE



G ALUMINUM SUN-SHADE
A4.6 DETAILS SCALE: 1 1/2" = 1'-0"



I ACOUSTIC SLAT WOOD
A4.6 PANEL DETAIL (SOUTH WALL) SCALE: 1 1/2" = 1'-0"



H ACOUSTIC SLAT WOOD
A4.6 PANEL DETAIL (NORTH WALL) SCALE: 1 1/2" = 1'-0"

OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA

LAND 3
Architect

LAND 3
ARCHITECT, INC.
A PROFESSIONAL CORPORATION
1800 STUBBS AVENUE
MONROE, LA.
71201-5786


WILLIAM A. LAND
No. 4155
STATE OF LOUISIANA
REGISTERED ARCHITECT

DRAWN BY: GWM
CHK'D BY: WAL
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED


ELEVATOR DETAILS,
MOUNTING DETAILS,
& SUN SHADE DETAILS

A4.6


SHEET SIZE: 24 X 36 SCALE: 1 1/2" = 1'-0"




J
A5.2 WINDOW HEAD DETAIL
NEW METAL PANEL AT EXISTING TILE ABOVE WINDOW
SCALE: 3" = 1'-0"




K
A5.2 ROOF DECK REPAIR DETAIL
SCALE: 1" = 1'-0"
SEE UNIT PRICE INSTRUCTIONS IN SPECIFICATIONS




I
A5.2 ENLARGED DETAIL
E.I.F.S. CORNICE MOULDING




H
A5.2 SECTION THRU BOOK DROP
SCALE: 1" = 1'-0"




G
A5.2 ENLARGED DETAIL
AT BRICK CANOPY COLUMNS
SHOWING BOOK DROP
SCALE: 1" = 1'-0"




F
A5.2 ENLARGED ELEVATION AT
FRAMING FOR COMPOSITE SIDING
SCALE: 1/2" = 1'-0"




E
A5.2 ENLARGED SECTION AT
METAL PANEL TO COMPOSITE SIDING
AT EXISTING BRICK ABOVE WINDOW
SCALE: 2" = 1'-0"




D
A5.2 ENLARGED SECTION AT
METAL PANEL TO COMPOSITE SIDING
AT EXISTING TILE ABOVE WINDOW
SCALE: 2" = 1'-0"



C
A5.2 ENLARGED DETAIL
AT COMPOSITE SIDING
SCALE: 1" = 1'-0"




B
A5.2 ENLARGED DETAIL
AT BRICK CANOPY COLUMNS
SCALE: 1" = 1'-0"




A
A5.2 ENLARGED DETAIL
AT BRICK CANOPY COLUMNS
SCALE: 1" = 1'-0"


SHEET SIZE: 24 X 36 SCALE: 1" = 1'-0"




B EXT. ALUMINUM DOOR
A5.3 CANOPY SECTION NOT TO SCALE




D EXT. WALL PATCH WP1
A5.3 WHERE EXTERIOR DOORS, EQUIPMENT, ETC. ARE REMOVED
SCALE: 1 1/2" = 1'-0"




K UTILITY PATCH DETAIL
A5.3 AT EXISTING SLAB N.T.S.
NOTE: REQUIRED AT ALL SAW-CUTTING FOR UTILITIES UNDER GROUND FLOOR. VERIFY LOCATIONS REQUIRED WITH MECHANICAL, PLUMBING, AND ELECTRICAL DRAWING SHEETS (VERIFY PRIOR TO BIDS)




J GYPSUM BOARD
A5.3 FURR-DOWN F.D.-3 SCALE: 1" = 1'-0"




A PENTHOUSE PENETRATION
A5.3 THRU EXISTING ROOF SCALE: 1 1/2" = 1'-0"




C PENTHOUSE PENETRATION
A5.3 THRU EXISTING ROOF SCALE: 1 1/2" = 1'-0"




F TYP. SHEET-ROCK PATCH WP2
A5.3 WHERE INTERIOR DOORS, EQUIPMENT, ETC. ARE REMOVED
NOT TO SCALE



E TYP. MASONRY WALL PATCH WP3
A5.3 WHERE INTERIOR DOORS, EQUIPMENT, ETC. ARE REMOVED
NOT TO SCALE



I GYPSUM BOARD
A5.3 FURR-DOWN F.D.-2 SCALE: 1" = 1'-0"



H PRE-HUNG DOOR DETAIL IN
A5.3 NEW WALL OPNG. SCALE: 3" = 1'-0"

**OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA**

**LAND 3
Architect**


LAND 3
ARCHITECT, INC.
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA.
71201-5786

NO. 4155
REGISTERED ARCHITECT
STATE OF LOUISIANA

DRAWN BY: LOH
CHK'D BY: WAL
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED


ELEVATOR PENTHOUSE
WALL SECTIONS,
MISC. DETAILS, &
& FURR-DOWN DETAILS
A5.3

SHEET SIZE: 24 X 36 SCALE: 1 1/2" = 1'-0"



REFER TO PLANS & SPEC. SECTIONS FOR LOCATIONS OF EQUIPMENT REQUIRING WALL BLOCKING (BY SECTION 06 10 01)


C TYP. BLOCKING DETAIL FOR ALL WALL MOUNTED EQUIPMENT SCALE: 3" = 1'-0"



NOTE: WHERE APPLICABLE RUN WALLCOVERING IN JOINT (FIN. SCH.)


NOTE: WHERE APPLICABLE RUN WALLCOVERING IN JOINT (FIN. SCH.)

F GYPSUM BOARD CONTROL JOINT DETAILS NOT TO SCALE (COMPLY WITH SECTION 09 21 16)




NOTE: THIS DETAIL IS CONCEPTUAL - SIZE & FASTENERS AS REQUIRED BY STRUCTURAL DESIGN CALCULATIONS AND IN ACCORDANCE WITH SECTION 05 40 00

I TYP. METAL STUD HEADER @ EXTERIOR WINDOW/DOOR OPENINGS (PROVIDED BY SECTION 05 40 00)



ENLARGED PLAN OF POCKET DOOR SCALE: 1/4" = 1'-0"


BOTTOM PANEL EDGE N.T.S.



JAMB AT FINISHED WALL N.T.S.



EXPANDABLE PANEL W/ SOFT SEAL N.T.S.

L FOLDING WALL MISC. DETAILS




TYPICAL SEALANT JOINT
THE DEPTH OF THE OPENING SHALL BE 1/2" THE WIDTH OF THE JOINT. IN DEEP OPENINGS, THE DEPTH OF THE SEALANT SHALL BE CONTROLLED WITH A CLOSED CELL, "NON GASSING" TYPE BACKER ROD. THE BACKER ROD SHALL BE ABOUT 1/8" WIDER THAN THE OPENING. PREVENT 3 POINT ADHESION WITH BACKER RODS OR BOND BREAKER TAPE.

B TYPICAL SEALANT JOINTS NOT TO SCALE (COMPLY WITH SECTION 07 92 00)




E TYPICAL DRYWALL FRAMING DETAILS NOT TO SCALE (COMPLY WITH SECTION 09 21 16)




H METAL STUD BLOCKING/ BRIDGING DETAIL NOT TO SCALE


REFER TO SECTION 05 40 00 FOR ENGINEERING REQUIREMENTS




K FOLDING WALL HEAD DETAIL SCALE: 1 1/2" = 1'-0"




A TYPICAL APPROACH TO ALL NEW SWINGING DOORS N.T.S.



D TYPICAL GYPSUM BOARD SYSTEMS NOT TO SCALE (COMPLY WITH SECTION 09 21 16)



E ALUMINUM TRIM AT WALL CORNERS SCALE: 3" = 1'-0"




J SURFACE MOUNT WALL CORNER GAUARD SCALE: 3" = 1'-0"


NOTE: ALUMINUM TUBE MEMBER SHOWN IS BASED ON INFORMATION FOR PRODUCTS AS MANUFACTURED BY "KAWNEER" EQUAL APPROVED PRODUCTS BY "VISTAWALL", "YKOC" OR "U.S. ALUMINUM MAY BE SUBSTITUTED & USED

SHEET SIZE: 24 X 36 SCALE: 1 1/2" = 1'-0"

OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA



LAND 3 ARCHITECT, INC.
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA.
71201-5786




DRAWN BY: LOH
CHK'D BY: WAL
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED

MISC. DETAILS

A5.4

Design No. U425

(For Exterior Walls, Ratings Applicable For
Exposure To Fire On Interior Face Only)
See Items NO. 4 & 5
Bearing Wall Rating - 1 HR.
See Items No. 2 & 4




**Horizontal Section
EXTERIOR WALL**

1. **steel floor and ceiling tracks** — (not shown) — top and bottom tracks of wall assemblies shall consist of steel members, min no. 20 msg (0.0329 in., min bare metal thickness) steel or min no. 20 msg (0.036 in. thick) galv steel or no. 20 msg (0.033 in. thick) primed steel, that provide a sound structural connection between steel studs, and to adjacent assemblies such as a floor, ceiling, and/or other walls, attached to floor and ceiling assemblies with steel fasteners spaced not greater than 24 in. o.c.
2. **steel studs** — min 3-1/2 in. wide, no. 20 msg (0.0329 in., min bare metal thickness) corrosion protected cold formed steel studs designed in accordance with the current edition of the specification for the design of cold-formed steel structural members by the american iron and steel institute. all design details enhancing the structural integrity of the wall assembly, including the axial design load of the studs, shall be as specified by the steel stud designer and/or producer, and shall meet the requirements of all applicable local code agencies. the max stud spacing of wall assemblies shall not exceed 24 in. oc (or 16 in. oc when item 5b is used). studs attached to floor and ceiling tracks with 1/2 in. long type s-12 steel screws on both sides of studs or welded or bolted connections designed in accordance with the aisi specifications.
3. **lateral support members** — (not shown) — where required for lateral support of studs, support may be provided by means of steel straps, channels or other similar means as specified in the design of a particular steel stud wall system.
4. **gypsum board*** — any 1/2 in. thick ul classified gypsum board that is eligible for use in design no. x515. any 5/8 in. thick ul classified gypsum board that is eligible for use in design nos. 1501, g512 or u305. gypsum board bearing the ul classification marking as to fire resistance. applied vertically with joints between layers staggered. outer layer of 3 layer construction may be applied horizontally unless specified below. the thickness and number of layers and percent of design load for the 45 min, 1 hr, 1-1/2 hr and 2 hr ratings are as follows:
4b. **gypsum board*** — (as an alternate to item 4) — non. 5/8 in. thick gypsum panels, with square edges, applied horizontally. gypsum panels fastened to framing with 1 in. long bugle head steel screws spaced a max 8 in. oc, with last 2 screws 3/4 in. and 4 in. from each edge of board. horizontal joints need not be backed by steel framing. horizontal edge joints and horizontal butt joints on opposite sides of studs on interior walls need not be staggered. horizontal edge joints and horizontal butt joints in adjacent layers on interior walls (multilayer systems) staggered a min of 12 in.
Exterior Walls (Fire from Interior Side Only)


Rating	Wallboard Protection on Interior Side of Wall - No. of Layers & Thickness of Board In. Each Layer	% of design load
45 min	1 LAYER 5/8" thick	100
1 hr	2 LAYERS 1/2" THICK, see 4b for 1 layer 5/8" thick	100
1 1/2 hr	2 LAYERS 5/8" thick	100
2 hr	3 LAYERS 1/2" thick	100
2 hr	2 LAYERS 5/8" thick	100

5. **gypsum boards** — for exterior walls, rating from interior side only - 1/2 or 5/8 in. thick classified or unclassified gypsum boards applied vertically and attached to studs and runner tracks with 1 in. long type s-12 bugle head screws spaced 12 in. oc. along studs and tracks. one of the following exterior facings are to be applied over the gypsum board.
(a) siding, brick, or stucco — aluminum siding, steel siding, brick veneer, or stucco attached to studs over gypsum sheathing and meeting the requirements of local code agencies. when a min 3-3/4 in. thick brick veneer facing is used, the exterior wall rating is applicable with exposure on either face. brick veneer wall attached to studs with corrugated metal wall ties attached to each stud with steel screws, not more than each sixth course of brick. when a min 3-3/4 in. thick brick veneer facing is used, foamed plastic (item 10) may be used.
6. **fasteners** — (not shown) — screws used to attach wallboard to studs: self-tapping bugle head steel type, spaced 12 in. o.c. first layer type s-12 by 1 in. long for 1/2 and 5/8 in. thick wallboards and 1-1/4 in. long for 3/4 in. thick wallboard. second layer type s-12 by 1-5/8 in. long for 1/2 and 5/8 in. thick wallboards and 2-1/4 in. long for 3/4 in. thick wallboard. third layer type s-12 by 1-7/8 in. long. fasteners when item 4g is used: first layer #6 x 2 in. long drywall screw spaced 8 in. oc along the perimeter and 12 in. oc in the field. second layer #6 x 4 in. long drywall screw spaced 8 in. oc along the perimeter and 12 in. oc in the field. horizontal joints to be staggered 12 in. between layers.
7. **batts and blankets*** — placed in stud cavities of all exterior walls. may or may not be used in interior walls. any glass fiber or mineral wool batt material bearing the ul classification marking as to fire resistance, of a thickness to completely fill stud cavity. see batts and blankets* (b2g) category for names of classified companies.
7a. **fiber, sprayed*** — as an alternate to batts and blankets (item 7) — spray applied cellulose fiber. the fiber is applied with water to completely fill the enclosed cavity in accordance with the application instructions supplied with the product. the minimum dry density shall be 4.30 lbs/ft.
7d. **fiber, sprayed*** — (optional) — as an alternate to batts and blankets (item 7) — spray applied mineral wool insulation. the fiber is applied with adhesive, at a minimum density of 4.0 pcf, to completely fill the enclosed cavity in accordance with the application instructions supplied with the product.
8. **joint tape and compound** — (not shown) — vinyl or cassin, dry or premixed joint compound applied in two coats to joints and screw heads of outer layer. perforated paper tape, 2 in. wide, embedded in first layer of compound over all joints of outer layer.
9. **furring channels** — (optional, not shown, for single or double layer systems) — resilient furring channels fabricated from min 25 msg corrosion-protected steel, spaced vertically a max of 24 in. oc. flange portion attached to each intersecting stud with 1/2 in. long type s-12 steel screws.



**J FIRE WALL LABEL
A5.5 (TYPICAL FOR ALL RATED WALLS)**
NOT TO SCALE

**Design No. U465
Assembly Rating - 1 HR Nonbearing Wall**




1. **Floor and Ceiling Runners** - (not shown) - Channel shaped runners, 3-5/8 in. wide (min), 1-1/4 in. legs, formed from min No. 25 MSG galv steel, attached to floor and ceiling with fasteners spaced 24 in. OC max.
2. **Steel Studs** - Channel shaped, 3-5/8 in. wide (min), 1-1/4 in. legs, 3/8 in. folded back returns, formed from min No. 25 MSG galv steel spaced 24 in. OC max.
3. **Batts and Blankets*** - (Optional) - Mineral wool or glass fiber batts partially or completely filling stud cavity. See Batts and Blankets* (D2Z2) category for names of Classified companies.
3A. **Fiber, Sprayed*** - As an alternate to Batts and Blankets (Item 3) - Spray applied cellulose material. The fiber is applied with water to completely fill the enclosed cavity in accordance with the application instructions supplied with the product. Nominal dry density of 3.0 lb/ft³. Alternate application method: The fiber is applied with U.S. Greenfiber LLC Type AD100 hot melt adhesive at a nominal ratio of one part adhesive to 6.6 parts fiber to completely fill the enclosed cavity in accordance with the application instructions supplied with the product. Nominal dry density of 2.5 lb/ft³.
3B. **Fiber, Sprayed*** - As an alternate to Batts and Blankets (Item 3) and Item 3A - Spray applied cellulose insulation material. The fiber is applied with water to interior surfaces in accordance with the application instructions supplied with the product. Applied to completely fill the enclosed cavity. Minimum dry density of 4.3 pounds per cubic ft.
4. **Gypsum Board*** - 5/8 in. thick, 4 ft wide, attached to steel studs and floor and ceiling track with 1 in. long, Type S steel screws spaced 8 in. OC. along edges of board and 12 in. OC in the field of the board. Joints oriented vertically and staggered on opposite sides of the assembly. When attached to item 6 (resilient channels) or 6A (furring channels), wallboard is secured to studs with 1 in. long, Type S steel screws spaced 12 in. OC.
4A. **Gypsum Board*** - (As alternate to Item 4) - Non 5/8 in. thick gypsum panels with beveled, square or tapered edges, applied vertically or horizontally. Vertical joints centered over studs and staggered one stud cavity on opposite sides of studs. Horizontal edge joints and horizontal butt joints on opposite sides of studs need not be staggered or backed. Panels attached to steel studs and floor runner with 1 in. long Type S steel screws spaced 8 in. OC when applied horizontally, or 8 in. OC along vertical and bottom edges and 12 in. OC in the field when panels are applied vertically.
4B. **Gypsum Board*** - (As an alternate to Items 4 or 4A) - Non 3/4 in. thick, 4 ft wide, installed as described in Item 4A with screw length increased to 1-1/4 in.

5. **Joint Tape and Compound** - Vinyl, dry or premixed joint compound, applied in two coats to joints and screw heads; paper tape, 2 in. wide, embedded in first layer of compound over all joints. As an alternate, nominal 3/32 in. thick gypsum veneer plaster may be applied to the entire surface of Classified veneer baseboard. Joints reinforced.
6. **Resilient Channel** - (Optional-Not Shown) - 25 MSG galv steel resilient channels spaced vertically max 24 in. OC, flange portion attached to each intersecting stud with 1/2 in. long type S-12 panhead steel screws.
6A. **Steel Framing Members** - (Not Shown)* - As an alternate to Item 3, furring channels and resilient sound isolation clip as described below:
a. **Furring Channels** - Formed of No. 25 MSG galv steel, 2-3/8 in. wide by 7/8 in. deep, spaced 24 in. OC perpendicular to studs. Channels secured to studs as described in Item b. Ends of adjoining channels are overlapped 6 in. and tied together with double strand of No. 18 SWG galv steel wire near each end of overlap. As an alternate, ends of adjoining channels may be overlapped 6 in. and secured together with two self-tapping #6 framing screws, min. 7/16 in. long at the midpoint of the overlap, with one screw on each flange of the channel.
b. **Steel Framing Members*** - Used to attach furring channels (Item a) to studs (Item 1). Clips spaced 48 in. OC, and secured to studs with 1-5/8 in. wafer or hex head Type 5 steel screw through the center grommet. Furring channels are friction fitted into clips.
*Bearing the UL Classification Mark


**I 1hr. FIRE BARRIER DESIGN NO. U465
A5.5 NOT TO SCALE (PAGE NO. 983 IN 2007 U.L. FIRE RESISTANCE DIRECTORY)**

**EXTERIOR 1hr. FIRE BARRIER DESIGN NO. U425
(APPLIES TO EXT. PENTHOUSE ELEV. WALLS)**

H A5.5 NOT TO SCALE (PAGE NO. 983 IN 2007 U.L. FIRE RESISTANCE DIRECTORY)



**G SEALANT FIRE STOPPING DETAILS
A5.5 (COMPLY WITH SECTION 07 84 00) NOT TO SCALE**




MINIMUM EQUIVALENT THICKNESS CALCULATION FOR CMU BLOCK
 $T_e = 1728 A / (L \times H)$
WHERE:
 T_e = EQUIVALENT THICKNESS, IN.
A = NET VOLUME OF UNIT, FT.
L = LENGTH OF UNIT, IN.
H = HEIGHT OF UNIT, IN.
NET VOLUME "A" IS DETERMINED BY THE FOLLOWING EQUATION:
 $A = C/D$ (SEE ATTACHED DATA)
WHERE:
C = DRY WEIGHT OF UNIT, POUNDS. (28 LBS.)
D = DENSITY OF UNIT, PER CUBIC FOOT. (105 LBS./FT.)
 $T_e = (1.728 \text{ IN.} \cdot 3/\text{FT.}) / (0.27 \text{ FT.} \cdot (16.625 \text{ IN.} \cdot 7.625 \text{ IN.}))$
 $T_e = 3.9 \text{ INCHES.}$
2 3/4 HOUR FIRE RATING PER TABLE OF MINIMUM EQUIVALENT THICKNESS OF BEARING AND NONBEARING CONC. MASONRY WALLS IN - 2021 INTERNATIONAL BUILDING CODE

CALCULATIONS FOR EXISTING HOLLOW FACE BRICK **CALCULATIONS FOR EXISTING 8" CMU BLOCK**

**F EXISTING FIREWALL EQUIVALANCY
A5.5 CALCULATIONS (for existing masonry walls at stairs)**
NOT TO SCALE


PROVIDE ALL REQUIRED MATERIALS AS OUTLINED IN THE UNDERWRITERS' LABORATORY DIRECTORY AND AS NEEDED FOR FIRE MARSHALL COMPLIANCE



REFER TO PARTITION TYPES ON SHEET A6.1 FOR FIRE BARRIER LOCATIONS
REFER TO DETAIL I/A5.5 FOR UL REQUIREMENTS

**E ONE HOUR FIRE BARRIER (U.L. U465)
A5.5 PARALLEL TO METAL ROOF DECK** SCALE: 1 1/2" = 1'-0"


PROVIDE ALL REQUIRED MATERIALS AS OUTLINED IN THE UNDERWRITERS' LABORATORY DIRECTORY AND AS NEEDED FOR FIRE MARSHALL COMPLIANCE




REFER TO PARTITION TYPES ON SHEET A6.1 FOR FIRE BARRIER LOCATIONS
REFER TO DETAIL I/A5.5 FOR UL REQUIREMENTS

**D ONE HOUR FIRE BARRIER (U.L. U465)
A5.5 PERPENDICULAR TO METAL ROOF DECK** SCALE: 1 1/2" = 1'-0"

**C TYPICAL PENETRATION THRU
A5.5 GYP. BOARD WALLS
SMOKETIGHT & NON FIRE RATED**



**B PIPE THRU CONCRETE FLOOR
A5.5 SMOKETIGHT & NON FIRE RATED**




**A FIRE RATED GYPSUM BOARD
A5.5 CONTROL JOINT** NOT TO SCALE


SHEET SIZE: 24 X 36 SCALE: 1 1/2" = 1'-0"

****NOT REQUIRED BY CODE -**


***NOTE: INSTALL CEILING SYSTEM IN ACCORDANCE WITH UNDERWRITERS LABORATORY DESIGN NO L536**



A 2 HOUR FIRE RATED CEILING TERMINATION AT FIRE WALL SCALE: 1 1/2" = 1'-0"




B TWO HOUR FIRE BARRIER (U.L. U411) PARALLEL TO METAL ROOF DECK SCALE: 1 1/2" = 1'-0"



C TWO HOUR FIRE BARRIER (U.L. U411) PERPENDICULAR TO METAL ROOF DECK SCALE: 1 1/2" = 1'-0"

****NOT REQUIRED BY CODE -**

UL DESIGN NO. L536 Unrestrained Assembly Rating - 2 HR. Finish Rating - 71 min.




- FIRST LAYER END JOINT DETAIL** **SECOND LAYER END JOINT DETAIL**
- FLOORING SYSTEM NO. 2:** The Flooring System Shall Consist of The Following - SUB-FLOORING - Min. 23/32" thick plywood min. grade "c-d" or "sheathing". Face grain of ply-wood or strength axis of panel to be perpendicular to joists with joints staggered. VAPOR BARRIER - Nom. 0.010 in. thick commercial rosin - sized building paper. FINISH FLOORING - Min. 23/32" in. thick wood structural panels, min. grade "under-layment" or "single-floor". Face grain of ply-wood or strength axis of panels to be perpendicular to joists with joints staggered.
 - WOOD JOISTS** - Min. 2 x 10 Spaced 16 in. o.c. and effectively fire blocked in accordance with local codes.
 - CROSS BRIDGING** - Min. 1 by 3 in. or Min. 2 by 10 in. Solid blocking.
 - RESILIENT CHANNELS** - Formed of 25 MSG galv. steel, spaced 24in. o.c. perpendicular to joists and located 12in. from each side edge of base layer gypsum board. Channels placed with a 1/4in. clearance at the ends and located 12in. from each joist with 1-7/8in. long no. 7 type s bugle head screws. Min. and clearance of channels to walls; 3/8in. Additional channels 60in. long, placed adjacent to continuous channels at end joints of second layers of gypsum board (Item 5) and similarly secured. Channel ends to extend 6in. beyond each side of joints.
 - GYPSON BOARD*** - Two layers Nom. 5/8 in. thick, 4ft. wide gypsum board. First layer installed perpendicular to joists with end joints located under bottom of joists. Gypsum board attached to joists with 8d cement coated cooler nails 7 in. o.c. Nails shall be 1/2" from the butted end joints. Second layer installed with long edge perpendicular to the resilient channels, with the centerline of boards located under a joist and so placed that the long edge joints are staggered with the butted end joints of the first layer. Gypsum board secured to resilient channels with 1in. long no. 7 type s-12 bugle head steel screws spaced 12in. o.c. Butted end joints of gypsum board fastened at additional furring channels as shown in end joint detail. All screws shall be located 1 and 1-3/4in. from side joints and butted end joints of boards, respectively.
 - FINISHING SYSTEM (NOT SHOWN)** - Vinyl, dry or premixed joint compound, applied in two coats to joints and screw heads. Nom. 2in. wide paper tape embedded in first layer of compound over all joints. As an alternate nom. 3/32 in. thick veneer plaster may be applied to the entire surface of gypsum board. *Bearing the u.l. classification mark.

D 2hr. CEILING ASSEMBLY DESIGN NO. L536 NOT TO SCALE (PAGE NO. 494 - 496 IN 2007 U.L. FIRE RESISTANCE DIRECTORY) APPLIES TO AREA 172

****NOT REQUIRED BY CODE - FOR AREA 172**

Design No. U411 Assembly Rating - 2 HR Nonbearing Wall




- Floor and Ceiling Runners** - (not shown) - Min. 25 MSG galv. steel 1 in. high, return legs 2-1/2 in. wide (min.), attached to floor and ceiling with fasteners 24" in. o.c.
- Steel Studs** - Channel shaped, 3-5/8 in. wide (min), 1-1/4 in. legs, 3/8 in. folded back returns, formed from min. No. 25 MSG galv steel spaced 24 in. OC max. Studs to be cut 3/4 in. less than assembly height.
- Batts and Blankets*** - (Optional) - Mineral wool or glass fiber batts partially or completely filling stud cavity. See Batts and Blankets (B/Z/Z) category for names of Classified companies.
 - Fiber, Sprayed*** - As an alternate to Batts and Blankets (Item 3) - Spray applied cellulose insulation material. The fiber is applied with water to completely fill the enclosed cavity in accordance with the application instructions supplied with the product. Nominal dry density of 3.0 lb/ft³. Alternate application method: The fiber is applied with U.S. Greenfiber LLC Type AD100 hot melt adhesive at a nominal ratio of one part adhesive to 6.6 parts fiber to completely fill the enclosed cavity in accordance with the application instructions supplied with the product. Nominal dry density of 2.5 lb/ft³.
 - Fiber, Sprayed*** - As an alternate to Batts and Blankets (Item 3) and Item 3A - Spray applied cellulose insulation material. The fiber is applied with water to interior surfaces in accordance with the application instructions supplied with the product. Applied to completely fill the enclosed cavity. Minimum dry density of 4.3 pounds per cubic ft.
- Gypsum Board*** - 5/8 in. thick outer layer paper or vinyl surfaced, (laminated system) wallboard applied vertically in two layers, inner layer attached to steel studs with 1" long type s steel screws spaced 8" o.c. along vertical edges, and 12" o.c. in the field and outer layer laminated to inner layer with joint compound applied with a notched spreader producing cont. beads of compound about 3/8" in dia. spaced no greater than 2" o.c. joints of laminated outer layer offset 12" from inner layer joints, outer layer wallboard attached to floor and ceiling runner track with 1 5/8" long type s steel screws spaced 12" o.c. (DIRECT ATTACHED SYSTEM) inner layer attached to steel studs with 1" long type s steel screws spaced 16" o.c. in the field and along vertical edges outer layer attached to the studs over the inner layer with 1 5/8" long type s steel screws spaced 16" o.c. in the field and along vertical edges and 12" o.c. to the floor and ceiling runners. Joints of screw attached outer layer offset from inner layer joints. Joints of outer layer to be taped.
- Gypsum Board*** - (As alternate to Item 4) - Nom 3/4 in. thick gypsum panels installed as described in item 4 with 1 1/4 in. long type s screws for inner layer and 2 1/4 in. long type s screws for outer layer.
- Gypsum Board*** - (As an alternate to Items 4 or 4A) - Nom. 5/8 thick 24 to 54 in. wide applied horizontally as the outer layer to one side of the assembly. Secured as described in item 4 for the direct attached system. When used in widths other than 48 in. gypsum panels shall be installed horizontally.
- Joint Tape and Compound** - Vinyl, dry or premixed joint compound, applied in two coats to joints and screw heads; paper tape, 2 in. wide, embedded in first layer of compound over all joints. As an alternate, nominal 3/32 in. thick gypsum veneer plaster may be applied to the entire surface of Classified veneer baseboard. Joints reinforced.

E 2hr. FIRE BARRIER DESIGN NO. U411 NOT TO SCALE (PAGE NO. 952 & 953 IN 2007 U.L. FIRE RESISTANCE DIRECTORY)

SHEET SIZE: 24 X 36 SCALE: 1 1/2" = 1'-0"

**OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA**




LAND 3 ARCHITECT, INC.
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA.
71201-5786



DRAWN BY: GWM
CHKD BY: WAL
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED

**FIRE BARRIER/WALL
DETAILS & MISC.
FIRE RATING DETAILS**


A5.6



DRAWN BY: GWM
CHK'D BY: WAL
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED

1st & 2nd FLOOR
PARTITION PLANS

A6.1




1st FLOOR PLAN
SCALE: 1/16" = 1'-0"
REF. NORTH

2nd FLOOR PLAN
SCALE: 1/16" = 1'-0"
REF. NORTH

GENERAL NOTES:
REFER TO SECTION 09 21 16 IN SPECIFICATIONS FOR NON-STRUCTURAL STEEL FRAMING FOR INTERIOR WALLS AND PARTITIONS INDICATED ON PLANS.
REFER TO MECHANICAL, ELECTRICAL, AND PLUMBING SHEETS FOR DUCT OR PIPING LOCATIONS THAT PENETRATE FLOORS/WALLS. THESE SHALL BE SEALED AS SHOWN ON DETAILS B,C/A5.5
CONTRACTOR SHALL NOTIFY ARCHITECT OF ALL DISCREPANCIES & CONFLICTS PRIOR TO BIDS IN ACCORDANCE WITH SPECIFICATIONS.

PARTITION NOTES

- NOTE: ALL HUMID/ WET AREAS SHALL HAVE GYPSUM BOARD ON EACH SIDE OF STUDS BY SECTION 09 21 16 (TAPE, FLOAT, & PAINT BY SECTION 09 90 00)
- SEE ROOM FINISH SCHEDULE & INTERIOR ELEVATIONS FOR WALL FINISHES. (SOME PARTITIONS WILL HAVE MULTIPLE FINISHES ON ONE OR BOTH SIDES.)
- A PARTITION TYPE TO BE PROVIDED, RE: PLANS & PARTITION SECTIONS THIS SHEET.
- ALL PENETRATIONS IN FIRE BARRIERS SHALL BE SEALED WITH APPROPRIATE RATED FIRE SEALANT OR U.L. RATED SEALANT ASSEMBLY.
- PROVIDE 3" HIGH LETTERS ABOVE CEILINGS DENOTING FIRE BARRIER EACH SIDE OF ALL FIRE RATED WALLS.
- ALL PENETRATIONS IN SOUND RATED WALLS SHALL BE SEALED WITH AN ACOUSTICAL SEALANT. FIRE/SMOKE SEALANT SHALL TAKE PRECEDENCE OVER ACOUSTICAL SEALANT WHERE FIRE SEALANT IS REQUIRED.
- SEAL AROUND ALL PENETRATIONS IN FIRE BARRIERS, INCLUDING MECHANICAL, PLUMBING AND ELECTRICAL MATERIALS WITH AN APPROPRIATE U.L. RATED FIRE STOPPING SYSTEM. REFER TO MEP SHEETS FOR WALL PENETRATIONS.
- INSTALL FIRE RATED SEALANT STOPPING SYSTEMS FOR ALL PENETRATIONS IN FIRE RATED WALLS AND INSTALL ACOUSTICAL SEALANT AROUND ALL PENETRATIONS IN SOUND RATED WALLS.
- THERE ARE MANY PARTICULAR REQUIREMENTS FOR THE INTERIOR WALLS IN THIS PROJECT INCLUDING SOUND, FIRE, AND STRUCTURAL. MOCKUPS OF EACH WALL TYPE WILL BE REQUIRED & MUST RECEIVE ARCHITECT'S APPROVAL PRIOR TO FINAL INSTALLATION.
- PROVIDE A 4" MIN. JAMB ON HINGE SIDE, TYP. FOR ALL NEW INTERIOR DOORS.



A PARTITION SECTION
3 5/8" METAL STUDS

E PARTITION SECTION
FULL HEIGHT 6" METAL STUDS - SOUND RATED

H PARTITION SECTION
NEW WALL EXTENSION AT EXIST. PARTITION

K PARTITION SECTION
2 HOUR FIRE BARRIER U.L. DESIGN U411

D PARTITION SECTION
6" METAL STUDS - SOUND RATED

C PARTITION SECTION
3 5/8" METAL STUDS - SOUND RATED

G PARTITION SECTION
1 HOUR FIRE BARRIER U.L. DESIGN NO. U425/U465 (AT ELEVATOR SHAFT)

F PARTITION SECTION
1 HOUR FIRE BARRIER U.L. DESIGN NO. U465

J PARTITION SECTION
3 5/8" METAL STUDS - CHASE WALL

I PARTITION SECTION
1 HOUR FIRE BARRIER U.L. DESIGN NO. U465

B6 PARTITION SECTION
6" METAL STUDS - to bottom of exist. ceiling

B PARTITION SECTION
3 5/8" METAL STUDS - to bottom of exist. ceiling

A6 PARTITION SECTION
3 5/8" METAL STUDS - to bottom of exist. ceiling

A PARTITION SECTION
3 5/8" METAL STUDS - to bottom of exist. ceiling

A PARTITION SECTION
3 5/8" METAL STUDS - to bottom of exist. ceiling

A PARTITION SECTION
3 5/8" METAL STUDS - to bottom of exist. ceiling

A PARTITION SECTION
3 5/8" METAL STUDS - to bottom of exist. ceiling

A PARTITION SECTION
3 5/8" METAL STUDS - to bottom of exist. ceiling









































































































A PARTITION SECTION
3 5/8" METAL STUDS - to bottom of exist. ceiling

A PARTITION SECTION
3 5/8" METAL STUDS - to bottom of exist. ceiling


A PARTITION SECTION
3 5/8" METAL STUDS - to bottom of exist. ceiling

A PARTITION SECTION
3 5/8" METAL STUDS - to bottom of exist. ceiling


A PARTITION SECTION
3 5/8" METAL STUDS - to bottom of exist. ceiling




SHEET SIZE: 24 X 36 SCALE: 3" = 1'-0"




C TRANSOM DETAIL
A7.1 SCALE: 3" = 1'-0"




F TRANSOM DETAIL
A7.1 SCALE: 3" = 1'-0"




I TRANSOM DETAIL
A7.1 SCALE: 3" = 1'-0"




L HEAD DETAIL
A7.1 SCALE: 3" = 1'-0"




B JAMB DETAIL
A7.1 SCALE: 3" = 1'-0"




E JAMB DETAIL
A7.1 SCALE: 3" = 1'-0"




H JAMB DETAIL
A7.1 SCALE: 3" = 1'-0"




K JAMB DETAIL
A7.1 SCALE: 3" = 1'-0"




A SILL DETAIL
A7.1 SCALE: 3" = 1'-0"



D SILL DETAIL
A7.1 SCALE: 3" = 1'-0"



G SILL DETAIL
A7.1 SCALE: 3" = 1'-0"



J JAMB DETAIL
A7.1 SCALE: 3" = 1'-0"

AUTOMATIC SLIDING DOOR UNIT

EXT. ALUM. STOREFRONT DOOR - NEW WALL OPNG.


ALUMINUM STOREFRONT ENTRANCE DOOR

EXTERIOR H.M. DOOR - NEW WALL OPENING

OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA

LAND 3 Architect

LAND 3 ARCHITECT, INC.
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA. 71201-5786




DRAWN BY: GWM
CHKD BY: WAL
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED


DOOR DETAILS

A7.1


SHEET SIZE: 24 X 36 SCALE: 3" = 1'-0"




C HEAD DETAIL
A7.2 SCALE: 3" = 1'-0"




F HEAD DETAIL
A7.2 SCALE: 3" = 1'-0"




I HEAD DETAIL
A7.2 SCALE: 3" = 1'-0"




L HEAD DETAIL
A7.2 SCALE: 3" = 1'-0"




B JAMB DETAIL
A7.2 SCALE: 3" = 1'-0"




E JAMB DETAIL
A7.2 SCALE: 3" = 1'-0"




H JAMB DETAIL
A7.2 SCALE: 3" = 1'-0"




K JAMB DETAIL
A7.2 SCALE: 3" = 1'-0"




A SILL DETAIL
A7.2 SCALE: 3" = 1'-0"



D SILL DETAIL
A7.2 SCALE: 3" = 1'-0"



G SILL DETAIL
A7.2 SCALE: 3" = 1'-0"



J SILL DETAIL
A7.2 SCALE: 3" = 1'-0"


EXT. ALUMINUM STOREFRONT TRANSOM DOORS MK.100a & 100b

INT. ALUMINUM STOREFRONT TRANSOM DOORS MK.101a & 101b


NEW EXT. FIXED ALUM. STOREFRONT WINDOW MK. "D" - ALT. BID

NEW EXT. FIXED ALUM. STOREFRONT WINDOW MK. "E" - ALT. BID

OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
 MONROE, LOUISIANA















LAND 3
 ARCHITECT, INC.
 A PROFESSIONAL CORPORATION
 1900 STUBBS AVENUE
 MONROE, LA.
 71201-5786



DRAWN BY: GWM
 CHK'D BY: WAL
 JOB # 1963
 DATE: 08/2024
 COPYRIGHT PROTECTED

DOOR & WINDOW DETAILS

A7.2




SHEET SIZE: 24 X 36 SCALE: 3" = 1'-0"

INTERIOR DOOR - ALUMINUM STOREFRONT


INTERIOR WINDOW - ALUMINUM STOREFRONT

INTERIOR WINDOW - ALUMINUM STOREFRONT


MISC. ALUMINUM STOREFRONT DETAILS




C HEAD DETAIL
A7.4 SCALE: 3" = 1'-0"




F HEAD DETAIL
A7.4 SCALE: 3" = 1'-0"




I HEAD DETAIL
A7.4 SCALE: 3" = 1'-0"




L TYP. FRAME ANCHOR DETAILS
A7.4 (FOR DOOR FRAMES IN STUD WALLS) NOT TO SCALE




B JAMB DETAIL
A7.4 SCALE: 3" = 1'-0"




E JAMB DETAIL
A7.4 SCALE: 3" = 1'-0"




H JAMB DETAIL
A7.4 SCALE: 3" = 1'-0"




K MISC. SECTIONAL DOOR DETAILS
A7.4 SCALE: 3" = 1'-0"




A SILL DETAIL
A7.4 SCALE: 3" = 1'-0"



D SILL DETAIL
A7.4 SCALE: 3" = 1'-0"



G SILL DETAIL
A7.4 SCALE: 3" = 1'-0"



J JAMB DETAIL
A7.4 SCALE: 3" = 1'-0"

EXT. DOOR - ALUMINUM FULL VIEW SECTIONAL DOOR

INT. DOOR - ALUMINUM FULL VIEW SECTIONAL DOOR

INTERIOR INSULATED HOLLOW METAL DOOR IN H.M. FRME

MISC. DOOR & WINDOW DETAILS

**OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA**

**LAND 3
Architect**


**LAND 3
ARCHITECT, INC.**
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA.
71201-5786



DRAWN BY: GWM
CHK'D BY: WAL
JOB #: 1963
DATE: 08/2024
COPYRIGHT PROTECTED


**DOOR & WINDOW
DETAILS**

A7.4




C HEAD DETAIL
A7.5 SCALE: 3" = 1'-0"

***NOTE:**
5 7/8" FRAME WIDTH AT 3 5/8" METAL STUD PARTITIONS & 8 1/2" FRAME WIDTH AT 6" METAL STUD PARTITIONS




F HEAD DETAIL
A7.5 SCALE: 3" = 1'-0"


***NOTE:**
5 7/8" FRAME WIDTH AT 3 5/8" METAL STUD PARTITIONS & 8 1/2" FRAME WIDTH AT 6" METAL STUD PARTITIONS



I HEAD DETAIL
A7.5 SCALE: 3" = 1'-0"




L HEAD DETAIL
A7.5 SCALE: 3" = 1'-0"




B JAMB DETAIL
A7.5 SCALE: 3" = 1'-0"


***NOTE:**
DOOR & FRAME SHALL CARRY AN APPROPRIATE RATING LABEL. INSTALLATION AND CLEARANCES MUST COMPLY WITH N.F.P.A. 101/N.F.P.A. 80.



E JAMB DETAIL
A7.5 SCALE: 3" = 1'-0"




H JAMB DETAIL
A7.5 SCALE: 3" = 1'-0"




K JAMB DETAIL
A7.5 SCALE: 3" = 1'-0"


***NOTE:**
REFER TO SHEET D1.1 FOR EXTENT OF EXISTING CMU WALL THAT SHALL BE REMOVED FOR NEW SCH. DOOR OPENING. PATCH EXISTING ADJACENT CMU THAT IS TO REMAIN WHERE DAMAGED DUE TO REMOVAL




A SILL DETAIL
A7.5 SCALE: 3" = 1'-0"



D SILL DETAIL
A7.5 SCALE: 3" = 1'-0"



G SILL DETAIL
A7.5 SCALE: 3" = 1'-0"



J SILL DETAIL
A7.5 SCALE: 3" = 1'-0"

FIRE RATED DOOR & H.M. FRAME (rating varies)

INTERIOR SOLID CORE WOOD DOOR IN H.M. FRAME


INTERIOR PRE-HUNG DOOR UNIT

INTERIOR DOOR MK. 183

**OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA**



**LAND 3
ARCHITECT, INC.**
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA.
71201-5786




DRAWN BY: GWM
CHK'D BY: WAL
JOB #: 1963
DATE: 08/2024
COPYRIGHT PROTECTED


DOOR DETAILS

A7.5


SHEET SIZE: 24 X 36 SCALE: 3" = 1'-0"




C SHEET METAL SILL FLASHING
A7.6 DETAIL AT EXT. WINDOWS N.T.S.




F HEAD DETAIL
A7.6 SCALE: 3" = 1'-0"




I HEAD DETAIL
A7.6 SCALE: 3" = 1'-0"




L DOOR JAMB
A7.6 SCALE: 3" = 1'-0"




B ALUMINUM STOREFRONT
A7.6 DOOR JAMB SCALE: 3" = 1'-0"




E JAMB DETAIL
A7.6 SCALE: 3" = 1'-0"




H JAMB DETAIL
A7.6 SCALE: 3" = 1'-0"




K ALUMINUM STOREFRONT
A7.6 DOOR JAMB SCALE: 3" = 1'-0"




A WINDOW SILL REPAIR
A7.6 DETAIL AT AREA 118 SCALE: 3" = 1'-0"
(APPLIES TO EXISTING WEST WINDOWS - BASE BID)
MISC. WINDOW/DOOR DETAILS



D SILL DETAIL
A7.6 SCALE: 3" = 1'-0"



G SILL DETAIL
A7.6 SCALE: 3" = 1'-0"




J DOOR VISION LITE KIT
A7.6 SCALE: 3" = 1'-0"

SHEET SIZE: 24 X 36 SCALE: 3" = 1'-0"

**OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA**

**LAND 3
Architect**













**LAND 3
ARCHITECT, INC.**
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA.
71201-5786



DRAWN BY: GWM
CHKD BY: WAL
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED


DOOR & WINDOW
DETAILS

A7.6




SHEET SIZE: 24 X 36 SCALE: 3" = 1'-0"


EXT. FIXED WINDOW MK. "F"- ALUM. STOREFRONT EXT. FIXED WINDOW MK. "G"- ALUM. STOREFRONT INT. FRAMELESS ALUM. FIXED STOREFRONT WINDOW INTERIOR ALUMINUM STOREFRONT WINDOW




A CONCEALED MOUNT SHELF/COUNTER BRACKET DETAIL
SCALE: 1 1/2" = 1'-0"




B ENLARGED COUNTER EDGE DETAIL N.T.S.
D ENLARGED COUNTER EDGE DETAILS N.T.S.



E ADA COUNTER SECTION
SCALE: 1 1/2" = 1'-0"



B DELETED
SCALE: 1 1/2" = 1'-0"



F COUNTER SECTION
SCALE: 1 1/2" = 1'-0"

MILLWORK NOTES

ALL COUNTERTOP OUTSIDE CORNERS SHALL ROUNDED WITH A 2" RADIUS. SHOP DRAWINGS SUBMITTED WITHOUT ROUNDED RADIUS SHALL BE REJECTED.

ALL MILLWORK SHALL HAVE CONCEALED HINGES.


ALL INTERIOR METAL STUD WALLS BY GENERAL CONTRACTOR. WOOD STUD WALLS WHERE INDICATED ON MILLWORK SECTIONS THIS SHEET AT TABLES, BELOW COUNTER-TOPS, OR WHERE INDICATED IN DETAILS, ETC.... ARE TO BE PROVIDED BY MILLWORK CONTRACTOR. SEE SECTIONS 06 10 00 & 06 40 23 IN SPECIFICATIONS.

PROVIDE CONT. BEAD OF CAULK AT ALL COUNTER-TOP TO WALL TRANSITIONS.


AT MILLWORK PROVIDE .050 THICK HIGH PRESSURE PLASTIC LAMINATE OVER ALL EXPOSED SURFACES OF MILLWORK & PROVIDE MELLAMINE FOR ALL SEMI-EXPOSED SURFACES OF MILLWORK.

RECESS ALL FASTENERS AT MILLWORK THAT IS SECURED TO WALLS, FASTENERS SHALL NOT BE VISIBLE. FILL VOIDS AT FASTENERS WITH CAULK & PAINT/STAIN TO MATCH INTERIOR FINISH OF CABINET BACK.


PROVIDE PLYWOOD UNDER-LAYMENT WHERE INDICATED ON MILLWORK DETAILS OR ELEVATIONS. THIS REQUIREMENT IS INTENTIONALLY MORE STRINGENT THAN MILLWORK SPECS. INDICATE DUE TO HIGH ABUSE OR WET LOCATIONS.




H COUNTER-TOP TRANSITION DETAIL
NOT TO SCALE



I COUNTER SECTION
SCALE: 1 1/2" = 1'-0"



G COUNTER SECTION AT PRINTER STATION SCREEN WALL
SCALE: 1 1/2" = 1'-0"



J COUNTER SECTION AT CART SCREEN WALL
SCALE: 1 1/2" = 1'-0"

**OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA**

**LAND 3
Architect**

LAND 3 ARCHITECT, INC.
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA.
71201-5786




DRAWN BY: GWM
CHKD BY: WAL
JOB #: 1963
DATE: 08/2024
COPYRIGHT PROTECTED

MILLWORK

A8.1


SHEET SIZE: 24 X 36 SCALE: 1 1/2" = 1'-0"

****NOTE: REFER TO SHEET A8.1 FOR MILLWORK NOTES AND MOULDING NOTES**




A COUNTER DETAIL AT STUDY AREAS SCALE: 1 1/2" = 1'-0"


G.S. PROVIDE PLASTIC GROMMET SLEEVES NEATLY INSTALLED THROUGH COUNTER-TOPS SHOWN FOR CABLES, WIRING, ETC. (VERIFY TOTAL NUMBER REQUIRED & EXACT LOCATIONS WITH USER AGENCY PRIOR TO INSTALLATION) DETAILS BASED ON MODEL EDP3 - 2 1/2" FLIP TOP BY "MOCKETT". FINISH TO BE SELECTED BY ARCHITECT.




B SOLID CORE WOOD GATE DETAILS SCALE: 1 1/2" = 1'-0"



C COUNTER SECTION SCALE: 1 1/2" = 1'-0"




D RECESSED DISPLAY CASE SCALE: 1 1/2" = 1'-0"




E PLYWOOD TREE CANOPY DETAIL NOT TO SCALE

(9) TOTAL LIMBS/CANOPIES (THIS DETAIL DEPICTS 3 LIMBS) CANOPY HEIGHT VARIES FROM 10'-11', SEE A4.1




F JAMB SECTION (OPPOSITE END SIM.)



F ENLARGED FLOOR PLAN OF TREE HOUSE-AREA 156 SCALE: 1/2" = 1'-0"


SHEET SIZE: 24 X 36 SCALE: 1 1/2" = 1'-0"




NOTE: SECURELY MOUNT ALL SIGNAGE TO WALL WITH ADHESIVE AND SCREWS USING CONCEALED MOUNTING METHOD.
(USE ADHESIVE ONLY WHERE SIGNAGE IS SECURED AT FIRE WALLS FASTENERS NOT ALLOWED)
NOTE: WHERE SIGNAGE LOCATION SHOWN CONFLICTS WITH SCHEDULE OR WALL, PROVIDE ALTERNATE LOCATION AS DIRECTED BY FIRE MARSHAL.





THIS SIGN HAS ONE LINE OF TEXT AND A WINDOW OPTION FOR USER INSERT
(VERIFY WORDING FOR EACH ROOM & WORDING FOR INSERT WITH OWNER)
(12) REQUIRED PROVIDE AT AREAS 109,110,111,118,119,125,130,131, 139,159,178, & 217
6" HIGH SIGN X LENGTH AS REQUIRED WITH ADA BRaille - SECURE ON WALL ADJACENT TO DOOR FRAME. PROVIDE ON HALL/CORRIDOR SIDE OF DOORS. SEE MOUNTING DETAIL THIS SHEET (VERIFY EXACT WORDING WITH OWNER.)









THIS SIGN HAS ONE LINE OF TEXT, REFER TO ROOM NAMES ON ROOM FINISH SCHEDULES FOR 1ST & 2ND FLOORS TO GET NAME OF ROOM & TOTAL QUANTITY OF THIS SIGN TYPE TO BE PROVIDED.
PROVIDE 1 PER ROOM
3" HIGH SIGN X LENGTH AS REQUIRED WITH ADA BRaille - SECURE ON WALL ADJACENT TO DOOR FRAME. PROVIDE ON HALL/CORRIDOR SIDE OF DOORS. SEE MOUNTING DETAIL THIS SHEET (VERIFY EXACT WORDING WITH OWNER.)



THIS SIGN HAS TWO LINES OF TEXT, REFER TO ROOM NAMES ON ROOM FINISH SCHEDULES FOR 1ST & 2ND FLOORS TO GET NAME OF ROOM & TOTAL QUANTITY OF THIS SIGN TYPE TO BE PROVIDED.
PROVIDE 1 PER ROOM
6" HIGH SIGN X LENGTH AS REQUIRED WITH ADA BRaille - SECURE ON WALL ADJACENT TO DOOR FRAME. PROVIDE ON HALL/CORRIDOR SIDE OF DOORS. SEE MOUNTING DETAIL THIS SHEET (VERIFY EXACT WORDING WITH OWNER.)



PROVIDED BY SECTION 10 14 29. SEE SHEET A1.1 FOR LOCATION & VERIFY WITH ARCHITECT EXACT LOCATION PLAQUE SHALL BE MOUNTED PRIOR TO FINAL INSTALLATION.



A ADA SIGNAGE SYSTEMS
A8.3 NOT TO SCALE


ALL LETTERS AND ADA SIGNAGE BY SPECIALTIES SECTION 10 14 23

SEE SPECIFICATIONS FOR STYLE, FINISH, & LIST OF APPROVED MANUFACTURERS FOR SIGNAGE TYPES SHOWN ON THIS SHEET.

NOTE: SIGN SUPPLIER SHALL MEET WITH OWNER'S REPRESENTATIVE AND CONFIRM ALL INTERIOR SIGNAGE WORDING/SPELLING/NUMBERING PRIOR TO SUBMITTING SIGNAGE SHOP DRAWINGS TO ARCHITECT FOR APPROVAL

D EXTERIOR SIGNAGE SYSTEM
A8.3 CAST BRONZE PLAQUE NOT TO SCALE









PROVIDED BY SECTION 10 14 29. SEE SHEET A1.1 FOR LOCATION & VERIFY WITH ARCHITECT EXACT LOCATION PLAQUE SHALL BE MOUNTED PRIOR TO FINAL INSTALLATION.



STAIRWELL LEVEL & EXIT DISCHARGE INFORMATION SHALL BE LOCATED & INSTALLED ON WALL INSIDE EACH EXIT STAIRWELL. SIGNS MUST COMPLY WITH ALL PROVISIONS OF NFPA STAIR IDENTIFICATION 7.2.2.5.4.1

(2) REQUIRED. PROVIDE REQUIRED ADA BRaille - SECURE ADJACENT TO DOOR FRAME ON WALL. PROVIDE ADJ. TO DOORS ON WALL ADJ. TO STAIRS AT 1ST & 2ND FLOORS; SEE MOUNTING DETAIL ON THIS SHEET.


ADA COMPLIANCE CUSTOM SIGNAGE PROVIDED BY SECTION 10 14 23 IN SPECIFICATIONS



(2) REQUIRED. PROVIDE REQUIRED ADA BRaille - SECURE ADJACENT TO DOOR FRAME ON WALL. PROVIDE ADJ. TO DOORS ON WALL ADJ. TO STAIRS AT 1ST & 2ND FLOORS; SEE MOUNTING DETAIL ON THIS SHEET.

ADA COMPLIANCE CUSTOM SIGNAGE PROVIDED BY SECTION 10 14 23 IN SPECIFICATIONS

B INTERIOR CUSTOM ada SIGNAGE
A8.3 NOT TO SCALE



C DOOR TOP SIGNAGE
A8.3 NOT TO SCALE

NOTE: ALL DOOR TOP SIGNS CONSTRUCTED FROM 1" X 8" COMPOSITE CLADDING BOARDS BY DIV. 7 SECURED TO GYP. BD. INTO STUDS, MITER & RETURN TO WALL. ALL BOARD ENDS FOR A NEAT FINISHED LOOK. ATTACH PLASTIC LETTERS BY SECTION 10 14 29 IN THE SIZES SHOWN IN EACH ELEV.. LETTER COLOR, FONT TYPE, AND WOOD STAIN TO BE SELECTED BY ARCHITECT. SEE DETAILS FOR SIZE DIMENSIONS. VERIFY ALL SIGN LETTER WORDING WITH OWNER BEFORE SIGN CONSTRUCTION.

RIGID VINYL SIGNS - PROJECTION WALL MOUNT by Inprocorp.com SEE DETAIL H/A8.3 FOR SIGN

DOOR NO.	WORDING	DOOR NO.	WORDING	DOOR NO.	WORDING
# 104	REFERENCE OFFICE	# 153	CREATIVE WORKSHOP	# 165	BOOKMOBILE OFFICE
# 121, #188	RESTROOMS	# 109, #110 # 125, #159	MEETING ROOM	# 177	TECH SERVICES OFFICE
# 130	BRANCH MANAGER	# 160	I.L.L. OFFICE	# 178	TECH SERVICES DIRECTOR
# 138	ADMINISTRATIVE OFFICES	# 161	Friends of the LIBRARY	NEAR # 173 VERIFY W/ARCH.	VENDING
# 149	YOUNG ADULTS	NEAR # 162	COMMUNICATION DIRECTOR	# 176	COMPUTER CLASS
# 156	CHILDREN'S AREA	NEAR # 163	GRAPHIC ART OFFICE	# 155	PODCAST STUDIO


ADMINISTRATIVE OFFICES

REFERENCE DESK CIRCULATION DESK

SEE INTERIOR ELEVATIONS FOR WORDING & LOCATIONS. VERIFY EXACT WORDING TO BE USED WITH ARCHITECT.

- 6" HIGH UPPER CASE LETTERS
- FONT: GOUDY EXTRA BOLD
- FINISH: TO BE SELECTED FROM CHART OF 31 STANDARD COLORS


E INTERIOR PLASTIC LETTERS NOT TO SCALE



LETTERS TO BE LOCATED ON EAST/WEST FACE OF INTERIOR COLUMNS AT AREAS 132,133,136, AND 137. SEE FLOOR PLAN AND SHEET A4.1. VERIFY EXACT WORDING TO BE USED W/ ARCHITECT.

- 8" HIGH UPPER CASE LETTERS
- FONT: GOUDY EXTRA BOLD
- FINISH: TO BE SELECTED FROM 31 STANDARD COLORS


F INT. PLASTIC LETTERS AT INT. COLUMNS NOT TO SCALE



FONT: "Young" IS FONT - TURNER SCRIPT "Adults" IS FONT - AVANT GARDE MEDIUM
FINISH: TO BE SELECTED FROM CHART OF 31 STANDARD COLORS.

H INTERIOR PLASTIC LETTERS NOT TO SCALE

THESE LETTERS ARE TO BE LOCATED ON WALL ABOVE INTERIOR ENTRANCE DOORS TO CHILDREN'S AREA AND YOUNG ADULT'S AREA.



(22) REQUIRED 2'-0" X 1'-6" SIGN - PROJECTION TYPE SIGNS SECURED TO WALL 8" A.F.F. VERIFY LOCATIONS W/ARCHITECT PRIOR TO INSTALLATION.
CUSTOM SIGNAGE BY INPRO, SYDNEY COLLECTION. SEE SECTION 10 14 23 IN SPECIFICATIONS

J PROJECTION WALL MOUNTED SIGNS NOT TO SCALE

NOTE: SIGN SUPPLIER SHALL MEET WITH OWNER'S REPRESENTATIVE AND CONFIRM ALL SIGNAGE WORDING/SPELLING PRIOR TO SUBMITTING SIGNAGE SHOP DRAWINGS TO ARCHITECT FOR APPROVAL

OUACHITA PARISH PUBLIC LIBRARY

PLASTIC LETTERS SECURED WITH RUST PROOF FASTENERS SECURED TO COMPOSITE CLADDING USING METHOD AS RECOMMENDED BY MANUF.

SEE EXTERIOR ELEVATIONS FOR WORDING & LOCATION AND VERIFY EXACT WORDING TO BE USED WITH ARCHITECT.

- (27) 12" HIGH UPPER CASE LETTERS
- FONT: GOUDY EXTRA BOLD
- FINISH: TO BE SELECTED FROM CHART OF 31 STANDARD COLORS

Main Branch

PLASTIC LETTERS SECURED WITH RUST PROOF FASTENERS SECURED TO METAL WALL PANELS USING METHOD AS RECOMMENDED BY MANUF.


- (1) 24" HIGH UPPER CASE LETTER
- (3) 24" LOWER CASE LETTERS
- (1) 12" HIGH UPPER CASE LETTER
- (5) 12" HIGH LOWER CASE LETTERS

FONT: GOUDY EXTRA BOLD
FINISH: TO BE SELECTED FROM CHART OF 31 STANDARD COLORS



LETTERS PROVIDED BY SECTION 10 14 29

SEE EXTERIOR ELEVATIONS FOR WORDING & LOCATION AND VERIFY EXACT WORDING TO BE USED WITH ARCHITECT.

I EXTERIOR PLASTIC LETTERS NOT TO SCALE



FONT: "Young" IS FONT - TURNER SCRIPT "Adults" IS FONT - AVANT GARDE MEDIUM
FINISH: TO BE SELECTED FROM CHART OF 31 STANDARD COLORS.




K DIRECTIONAL SIGN NOT TO SCALE

NOTE: ALL SIGNS ARE MADE OF 3/4" MDF AND COVER WITH PLASTIC LAMINATE. SIGNS SHALL BE SUSPENDED W/ STAINLESS STEEL CABLE 12" BELOW CEILING GRID. LAMINATE COLOR SELECTED BY ARCHITECT. SEE FLOOR PLAN FOR MOUNTING LOCATIONS. ALL LETTER FONT SHALL BE HELVETICA LIGHT, UPPER CASE, FINISH WHITE. SEE EACH SIGN ABOVE FOR LETTER SIZE.

**OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA**

LAND 3 Architect

LAND 3 ARCHITECT, INC. A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA.
71201-5786



DRAWN BY: RM
CHK'D BY: WAL
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED

ADA SIGNAGE,
LETTERING &
MISC. SIGNAGE

A8.3

TOILET ACCESSORY LEGEND
BY SECTION 10 28 00 IN SPEC.

PT	PAPER TOWEL DISPENSER
ED	ELECTRIC HAND DRYER (REFER TO ELECTRICAL SHEETS FOR POWER REQUIREMENTS)
TP	TOILET TISSUE HOLDER
SD	SOAP DISPENSER
M	18" X 36" FRAMED MIRROR CENTERED OVER LAVATORY INDICATED
GB	STAINLESS STEEL GRAB BARS (SIZES SHOWN ON ENLARGED PLANS THIS SHEET)
TH	TOWEL HOOK (VERIFY LOCATION)
MH	MOP HOLDER (LOCATED IN JANITOR CLOSET)
RBC	RECESS MOUNTED ADA COMPLIANT HORIZONTAL BABY CHANGING STATION WITH BAG HOOK.

*SEE ENLARGED RESTROOM PLANS THIS SHEET AND DETAIL D/A9.2 FOR MOUNTING DIMENSIONS & LOCATIONS OF ITEMS LISTED ABOVE


RESTROOM NOTES:

1. PROVIDE METAL TRIM AT ALL WALL TILE TO DOOR FRAME AND WALL TILE TO WALL TILE CORNER TRANSITIONS. SEE DETAIL A/A9.2
2. SEE DETAILS ON SHEET A9.2 FOR CERAMIC FLOOR/WALL DETAILS AND TYP. RESTROOM DETAILS.
3. ALL PLUMBING FIXTURES SHOWN IN ENLARGED PLANS THIS SHEET ARE TO BE PROVIDED BY DIVISION 22, SEE PLUMBING SHEETS FOR FIXTURE SCHEDULE AND PLUMBING PLANS.
4. H/C DENOTED ON ENLARGED FLOOR PLANS SHALL MEAN HANDICAPPED ACCESSIBLE.
5. FOR TOILET ACCESSORIES DENOTED ON ENLARGED PLANS THIS SHEET SEE SECTION 10 28 00 IN SPECIFICATIONS.
6. FOR TOILET PARTITIONS AND URINAL SCREENS, RE: SPECS. SECTION 10 21 13.
7. REFER TO SHEET A1.2 FOR LEGENDS, EQUIPMENT SCHEDULES, NOTES, ETC.....

CONTRACTOR SHALL NOTIFY ARCHITECT OF ANY DISCREPANCIES AND CONFLICTS PRIOR TO BID IN ACCORDANCE WITH THE SPECS.


SOILD BLOCKING BY CONTRACTOR TO BE PROVIDED IN ALL WALLS THAT ARE LOCATED BEHIND TOILET ACCESSORIES, GRAB BARS AND VANITIES FOR SECURE ATTACHMENT OF THESE ITEMS.TYPICAL

*AT ALL ADA ACCESSIBLE TOILET PARTITIONS THE FRONT & AT LEAST ONE SIDE SHALL PROVIDE A TOE CLEARANCE OF 9" MIN. A.F.F. & 6" DEEP MIN. BEYOND FACE OF PARTITION, TYP. FOR ALL ADA ACCESSIBLE TOILET STALLS THIS PROJECT.



A RESTROOM ELEV. AREA 121
(LAV. - 34" MAX. HEIGHT TO TOP RIM OF LAVATORY. ADJUST HEIGHT OF END PANELS & COUNTER-TOP AS REQUIRED TO MAINTAIN A MAX. 34" HEIGHT.)


B RESTROOM ELEV. AREA 122
(LAV. - 34" MAX. HEIGHT TO TOP RIM OF LAVATORY. ADJUST HEIGHT OF END PANELS & COUNTER-TOP AS REQUIRED TO MAINTAIN A MAX. 34" HEIGHT.)



C RESTROOM ELEV. AREA 123 - east wall
(LAV. - 34" MAX. HEIGHT TO TOP RIM OF LAVATORY. ADJUST HEIGHT OF END PANELS & COUNTER-TOP AS REQUIRED TO MAINTAIN A MAX. 34" HEIGHT.)


D RESTROOM ELEV. AREA 123 - west wall
Rough Wall Opening at baby changing station
• 4" minimum depth
• 37 1/16" width x 21 5/8" height
• 26 9/16" from top of stud at bottom of opening to finished floor

E RESTROOM ELEV. AREA 150, AREA 157 SIM.
(LAV. - 34" MAX. HEIGHT TO TOP RIM OF LAVATORY. ADJUST HEIGHT OF END PANELS & COUNTER-TOP AS REQUIRED TO MAINTAIN A MAX. 34" HEIGHT.)




L RESTROOM ELEV. AREA 209


M RESTROOM ELEV. AREA 210




N INT. ELEVATION AREA 124 - east wall




F ENLARGED PLAN AT AREAS 209 & 210 SCALE: 1/4" = 1'-0"
(SHOWING NOTES & DIMENSIONS)




H ENLARGED PLAN AT AREA 157 SCALE: 1/4" = 1'-0"
(SHOWING NOTES AND DIMENSIONS)



G ENLARGED PLAN AT AREAS 209 & 210 SCALE: 1/4" = 1'-0"
(SHOWING TOILET ACCESSORIES & ADA CLEARANCES)




I ENLARGED PLAN AT AREA 157 SCALE: 1/4" = 1'-0"
(SHOWING TOILET ACCESSORIES & ADA CLEARANCES)




J ENLARGED PLAN AT AREAS 121,122,123, & 150 SCALE: 1/4" = 1'-0"
(SHOWING NOTES AND DIMENSIONS)

K ENLARGED PLAN AT AREAS 121,122,123, & 150 SCALE: 1/4" = 1'-0"
(SHOWING TOILET ACCESSORIES & ADA CLEARANCES)


SHEET SIZE: 24 X 36 SCALE: 1/4" = 1'-0"




A METAL TRIM @ WALL TILE (TYP. FOR ALL TILE WALLS) NOT TO SCALE




B C.T. BASE AT FRP PANEL TRANSITION NOT TO SCALE




G GRAB BAR SECTION AT GYP. BD. WALL NOT TO SCALE




E THRESHOLD TRANSITION SYSTEM tcna-TR6111 NOT TO SCALE




F TYP. THRESHOLD TRANSITION NOT TO SCALE




H CERAMIC WALL TILE SYSTEM tcna W243 WAINSCOT (THIN SET) NOT TO SCALE



I CERAMIC FLOOR TILE (THINSET) SYSTEM tcna-F122 NOT TO SCALE



C TYPICAL FRP WALLBOARD TRIM DETAILS DETAILS 6\"/>




D MOUNTING DIMENSIONS FOR TOILET FIXTURES, TOILET COMPARTMENTS, TOILET ACCESSORIES, & FIRE EXTINGUISHERS - REFER TO SECTION 10 28 00 SCALE: N.T.S.

SHEET SIZE: 24 X 36 SCALE: 1/4\"/>

OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA

LAND 3 Architect

LAND 3 ARCHITECT, INC.
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA.
71201-5786




DRAWN BY: GWM
CHK'D BY: WAL
JOB #: 1963
DATE: 08/2024
COPYRIGHT PROTECTED

typ. RESTROOM
DETAILS &
MOUNTING
DIMENSIONS
A9.2

FLOORING LEGEND

PRODUCTS EQUAL TO

- CONC INDICATES NON-SLIP BROOM FINISH ON NEW CONCRETE SLAB.
- ETR INDICATES EXISTING FLOORING TO REMAIN.
- TC AREA TO RECEIVE ARTIFICIAL TURF CARPETING BY SECTION 09 68 10
- AAC AREA TO RECEIVE 24"x24" CARPET TILES INSTALLED USING THE QUARTER TURN METHOD. MANUFACTURER - SHAW CONTRACT GROUP, TRADEMARK - ALL ACCESS COLLECTION, COLOR SELECTED BY ARCHITECT
- CP 1 AREA TO RECEIVE 24"x24" CARPET TILES INSTALLED USING THE QUARTER TURN METHOD. MANUFACTURER - SHAW CONTRACT GROUP, TRADEMARK - KINDRED COLLECTION, COLOR SELECTED BY ARCHITECT
- CP 2 AREA TO RECEIVE 24"x24" CARPET TILES INSTALLED USING THE MONOLITHIC METHOD. SHAW CONTRACT GROUP, TRADEMARK - MINDFUL PLAY COLLECTION. 3 COLOR FADED BLEND DIAGONAL FROM LEFT TO RIGHT SIDE OF AREAS, COLOR SELECTED BY ARCHITECT
- CP 3 AREA TO RECEIVE 24"x24" CARPET TILES. MANUFACTURER - SHAW CONTRACT GROUP, TRADEMARK - KINDRED COLLECTION. COLOR SELECTED BY ARCHITECT. SEE ENLARGED PLAN ON THIS SHEET FOR INSTALL METHOD.
STYLE:
 - a = BELONG, INSTALL MONOLITHIC
 - b = DREAM, INSTALL MONOLITHIC
 - c = MEMORY, INSTALL QUARTER TURN
- LVT-1 7"x48" WOOD LUXURY VINYL TILE PLANKS, INSTALLED USING BRICK METHOD. MANUFACTURER - SHAW HARD SURFACE TRADEMARK, STYLE "GRAIN+PIGMENT". COLOR SELECTED BY ARCHITECT
- LVT-2 18"x18" HIGH PERFORMANCE LUXURY VINYL TILE, MANUFACTURER - SHAW COMMERCIAL HARD SURFACE, CRETE & JEOPORI Trademark, STYLE "CRETE". COLOR SELECTED BY ARCHITECT
- LVT-3 18"x18" HIGH PERFORMANCE LUXURY VINYL TILE, MANUFACTURER - ARMSTRONG NATURAL CREATION. COLORS SELECTED BY ARCHITECT
- PT 12"x24" COLORBODY PORCELAIN TILE, INSTALLED USING THE BRICK METHOD. MANUFACTURER - DaTile FLOORING, STONE ARRACHE COLLECTION, STYLE "DIGNITARY", COLOR SELECTED BY ARCHITECT. (UTILIZE NARROW 1/8" JOINTS WITH RECTIFIED TILE)




1 VINYL TILE TO CARPET
FL.11 TRANSITION NOT TO SCALE

FLOORING NOTES

1. REFER TO ROOM FINISH SCHEDULES ON SHEET A1.1 FOR ADDITIONAL FLOOR FINISHES THAT MAY NOT BE INDICATED ON THIS PLAN.
2. REFER TO ALL OTHER SHEETS FOR LOCATION OF ANY EQUIPMENT AND/OR ACCESSORIES WHICH MAY AFFECT THE TILE PLAN.
3. VERIFY TILE PATTERNS AND COLORS SHOWN WITH THE ARCHITECT PRIOR TO LAYING OF ANY FLOOR TILE.
4. CONTRACTOR SHALL NOTIFY ARCHITECT OF DISCREPANCIES AND CONFLICTS PRIOR TO BID IN ACCORDANCE WITH THE SPECIFICATIONS.
5. SEE SHEET A9.1 FOR TILE PATTERNS IN RESTROOMS.
6. ALL COLORS TO BE SELECTED BY ARCHITECT.

SEE ENLARGED PLAN ON THIS SHEET FOR FLOORING TYPES, LOCATIONS AND INSTALL PATTERN FOR THIS DASH-LINE AREA.


18"x18" TILES IN 3 DIFFERENT COLOR STYLES




ENLARGED PLAN

AREA 149 SCALE: 1/8" = 1'-0"

AREA TO RECEIVE 18"x18" LUXURY VINYL TILES MANUFACTURER- EQUAL TO "ARMSTRONG" NATURAL CREATIONS MYSTIX LUXURY FLOORING "KENSIE" COLLECTION, TRADEMARK - KINDRED COLLECTION. COLORS SELECTED BY ARCHITECT. SEE ENLARGED PLAN - LVT FOR THREE DIFFERENT COLOR STYLES (A, B & C).



1st FLOOR FLOORING PLAN
 SCALE: 1/16" = 1'-0"




2nd FLOOR FLOORING PLAN
 SCALE: 1/16" = 1'-0"

EXISTING METAL STAIRS TO BE Sanded, primed and painted with two coats of SEMI-GLOSS ENAMEL PAINT. COLOR SELECTED BY ARCHITECT.

SHEET SIZE: 24 X 36 SCALE: 1/16" = 1'-0"

OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
 MONROE, LOUISIANA




LAND 3 ARCHITECT, INC.
 A PROFESSIONAL CORPORATION
 1900 STUBBS AVENUE
 MONROE, LA.
 71201-5786



DRAWN BY: RM
 CHK'D BY: WAL
 JOB # 1963
 DATE: 08/2024
 COPYRIGHT PROTECTED

1ST & 2ND FLOOR FLOORING PLANS

FL1.1




ALL FURNITURE ON 1ST & 2ND FLOOR PLANS IS SHOWN FOR SCALE OR REFERENCE PURPOSES ONLY

THIS LINE TYPE AT FURNITURE INDICATED ON PLANS IS EXISTING FURNITURE ON SITE THAT IS TO BE RE-INSTALLED IN AREAS SHOWN. (VERIFY ALL LOCATIONS SHOWN AND LAY-OUT WITH OWNER PRIOR TO MOVING AND INSTALLING THIS FURNITURE.)

HATCHED BOOKCASES ARE TALLER HEIGHT


THIS LINE TYPE AT FURNITURE INDICATED ON PLANS IS EXISTING FURNITURE ON SITE THAT IS TO BE RE-INSTALLED IN AREAS SHOWN. (VERIFY ALL LOCATIONS SHOWN AND LAY-OUT WITH OWNER PRIOR TO MOVING AND INSTALLING THIS FURNITURE.)

**2nd FLOOR
FURNITURE PLAN**
SCALE: 3/32" = 1'-0"




ALL FURNITURE SHOWN (U.O.N.) SHALL BE PROVIDED BY OWNER UNDER SEPARATE CONTRACT


**1st FLOOR
FURNITURE PLAN**
SCALE: 3/32" = 1'-0"




SHEET SIZE: 24 X 36 SCALE: 1/16" = 1'-0"



CEILING LAYOUT PLAN
1st FLOOR SCALE: 1/16" = 1'-0"



REFLECTED CEILING PLAN LEGEND	
	GYPSUM BOARD FURR DOWN. SHAPE VARIES, SEE PLAN FOR LOCATIONS.
	2 HR RATED CEILING ASSEMBLY PER DETAIL D/AS.6 ABOVE SCHEDULED SUSPENDED ACOUSTIC CEILING THIS AREA.
	2'x2' ACOUSTIC CEILING GRID AND TILE, BY SPECIFICATION 09 51 13
	ALL 2'x4' CEILING TILE TO BE REMOVED AND REPLACED WITH NEW CEILING TILE INSTALLED IN EXISTING GRID SYSTEM. (PATCH/REPAIR GRID WHERE DAMAGED) PROVIDE NEW INSUL. BY DIV. 7 ABOVE ALL ACOUSTIC CEILINGS
	2'x2' BLACK SUSPENDED GRID SYSTEM AND ACOUSTIC CEILING TILE BY SECTION 09 51 13. (AREAS 155 & 176 TO HAVE GRID & TILE ON A 45° ANGLE.) PROVIDE NEW INSUL. BY DIV. 7 ABOVE ALL ACOUSTIC CEILINGS




CEILING LAYOUT PLAN
2nd FLOOR SCALE: 1/16" = 1'-0"



****ALTERNATE BIDS**
SEE SECTION 01 23 00 IN SPECS.
FOR COMPLETE LIST
AND DESCRIPTION OF ALTERNATE BIDS

OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA



LAND 3
ARCHITECT, INC.
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA.
71201-5786





DRAWN BY: RM
CHK'D BY: WAL
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED

1st & 2nd FLOOR
ACOUSTIC CEILING TILE
LAYOUT PLANS


RC1.1

PLAN LEGEND	
	ROOF MEMBRANE REPAIR: 1 YEAR MANUFACTURER 2 YEAR CONTRACTOR 1 PLY SELF ADHERED CAP SHEET OVER 1 PLY BASE FELT MECHANICALLY SECURED THRU EXISTING ZONOLITE INTO EXISTING METAL ROOF DECK WITH SCREWS. SEE DETAIL B/R1.1.
	NEW MEMBRANE ROOF SYSTEM AT PENTHOUSE: 10 YEAR WARRANTY 1-PLY SELF ADHERED CAP SHEET OVER 1-PLY BASE FELT MECHANICALLY SECURED OVER 1-1/2" RIGID INSULATION INTO NEW METAL ROOF DECK THAT IS SLOPED 1/4" PER FOOT. SEE DETAILS ON SHEET A4.5 & A5.3 FOR WALL CONSTRUCTION AND DETAILS ON SHEET R2.1 FOR ROOF CONSTRUCTION
	NEW SHEET METAL COPING, SEE DETAIL "G" ON R2.1
	EXISTING CONDENSING UNIT AND REFRIGERANT LINE PENETRATION THRU ROOF TO REMAIN
	EXISTING PVC VENT PIPE PENETRATION THRU ROOF TO REMAIN U.O.N.
	EXISTING DOME VENT WITH ROOF CURB PENETRATION THRU ROOF TO REMAIN U.O.N.
	EXISTING MINI SPLIT CONDENSER AND REFRIGERANT LINE PENETRATION THRU ROOF TO REMAIN
	EXISTING ROOF TOP AIR CONDITIONING UNIT ON CURB TO REMAIN. EXTEND EXISTING PVC CONDENSATE DRAINS TO NEAREST ROOF DRAIN WITH 1" PVC PIPE ON SUPPORT BLOCKS
	EXISTING ROOF DRAIN TO REMAIN U.O.N.
	EXISTING ROOF CURB WITH SHEET METAL OR BUILT UP ROOFING CAP TO REMAIN
	EXISTING GOOSENECK TO REMAIN
	EXISTING ROOF HATCH TO REMAIN
	NEW SCUPPER AND 4" SQ. DOWNSPOUT TO DISCHARGE ON LOWER ROOF
	NEW ROOF TOP AIR CONDITIONING UNIT ON NEW CURB. PROVIDE 4X4X1/4" STEEL ANGLE SUPPORTS UNDER ROOF DECK SECURED TO EXISTING BAR JOISTS AT PERIMETER OF CURB. SEE DETAIL A/R2.1 FOR ROOFING WORK.


- GENERAL ROOFING NOTES**
- COMPLY WITH SECTION 07 52 00
 - VERIFY ALL DIMENSIONS, CONDITIONS, SIZES AND NUMBERS OF EXISTING ITEMS PRIOR TO BIDDING. VERIFY ROOF AREAS PRIOR TO BIDS.
 - ALL WORK SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURERS WRITTEN INSTRUCTIONS. COMPLY W/ OSHA & ALL APPLICABLE CODES.
 - VERIFY EXACT LOCATIONS & NUMBER OF ALL EXISTING ROOF DRAINS, VENTS, MECHANICAL EQUIPMENT, COLUMN COVERS, ELECTRICAL CONDUITS, GAS LINES, ETC.... PRIOR TO BIDDING.
 - THE DESIGN INTENT IS FOR EXISTING WOOD BLOCKING TO BE RE-USED IF IT IS SOUND & SALVAGEABLE, OTHERWISE NEW BLOCKING TO MATCH EXISTING SHALL BE PROVIDED & PAID BY UNIT COST. MATERIALS SHALL BE CONSIDERED SALVAGEABLE IF IT IS NOT STRUCTURALLY DAMAGED OR MISSING. MINOR COSMETIC DAMAGE IS ACCEPTABLE.




ENLARGED ROOF PLAN AT ELEVATOR PENTHOUSE
SCALE: 1/4" = 1'-0"



ROOF MEMBRANE DETAIL
SCALE: 1 1/2" = 1'-0"




ROOF REPAIR DETAIL
SCALE: 1 1/2" = 1'-0"




ROOF DECK DETAIL
NOT TO SCALE
SEE UNIT COST INSTRUCTIONS UC-3

ROOF PLAN
SCALE: 1/16" = 1'-0"


SHEET SIZE: 24 X 36 SCALE: 1/16" = 1'-0"




**B SCUPPER & DOWN-SPOUT
R2.1 ELEVATOR PENTHOUSE**
SCALE: 1 1/2" = 1'-0"




**E EMBEDDED EDGE METAL FLASHING
R2.1 AT EXISTING ROOF**
NOT TO SCALE




**C EXISTING ROOF DRAIN
R2.1 DETAIL AT ROOF REPAIR**
NOT TO SCALE




**I EMBEDDED EDGE METAL FLASHING
R2.1**
NOT TO SCALE




**H EMBEDDED EDGE METAL FLASHING
R2.1 AT PENTHOUSE ROOF**
NOT TO SCALE




**G TYP. SHEET METAL
R2.1 FASCIA**
NOT TO SCALE



**A NEW RAISED CURB DETAIL
R2.1**
NOT TO SCALE
(VERIFY ALL LOCATIONS AND NUMBER)




**D TYP. PLUMBING VENT AND CONDUIT
R2.1 BOOT WRAP DETAIL**
SCALE: 1 1/2" = 1'-0"
VERIFY LOCATIONS AND NUMBER ON MECHANICAL AND ELECTRICAL SHEETS




**F PIPE ROLLER SUPPORT
R2.1**
SCALE: 1 1/2" = 1'-0" NOTE: PROVIDE UNDER ALL PIPE AND CONDUIT ON ROOF

SHEET SIZE: 24 X 36 SCALE: 1-1/2" = 1'-0"




STRUCTURAL NOTES: COMPLY WITH SECTION 13 34 19
 NOTE: DUE TO THE VARIATIONS OF DESIGN BETWEEN METAL BUILDING MANUFACTURERS, STRUCTURAL SHAPES, MEMBER SIZES ARE OMITTED FROM THIS SHEET. WHEN A PARTICULAR MANUFACTURER IS SELECTED BY THE CONTRACTOR, HE SHALL SUBMIT TO THE ARCHITECT A STRUCTURAL LAYOUT WITH CALCULATED END REACTIONS UNDER VARIOUS DEAD, LIVE, AND WIND LOADS FOR THE PARTICULAR FRAMES ALONG WITH SUFFICIENT DETAILS FOR COORDINATION WITH STRUCTURAL AND ARCHITECTURAL PLANS. STEEL MEMBERS SHALL BE OVER-DESIGNED TO ACCOMMODATE ADDITIONAL LOADS AT SOFFITS, LIGHT FIXTURES, ETC..... SEE ARCHITECTURAL PLANS FOR DETAILS; RIGID FRAME MEMBERS AND FOUNDATIONS SHALL BE DESIGNED TO RESIST LATERAL WIND LOADS AS REQUIRED BY, THE 2021 INTERNATIONAL BUILDING CODE. NO STRUCTURAL MEMBERS OR BRACING SHALL BE EXPOSED IN THE INTERIOR




STEEL FRAMING PLAN
SHOWING ROOF FRAMING
 SCALE: 1/4" = 1'-0"
 REF. NORTH




STEEL FRAMING PLAN
SHOWING SOFFIT FRAMING
 SCALE: 1/4" = 1'-0"
 REF. NORTH



A RIGID FRAME ELEVATION
AT LINES A & B
 SCALE: 1/4" = 1'-0"



B RIGID FRAME ELEVATION
AT LINE 4
 SCALE: 1/4" = 1'-0"




C RIGID FRAME ELEVATION
AT LINE 1
 SCALE: 1/4" = 1'-0"

SHEET SIZE: 24 X 36 SCALE: 1/4" = 1'-0"

OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
 MONROE, LOUISIANA

LAND 3
 Architect


LAND 3
 ARCHITECT, INC.
 A PROFESSIONAL CORPORATION
 1900 STUBBS AVENUE
 MONROE, LA
 71201-5788



DRAWN BY: LOH
 CHK'D BY: WAL
 JOB #: 1963
 DATE: 08/2024
 COPYRIGHT PROTECTED

ARCHITECTURAL STEEL
 FRAMING PLAN
 @ ARCHED ENTRANCE


ASF1.1



1 ELEVATOR SHAFT FRAMING ELEVATION
S1.1
SCALE: 1/4" = 1'-0"

2 ELEVATOR SHAFT FRAMING ELEVATION
S1.1
SCALE: 1/4" = 1'-0"

3 BEAM TO COLUMN CONNECTION PLAN
S1.1
SCALE: 1 1/2" = 1'-0"



B FOOTING AT ENTRANCE CANOPY
S1.1
SCALE: 1" = 1'-0"

C FOOTING AT ENTRANCE CANOPY
S1.1
SCALE: 1" = 1'-0"

A FOOTING AT ELEVATOR PIT
S1.1
SCALE: 1" = 1'-0"

EXCAVATION/FILL NOTES


CONTRACTOR SHALL COMPLY WITH SOIL REPORT SECTION 02 30 00.

SELECT FILL MATERIAL SHALL HAVE PROPERTIES AS LISTED IN THE SOIL REPORT. IF NONE IS LISTED USE THE FOLLOWING: A LIQUID LIMIT LESS THAN 35 AND A PLASTICITY INDEX OF BETWEEN 8 AND 18. THE SELECT FILL SHALL BE PLACED IN 6" THICK LIFT AND COMPACTED TO 95% OF THE STANDARD PROCTOR MAXIMUM DRY DENSITY (ASTM D998) AT 2% OF THE OPTIMUM MOISTURE CONTENT.


ONCE THE WORK AREA HAS BEEN SCARIFIED A MINIMUM OF 6", TESTING LAB FIELD REPRESENTATIVE SHALL BE CONTACTED TO ASCERTAIN IF THE SUBGRADE SOILS AND MOISTURE CONTENT ARE SUITABLE FOR PLACEMENT OF THE SELECT FILL MATERIAL. CONTRACTOR SHALL COMPACTION TEST THE EXISTING SUB-GRADE IN THE PRESENCE OF THE TESTING LAB FIELD REPRESENTATIVE. ANY AREAS DETERMINED TO BE UNSUITABLE FOR PLACEMENT OF SELECT FILL MATERIAL SHALL BE REMOVED AND FILLED WITH COMPACTED SELECT FILL MATERIAL OR STABILIZED WITH A CHEMICAL AS RECOMMENDED BY THE SUB SURFACE EXPLORATION REPORT AND TESTING LAB FIELD TECHNICIAN.

FOUNDATION NOTES:


- THE DESIGN, MATERIALS, AND WORKMANSHIP OF REINFORCED CONCRETE SHALL BE IN ACCORDANCE WITH THE CURRENT EDITIONS OF THE FOLLOWING STANDARDS:
 - ACT 318 - BUILDING CODE REQUIREMENTS FOR REINFORCED CONCRETE
 - SP66 - ACI DETAILING MANUAL
 - ACI 301 - SPECIFICATIONS FOR STRUCTURAL CONCRETE FOR BUILDINGS
 - CRSI - RECOMMENDED PRACTICE FOR PLACING REINFORCING STEEL
 - REINFORCING STEEL: DEFORMED BARS ASTM A615 - GRADE 60
 - WELDED WIRE MESH: NEW MATERIAL; FABRICATION TO COMPLY WITH ASTM A185. FLAT SHEETS ONLY.
 - CONCRETE 28 DAY STRENGTH: 4000 PSI. MINIMUM. CONCRETE NOT MEETING STRENGTH REQUIREMENTS SHALL REQUIRE REMOVAL AND REPLACEMENT.
 - UNLESS NOTED OTHERWISE, CONCRETE COVER OVER REINFORCING STEEL SHALL BE AS FOLLOWS:
 - 3" WHEN CONCRETE IS PLACED DIRECTLY AGAINST EARTH
 - 2" FOR #6 BARS AND LARGER IF, AFTER FORM REMOVAL, THE CONCRETE IS DIRECTLY EXPOSED TO WEATHER OR EARTH
 - 1 1/2" FOR #5 BARS AND SMALLER IF, AFTER FORM REMOVAL, THE CONCRETE IS DIRECTLY EXPOSED TO WEATHER OR EARTH
- EARTH:
 - 1" IN SLABS AND WALLS
 - 1 1/2" FOR BEAMS AND COLUMNS NOT DIRECTLY EXPOSED TO WEATHER OR EARTH
 - UNLESS NOTED OTHERWISE ON THE DRAWINGS, THE MINIMUM LAP FOR BAR SPLICES SHALL BE:
 - BAR SIZE TOP BARS: BOTTOM & VERTICAL BARS
 - #3 12"
 - #4 2'-4"
 - #5 2'-11"
 - #6 3'-4"
 - 1" HORIZONTAL BARS WITH 12" OR MORE OF CONCRETE CAST BELOW THEM.
 - ALL TOP BARS SHALL BE SPLICED AT MIDSPAN; BOTTOM BARS AT PIER LOCATIONS.
 - ALL REINFORCING STEEL AND W.W. MESH: ADEQUATELY SUPPORTED ON CHAIRS OR CONC BRICKS, SUPPORTS TO COMPLY WITH ACI - 315. CLAY BRICKS NOT ALLOWED.
- DOWEL INTERSECTING WALLS, BEAMS, OTHER CONCRETE ELEMENTS WITH DOWELS OF SAME SIZE AND SPACING AS HORIZONTAL STEEL IN CONNECTING MEMBER.
- PLACE 2-0 X 2-0 CORNER BARS AT ALL CORNERS IN WALLS AND BEAMS SIZE AND SPACING: SAME AS HORIZONTAL STEEL.
- CONSTRUCTION JOINTS IN SLAB AND BEAMS: AT COLUMN CENTERLINE OR POINT OF MINIMUM STRESS.
- EXPOSED JOINTS, EDGES OF CONCRETE WALLS: FORMED WITH 3/4" CHAMFER.
- EXPOSED CONCRETE SURFACES: FORMED WITH PLYWOOD OR METAL FORMS.
- LAP W.W. MESH MINIMUM OF 6" AND TIE.
- SEE ARCHITECTURAL, MECHANICAL, ELECTRICAL DRAWINGS FOR INSERTS IN OR PASSING THRU CONCRETE ELEMENTS.
- PRIOR TO PLACING CONCRETE, REFER TO ARCHITECTURAL, PLUMBING, MECHANICAL AND ELECTRICAL DRAWINGS FOR UNDERGROUND AND EMBEDDED ITEMS NOT SHOWN ON THE STRUCTURAL DRAWINGS.
- FURNISH 30" X 30" X 1" SHARP BARS OF SAME SIZE AND SPACING WITH MAIN HORIZONTAL REINFORCING STEEL IN CONTINUOUS FOOTINGS. PLACE AT ALL EXTERIOR FACES OF EXTERIOR CORNERS.
- CORNER BARS 30"x30" AT ALL INTERSECTING GRADE BEAMS SAME SIZE AND SPACING WITH MAIN HORIZONTAL STEEL.
- WELDED WIRE FABRIC IN ALL SLABS SHALL BE SUITABLY SUPPORTED SO THAT THE MESH WILL BE 2-1/2" FROM TOP SURFACE OF CONCRETE.
- CONTRACTOR SHALL VERIFY ALL DIMENSIONS AT THE BUILDING SITE AND SHALL BRING TO THE ATTENTION OF THE ARCHITECT ANY DISCREPANCIES BEFORE PROCEEDING WITH WORK.
- ANCHOR BOLTS SHALL MEET THE REQUIREMENTS OF ASTM A307 OR A36 UNLESS NOTED OTHERWISE ON THE DRAWINGS. MINIMUM ANCHOR BOLT EMBEDMENT INTO CONCRETE SHALL BE (12) BOLT DIAMETERS THE PORTION OF THE BOLT PROJECTING ABOVE THE CONCRETE SHALL BE THREADED.
- ALL GROUT FOR DRILLED-IN ANCHOR BOLTS OR REINFORCING BARS SHALL BE FIVE STAR EPOXY GROUT AS MANUFACTURED BY FIVE STAR PRODUCTS, INC. OR APPROVED EQUAL W/ IDENTICAL PROPERTIES SPECIFICATION.
- THE CONTRACTOR SHALL CARRY EXTERIOR BACK FILL AND THE BACK FILL WITHIN THE BUILDING TO REQUIRED FINISH ELEVATION AT THE SAME TIME IN ORDER THAT NO UNEQUAL PRESSURE BE EXERTED AGAINST FOUNDATION WALLS.
- COMPACTING SHALL BE DONE ON EACH SIDE OF WALL AT THE SAME TIME.
- CONTRACTOR SHALL RUN PIPE SLEEVES THRU GRADE WALL AND NOT BELOW FOOTINGS.
- THE CONTRACTOR SHALL PROVIDE THE TESTING LAB WITH THE QUALITY CONTROL SECTION 01 40 00 OF THE PROJECT MANUAL AND SEE THAT IT IS FOLLOWED BY THE TESTING LAB REPRESENTATIVE.




6 COLUMN BASE PLATE DETAIL (ELEVATOR)
S1.1
N.T.S.
RECESS ALL BASEPLATES AND FILL WITH NON-SHRINK AFTER INSTALLATION OF STEEL




5 TYP. BEAM TO COLUMN CONNECTION
S1.1
DETAIL
SCALE: 1 1/2" = 1'-0"




ROOF FRAMING PLAN AT PENTHOUSE
SCALE: 1/4" = 1'-0"




7 COLUMN BASE PLATE DETAIL (STAIRS)
S1.1
N.T.S.



9 FRONT CORNICE BEAM AT ROOF
S1.1
SCALE: 1" = 1'-0"




8 EXISTING BAR JOIST MODIFICATION
S1.1
DETAIL (2 JOISTS EACH END OF SHAFT)
SCALE: 1" = 1'-0"



FOUNDATION PLAN AT ELEVATOR PIT
SCALE: 1/4" = 1'-0"

STRUCTURAL STEEL GENERAL NOTES:

- DESIGN, FABRICATION, AND ERECTION OF STRUCTURAL STEEL SHALL BE IN ACCORDANCE WITH THE AISC MANUAL OF STEEL CONSTRUCTION, 14TH EDITION, ASD, UNLESS NOTED OTHERWISE.
- MATERIAL SPECIFICATIONS FOR ALL STRUCTURAL STEEL COMPONENTS SHALL BE AS FOLLOWS:
 - W-SHAPES & TEES CUT FROM W-SHAPES - ASTM A992
 - SQUARE & RECTANGULAR HOLLOW STRUCTURAL SECTIONS - ASTM A500, GR. B, Fy = 46 KSI
 - ROUND HOLLOW STRUCTURAL SECTIONS - ASTM A500, GR. B, Fy = 42 KSI
 - STANDARD STEEL PIPE SECTIONS - ASTM A53, Fy = 35 KSI
 - PLATES, BARS, AND ROUNDS - ASTM A36, Fy = 36 KSI
 - CHANNELS, ANGLES, S-SHAPES - ASTM A36
- ALL STEEL SURFACES SHALL BE PREPARED TO SSPC-SP6 AND RECEIVE ONE COAT OF RUST INHIBITIVE PRIMER.
- WELDING SHALL CONFORM TO AWS D1.1, CURRENT EDITION, USING E70XX, LOW HYDROGEN SMAW ELECTRODES, OR OTHER ELECTRODE-FLUX COMBINATIONS ALLOWED BY AWS D1.1.
- FIELD CONNECTIONS SHALL BE BOLTED UNLESS NOTED OTHERWISE. SHOP CONNECTIONS MAY BE BOLTED OR WELDED EXCEPT WHERE OTHERWISE SHOWN ON THE DRAWINGS.
- HIGH-STRENGTH, BOLTED STRUCTURAL CONNECTIONS SHALL BE MADE USING ASTM A325, TYPE 1, 3/4" DIAMETER (MINIMUM) BOLTS, UNLESS NOTED OTHERWISE. SECONDARY FRAMING MEMBER CONNECTIONS (E.G. PURLINS, GIRTS, JOISTS) MAY BE MADE WITH 1/2" DIAMETER (MINIMUM) ASTM A307 OR A325 BOLTS.
- ALL HIGH-STRENGTH, BOLTED STRUCTURAL CONNECTIONS SHALL BE BEARING TYPE WITH THE THREADS INCLUDED IN THE SHEAR PLANE (A325N), UNLESS NOTED OTHERWISE.
- ALL HIGH-STRENGTH, STRUCTURAL BOLTS SHALL BE TIGHTENED BY THE TURN-OF-THE-NUT METHOD TO THE MINIMUM TENSION SPECIFIED IN SPECIFICATION FOR STRUCTURAL JOINTS USING ASTM A325 OR A490 BOLTS, UNLESS NOTED OTHERWISE. HARDENED WASHERS SHALL BE USED UNDER THE ELEMENT TURNED IN TIGHTENING THE BOLT.
- ALL BEAM CONNECTIONS WHICH ARE NOT DETAILED OR OTHERWISE NOTED ON THE DRAWINGS SHALL BE BOLTED IN ACCORDANCE WITH AISC TABLE 10-1, USING THE MAXIMUM NUMBER OF ROWS OF BOLTS POSSIBLE FOR THE BEAM'S DEPTH AND A MINIMUM CLIP ANGLE THICKNESS OF 1/4". EQUIVALENT WELDED CONNECTIONS IN ACCORDANCE WITH AISC TABLE 10-2, USING A MINIMUM WELD 'A' OF 3/16", MAY BE USED.
- ALL HORIZONTAL AND VERTICAL BRACING MEMBERS SHALL BE CONNECTED TO THEIR GUSSET PLATES USING A MINIMUM OF TWO (2) ROWS OF ASTM A325N BOLTS. GUSSET PLATES SHALL BE A 3/8" THICK, MINIMUM.
- THE ERECTOR SHALL PROVIDE ALL TEMPORARY SHORING AND/OR BRACING NECESSARY TO ENSURE STABILITY OF THE STRUCTURE UNTIL IT IS COMPLETED.





FOUNDATION PLAN AT ENTRANCE CANOPY
SCALE: 1/4" = 1'-0"

Don Arrington

NOTES FOR EXTERIOR STAIR


- THE DESIGN INTENT IS FOR ALL STAIRS TO BE EQUIPPED WITH HANDRAILS AND GUARDRAILS COMPLYING W/ ADDAG & NFPA 101.
- STAIRWAYS SHALL HAVE HANDRAILS AT BOTH SIDES.
- HANDRAILS SHALL BE CONTINUOUS ALONG INSIDE OF STAIRS. THE INSIDE HANDRAIL ON SWITCHBACK OR DOGLEG STAIRS SHALL BE CONTINUOUS.
- AT LANDINGS WHERE THE HANDRAILS ARE NOT CONTINUOUS, THEY SHALL EXTEND AT LEAST 12" BEYOND THE TOP RISER AND ONE TREAD WIDTH BEYOND THE BOTTOM RISER. AT THE TOP, THE EXTENSION SHALL BE PARALLEL WITH THE GROUND AT THE BOTTOM THE HANDRAIL SHALL CONTINUE TO SLOPE FOR A MIN. DISTANCE OF THE WIDTH OF ONE TREAD FROM THE BOTTOM RISER.
- THE CLEAR SPACE BETWEEN HANDRAILS AND WALL OR ALL OTHER ADJACENT MATERIALS SUCH AS COLUMNS, ETC. SHALL BE 2 1/4".
- GRIPPING SURFACES SHALL BE UNINTERRUPTED BY NEWEL POSTS, OTHER CONSTRUCTION ELEMENTS OR OBSTRUCTIONS.
- TOP OF HANDRAIL GRIPPING SURFACE SHALL BE MOUNTED BETWEEN 34" & 38" ABOVE STAIR NOSINGS. ALL HANDRAILS SHALL BE SAME HEIGHT.
- GUARDRAILS SHALL BE 42" MIN. IN HEIGHT AND INFILL SHALL BE SPACED WHERE A 4" SPHERE CANNOT PASS THRU THEM.
- VERIFY ALL CONDITIONS AND FINAL FINISHED FLOOR ELEVATIONS PRIOR TO DETERMINING FINAL RISER HEIGHT FOR STAIR. ALL RISER SHALL BE EQUAL.
- INCLUDE IN BID ALL WORK REQUIRED FOR A COMPLETE FUNCTIONING STAIR RAIL SYSTEM INCLUDING ALL COMPONENTS NECESSARY. SUBMIT SHOP DRAWINGS FOR APPROVAL.
- VERIFY ALL EXISTING CONDITIONS AND DIMENSIONS PRIOR TO FABRICATION OF HANDRAILS.
- ALL WELDS AND CONNECTIONS SHALL BE GROUND SMOOTH.
- ALL METAL MATERIALS THAT ARE NOT STAINLESS STEEL, ALUMINUM, OR PRE-FINISHED SHALL BE PAINTED BY SECTION 09 90 00
- GUARDRAILS SHALL BE 42" MIN. IN HEIGHT AND INFILL SHALL BE SPACED WHERE A 4" SPHERE CANNOT PASS THRU THEM.
- THE TOLERANCE BETWEEN THE LARGEST & SMALLEST HORIZ. NOSING PROJECTION, BETWEEN THE LARGEST & SMALLEST RISER HEIGHT, OR BETWEEN THE LARGEST & SMALLEST TREAD DEPTH IN ANY FLIGHT OF STAIRS SHALL NOT EXCEED 3/8". IN ADDITION THE VARIATION BETWEEN ADJ. HORIZ. NOSINGS, BETWEEN ADJ. RISER HEIGHTS, OR BETWEEN ADJ. TREAD DEPTHS ON STAIRS SHALL NOT EXCEED 3/16".



F TUBE COL. TO CHANNEL
SCALE: 1 1/2" = 1'-0"


G C 10 TO C 10 CHANNEL
SCALE: 1 1/2" = 1'-0"

H C 8 TO C 10 CHANNEL
SCALE: 1 1/2" = 1'-0"




D TYPICAL PAN STAIR TREAD & RISER
SCALE: 1 1/2" = 1'-0"


E STAIR TO LANDING TRANSITION
SCALE: 1 1/2" = 1'-0"




C TUBE COLUMN PLAN
SCALE: 1 1/2" = 1'-0"




B POST/RAIL/STRINGER CONNECTION DETAILS
NOT TO SCALE




J ATTACHMENT DETAIL STRINGER TO CONC. SLAB
SCALE: 1" = 1'-0"




A CONC. LANDING DETAIL
SCALE: 1 1/2" = 1'-0"




N BEAM CONNECTION FOLDING WALL AREA 118
SEE DET. K/A5.4 & SHEET A6.1
SCALE: 1/2" = 1'-0"




K ROOF TOP UNIT SUPPORT DETAIL (RTU-3)
SCALE: 1/8" = 1'-0"




I HANDRAIL/GUARDRAIL SECTION
NOT TO SCALE



L ROOF TOP UNIT SUPPORT DETAIL (RTU-1 & RTU-2)
SCALE: 1/8" = 1'-0"



M ROOF TOP UNIT SUPPORT DETAIL (RTU-4)
SCALE: 1/8" = 1'-0"



E EXTERIOR STAIR ELEVATION
SCALE: 1/2" = 1'-0"



EXTERIOR STAIR PLAN
SCALE: 1/4" = 1'-0"

SHEET SIZE: 24 X 36 SCALE: 1/4" = 1'-0"

CONTRACTOR'S OPTION TO FULLY SHOP WELD ALL CONNECTIONS AND INSTALL STAIR ASSEMBLY ON SITE IN 1 PIECE

****NOTE: ALL METAL COMPONENTS OF STAIR SHALL BE SANDED, PRIMED, & PAINTED BY SECTION 09 90 00 IN SPECIFICATIONS**




SEE SHEET P3.1 FOR PLUMBING DEMOLITION
 GENERAL NOTES AND CONTRACTORS NOTES.

PLUMBING DEMOLITION NOTES:

- EXISTING TO REMAIN.
- x-x- EXISTING TO BE REMOVED.
- PD1 REMOVE AND DISCARD EXISTING PLUMBING FIXTURE. RETAIN EXISTING ROUGH-IN AS REQUIRED FOR MODIFICATION AND RECONNECTION. REMOVE AND DISCARD DOMESTIC WATER PIPING BRANCH PIPING AND CAP AT MAIN AS REQUIRED. CAP WASTE BRANCH BEHIND WALL/BELOW SLAB AND PATCH TO MATCH ADJACENT AS REQUIRED. FIELD VERIFY EXISTING CONDITIONS.
- PD2 REMOVE AND DISCARD EXISTING PLUMBING FIXTURE. RETAIN EXISTING ROUGH-IN FOR MODIFICATION AND RECONNECTION.
- PD3 EXISTING PLUMBING FIXTURE TO REMAIN. PROTECT DURING DEMOLITION AND NEW CONSTRUCTION.
- PD4 EXISTING FIRE SPRINKLER RISER TO REMAIN. PROTECT DURING DEMOLITION AND NEW CONSTRUCTION.
- PD5 PURGE, REMOVE AND DISCARD EXTERIOR GAS SCONCE LIGHTING AND ASSOCIATED ACCESSORIES. REMOVE EXISTING BRANCH PIPING BACK TO MAIN AND CAP.
- PD6 EXISTING WATER HEATER AND ASSOCIATED ACCESSORIES TO REMAIN. PROTECT DURING DEMOLITION AND NEW CONSTRUCTION.
- PD7 EXISTING GAS METER SET TO REMAIN. PROTECT DURING DEMOLITION AND NEW CONSTRUCTION.




FIRST FLOOR PLAN DEMOLITION – PLUMBING
 SCALE: 1/16" = 1'-0"



SECOND FLOOR PLAN DEMOLITION – PLUMBING
 SCALE: 1/16" = 1'-0"

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.




PARTIAL FIRST FLOOR PLAN – WASTE AND VENT
 SCALE: 1/8" = 1'-0"

- PLUMBING NOTES:**
- (P1) SWEEP ELBOW OR COMBINATION WITH 4" WASTE STACK, 4" COMBINATION (OR DOUBLE COMBINATION AS APPLICABLE) AND 4" WASTE ARM BRANCH UNDERSLAB TO CLOSET BEND AND CLOSET FLANGE. PROVIDE 4"x3" REDUCING BUSHING AND EXTEND 3" VENT UP IN CHASE TO FULL-SIZE HEADER.
 - (P2) REDUCING COMBINATION WITH 3" WASTE STACK, 3" SANITARY CROSS, 3" DEEP-SEAL P-TRAP UNDERSLAB FOR FLOOR DRAIN CONNECTION. PROVIDE 3"x2" REDUCING BUSHING AND 2" VENT STACK IN WALL. EXTEND 2" VENT UP CHASE TO FULL-SIZE HEADER.
 - (P3) REDUCING COMBINATION WITH 2" WASTE/VENT STACK IN CHASE FOR URINAL. EXTEND 2" VENT UP IN CHASE TO FULL-SIZE HEADER.
 - (P4) REDUCING COMBINATION WITH 2" WASTE/VENT STACK IN WALL FOR LAVATORY/SINK ROUGH-IN CONNECTION. EXTEND 2" VENT UP IN CHASE TO FULL-SIZE HEADER.
 - (P5) 1/2" TYPE "L" COPPER UNDERSLAB FROM "WATER-SAVER" TRAP PRIMING ASSEMBLY. EXTEND AND CONNECT TO FLOOR DRAIN (FD/TP). RE: DETAIL "C", SHEET P4.1.
 - (P6) VENT PIPING ABOVE CEILING, HIGH THROUGH STRUCTURE ABOVE; 2" UNLESS NOTED OTHERWISE.
 - (P7) SEE SHEET P1.2 FOR CONTINUATION.
 - (P8) EXTEND NEW 4" SANITARY SEWER AND CONNECT TO EXISTING SANITARY SEWER; APPROXIMATELY 30 FEET TO THE SOUTHWEST. FIELD VERIFY EXACT SIZE, DEPTH, LOCATION, INVERT ELEVATION, ETC.

SEE SHEET P3.1 FOR PLUMBING GENERAL NOTES AND CONTRACTORS NOTES.

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.



PARTIAL FIRST FLOOR PLAN - WASTE AND VENT

SCALE: 1/8" = 1'-0"


SEE SHEET P3.1 FOR PLUMBING GENERAL NOTES AND CONTRACTORS NOTES.

PLUMBING NOTES:

- (P1) SWEEP ELBOW OR COMBINATION WITH 4" WASTE STACK, 4" COMBINATION (OR DOUBLE COMBINATION AS APPLICABLE) AND 4" WASTE ARM BRANCH UNDERSLAB TO CLOSET BEND AND CLOSET FLANGE. PROVIDE 4"x3" REDUCING BUSHING AND EXTEND 3" VENT UP IN CHASE TO FULL-SIZE HEADER.
- (P2) REDUCING COMBINATION WITH 3" WASTE STACK, 3" SANITARY CROSS (OR 3" SANITARY TEE), 3" DEEP-SEAL P-TRAP UNDERSLAB FOR FLOOR DRAIN CONNECTION. PROVIDE 3"x2" REDUCING BUSHING AND 2" VENT STACK IN WALL. EXTEND 2" VENT UP CHASE TO FULL-SIZE HEADER.
- (P3) REDUCING COMBINATION WITH 2" WASTE/VENT STACK IN WALL FOR LAVATORY/SINK/JANITOR SINK ROUGH-IN CONNECTION. EXTEND 2" VENT UP IN WALL TO FULL-SIZE HEADER.
- (P4) 1/2" TYPE "L" COPPER UNDERSLAB FROM "WATER-SAVER" TRAP PRIMING ASSEMBLY. EXTEND AND CONNECT TO FLOOR DRAIN (FD/TP). RE: DETAIL 'C', SHEET P4.1.
- (P5) VENT PIPING ABOVE CEILING, HIGH THROUGH STRUCTURE ABOVE; 2" UNLESS NOTED OTHERWISE.
- (P6) MODIFY EXISTING PLUMBING ROUGH-IN AS REQUIRED FOR FLOOR DRAIN, JANITOR SINK AND SINK.
- (P7) 3" DEEP-SEAL P-TRAP AND 3" STUB-UP FOR FLOOR DRAIN/MOP SINK CONNECTION.
- (P8) 4" SANITARY WASTE FROM ABOVE DOWN OFFSET ABOVE CEILING TO PLUMBING.
- (P9) EXTEND NEW SANITARY SEWER AND CONNECT TO EXISTING SANITARY SEWER. FIELD VERIFY EXACT SIZE, DEPTH, LOCATION, INVERT ELEVATION, ETC.

- (P10) EXTEND AND CONNECT TO NEAREST EXISTING SITE STORM DRAINAGE SYSTEM AS REQUIRED.
- (P11) SEE SHEET P1.1 FOR CONTINUATION.
- (P12) EXTEND NEW 2" VENT ABOVE CEILING AND CONNECT TO EXISTING VENT OF SUFFICIENT SIZE.
- (P13) MODIFY EXISTING SINK ROUGH-IN RETAINED FROM DEMOLITION AS REQUIRED FOR NEW SINK CONNECTION.
- (P14) 2" WASTE/VENT STACK IN WALL FOR DRINKING FOUNTAIN ROUGH-IN CONNECTION. OFFSET AND EXTEND SANITARY WASTE BRANCH THROUGH WALL FRAMING AND CONNECT TO EXISTING SANITARY WASTE STACK IN WALL. PROVIDE INSULATED 2" DEEP-SEAL P-TRAP WITH PROSET TRAP GUARD AND 2" OPEN-SITE DRAIN (OSD) WITH HUB AND ELONGATED FUNNEL IN VENT STACK ABOVE ACCESSIBLE CEILING FIELD VERIFY EXISTING CONDITIONS.
- (P15) INSPECT EXISTING PLUMBING FIXTURE FOR SERVICEABILITY; NOTIFY ARCHITECT IMMEDIATELY OF ANY UNPREDICTABILITY. CLEAN AND SERVICE EXISTING PLUMBING FIXTURE AT COMPLETION OF PROJECT.
- (P16) PROVIDE INSULATED 2" DEEP-SEAL P-TRAP WITH PROSET TRAP GUARD AND 2" OPEN-SITE DRAIN (OSD) WITH HUB FOR AIR HANDLER CONDENSATE TERMINATION. EXTEND 2" WASTE ARM AND CONNECT TO EXISTING WATER CLOSET VENT STACK; DETAIL 'D', SHEET P4.2. FIELD VERIFY EXISTING CONDITIONS.

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.




SEE SHEET P3.1 FOR PLUMBING GENERAL NOTES AND CONTRACTORS NOTES.

PARTIAL FIRST FLOOR PLAN - DOMESTIC WATER AND GAS
 SCALE: 1/8" = 1'-0"

PLUMBING NOTES:

- (P1) 1/2" HOT AND COLD WATER DOWN IN WALL. BRANCH, EXTEND AND CONNECT 1/2" HOT AND COLD WATER TO EACH SINK FAUCET THROUGH KEYED ANGLE-STOP SUPPLIES. PROVIDE POINT-OF-USE TEMPERING VALVE (TV); REFERENCE DETAIL "H", SHEET P4.1.
- (P2) 1" HOT AND COLD WATER DOWN ALONG WALL TO FULL SIZE HEADER AT SEALED-COMBUSTION GAS-FIRED TANKLESS WATER HEATER (TWH-1) WITH FULL-PORT BALL SHUT-OFF VALVES AND UNIONS. BRANCH, EXTEND AND CONNECT 1" HOT WATER DISTRIBUTION PIPING AS INDICATED. ROUGH-IN, INSTALL AND CONNECT IN STRICT ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS AND PIPING DIAGRAMS. FURNISH AND INSTALL "PRESSURE ONLY" RELIEF VALVE ON HOT WATER OUTLET. RE: DETAIL "G", SHEET P4.1.
- (P3) 1/2" COLD WATER DOWN IN WALL. BRANCH, EXTEND AND CONNECT TO DRINKING FOUNTAIN/WATER COOLER THROUGH KEYED ANGLE-STOP SUPPLY.
- (P4) 1 1/4" COLD WATER DOWN IN WALL TO FULL-SIZE HEADER. BRANCH, EXTEND THROUGH WALL FRAMING AND CONNECT 1/2" COLD WATER TO LAVATORY FAUCET THROUGH KEYED ANGLE-STOP SUPPLY, 3/4" COLD WATER TO URINAL FLUSH VALVE WITH INTEGRAL SERVICE STOP AND 1" COLD WATER TO WATER CLOSET FLUSH VALVE WITH INTEGRAL SERVICE STOP. PROVIDE WATER HAMMER AS REQUIRED.
- (P5) 1 1/2" COLD WATER DOWN IN WALL TO FULL-SIZE HEADER. BRANCH, EXTEND AND CONNECT THROUGH WALL FRAMING AND CONNECT 1/2" COLD WATER TO LAVATORY FAUCET THROUGH KEYED ANGLE-STOP SUPPLY, AND 1" COLD WATER TO EACH WATER CLOSET FLUSH VALVE WITH INTEGRAL SERVICE STOP. PROVIDE WATER HAMMER AS REQUIRED.
- (P6) 1/2" COLD WATER DOWN IN WALL; BRANCH, OFFSET THROUGH WALL FRAMING WITH RECESSED WALL BOX, 1/2"x 1/4" REDUCER, 1/4" FULL-PORT BALL VALVE AND TYPE "L" COPPER TUBING FOR REFRIGERATOR ICE MAKER. COORDINATE EXACT LOCATION AND ROUGH-IN REQUIREMENTS WITH VENDOR AND ARCHITECT PRIOR TO INSTALLATION. RECESSED WALL BOX SHALL BE EQUAL TO GUY GRAY 88164 304 STAINLESS STEEL WITH LEAD FREE QUARTER-TURN VALVE AND 1/2" MIP/SWEAT CONNECTION.
- (P7) EXTEND NEW 2" DOMESTIC WATER OVERHEAD AND CONNECT TO EXISTING WATER MAIN. FIELD VERIFY EXISTING CONDITIONS.
- (P8) 1 1/2" COLD WATER DOWN IN WALL TO FULL-SIZE HEADER. BRANCH, EXTEND THROUGH WALL FRAMING AND CONNECT 1/2" COLD WATER TO LAVATORY FAUCET THROUGH KEYED ANGLE-STOP SUPPLY, AND 1" COLD WATER TO WATER CLOSET FLUSH VALVE WITH INTEGRAL SERVICE STOP. PROVIDE WATER HAMMER AS REQUIRED.
- (P9) PROVIDE POINT-OF-USE MIXING VALVE UNDER SINK; RE: DETAIL "H", SHEET P4.1.
- (P10) 3/4" HOT WATER LOOP DOWN IN WALL TO WITH-IN 2'-0" OF LAVATORY FAUCET. BRANCH, EXTEND AND CONNECT 1/2" HOT WATER TO EACH LAVATORY FAUCET THROUGH KEYED ANGLE-STOP VALVE. EXTEND 3/4" HOT WATER LOOP UP IN WALL TO ABOVE CEILING.
- (P11) GAS PIPING FROM ROOF, DOWN IN CHASE. BRANCH, OFFSET, DROP AND CONNECT TO WATER HEATER PER MANUFACTURER'S INSTALLATION INSTRUCTIONS AND PIPING DIAGRAMS. PROVIDE GAS COCK, UNION, REDUCER, 12" LONG DRIP LEG AND CORRUGATED FLEXIBLE STAINLESS STEEL TUBING CONNECTOR WITH SWIVEL ENDS; BRANCH PIPE SIZE AS NOTED. PREP, PRIME AND PAINT TO MATCH WALL. COORDINATE EXACT PIPE DROP LOCATION WITH MANUFACTURER PRIOR TO MATERIAL ORDER, ROUGH-IN, AND CONNECTION.
- (P12) SEE SHEET P1.4 FOR CONTINUATION.
- (P13) 1/2" HOT AND COLD WATER DOWN IN WALL. BRANCH, EXTEND AND CONNECT TO SINK FAUCET THROUGH KEYED ANGLE-STOP SUPPLIES. PROVIDE POINT-OF-USE TEMPERING VALVE (TV); REFERENCE DETAIL "H", SHEET P4.1.
- (P14) EXTEND ABS CONCENTRIC FLUE/VENT AND PIPING FROM TANKLESS WATER HEATER TO ABOVE CEILING; OFFSET AND EXTEND UP THROUGH WALL TO MANUFACTURERS APPROVED CONCENTRIC VENT HOOD.
- (P15) MODIFY EXISTING WALL FAUCET IN THIS AREA AS REQUIRED TO FACILITATE NEW CONSTRUCTION.

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.




PARTIAL FIRST FLOOR PLAN – DOMESTIC WATER AND GAS
 SCALE: 1/8" = 1'-0"

SEE SHEET P-3.1 FOR PLUMBING GENERAL NOTES AND CONTRACTORS NOTES.


PLUMBING NOTES:

- P1 1/2" COLD WATER DOWN IN WALL. BRANCH, OFFSET THROUGH WALL FRAMING. EXTEND AND CONNECT 1/2" TO ELECTRIC TANKLESS WATER HEATER (ETWH) (UNDERCOUNTER) THROUGH FULL-PORT BALL VALVE; BRANCH, EXTEND AND CONNECT 1/2" COLD WATER TO SINK FAUCET THROUGH KEYED ANGLE STOP SUPPLY.
- P2 BRANCH AND EXTEND 1/2" HOT WATER FROM UNDERCOUNTER ELECTRIC TANKLESS WATER HEATER (ETWH) AND CONNECT TO SINK FAUCET.
- P3 1/2" COLD WATER DOWN IN WALL. BRANCH, EXTEND AND CONNECT TO DRINKING FOUNTAIN/WATER COOLER THROUGH KEYED ANGLE-STOP SUPPLY.
- P4 1 1/2" COLD WATER DOWN IN WALL TO FULL-SIZE HEADER. BRANCH, EXTEND THROUGH WALL FRAMING AND CONNECT 1/2" COLD WATER TO LAVATORY FAUCET THROUGH KEYED ANGLE-STOP SUPPLY, AND 1" COLD WATER TO WATER CLOSET FLUSH VALVE WITH INTEGRAL SERVICE STOP. PROVIDE WATER HAMMER AS REQUIRED.
- P5 3/4" COLD WATER DOWN IN INTERIOR FRAME WALL. BRANCH, OFFSET THROUGH WALL FRAMING AND CONNECT TO HOSE BIBB (HB).
- P6 1/2" COLD WATER DOWN IN WALL; BRANCH, OFFSET THROUGH WALL FRAMING WITH RECESSED WALL BOX, 1/2"x 1/4" REDUCER, 1/4" FULL-PORT BALL VALVE AND TYPE "L" COPPER TUBING FOR REFRIGERATOR ICE MAKER. COORDINATE EXACT LOCATION AND ROUGH-IN REQUIREMENTS WITH VENDOR AND ARCHITECT PRIOR TO INSTALLATION. RECESSED WALL BOX SHALL BE EQUAL TO GUY GRAY 88164 304 STAINLESS STEEL WITH LEAD FREE QUARTER-TURN VALVE AND 1/2" MIP/SWEAT CONNECTION.
- P7 1/2" HOT AND COLD WATER DOWN IN WALL. BRANCH, EXTEND AND CONNECT 1/2" HOT AND COLD WATER TO EACH LAVATORY/SINK FAUCET THROUGH KEYED ANGLE-STOP SUPPLIES.
- P8 PROVIDE POINT-OF-USE TEMPERING VALVE (TV); REFERENCE DETAIL "H", SHEET P4.1.
- P9 EXTEND NEW COLD WATER PIPING ABOVE CEILING AND CONNECT TO NEAREST EXISTING COLD WATER PIPING OF SUFFICIENT SIZE; NEW PIPING SIZES NOTED.
- P10 SEE SHEET P1.3 FOR CONTINUATION.
- P11 MODIFY EXISTING WATER HEATER ROUGH-IN AS REQUIRED AND CONNECT TO NEW PLATFORM MOUNTED WATER HEATER (SHOWN OFFSET FOR CLARITY); REFERENCE DETAIL "B", SHEET P4.2.
- P12 MODIFY EXISTING SINK ROUGH-IN RETAINED FROM DEMOLITION AS REQUIRED AND CONNECT TO NEW SINK. PROVIDE NEW KEY-ANGLE STOP VALVES. PROVIDE POINT-OF-USE TEMPERING VALVE (TV); REFERENCE DETAIL "H", SHEET P4.1.
- P13 PROVIDE NEW APPROPRIATELY SIZE GAS HEADER AT EXISTING GAS METER SET. FIELD VERIFY EXISTING CONDITIONS.
- P14 MODIFY EXISTING HOT AND COLD WATER ROUGH-INS RETAINED FROM DEMOLITION. BRANCH, EXTEND AND CONNECT 1/2" HOT AND COLD WATER TO MOP SINK FAUCET WITH INTEGRAL SERVICE STOPS ANN 1/2" HOT AND COLD WATER TO SINK FAUCET THROUGH KEYED ANGLE-STOP VALVES.


THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.



PARTIAL SECOND FLOOR PLAN – WASTE AND VENT
SCALE: 1/8" = 1'-0"



PARTIAL SECOND FLOOR PLAN – WASTE AND VENT
SCALE: 1/8" = 1'-0"




ENLARGED SECOND FLOOR PLAN – WASTE AND VENT
SCALE: 1/4" = 1'-0"

SEE SHEET P3.1 FOR PLUMBING GENERAL NOTES AND CONTRACTORS NOTES.

PLUMBING NOTES:

- (P1) SWEEP ELBOW OR COMBINATION WITH 4" WASTE STACK, 4" COMBINATION (OR DOUBLE COMBINATION AS APPLICABLE) AND 4" WASTE ARM BRANCH UNDER FLOOR TO CLOSET BEND AND CLOSET FLANGE. PROVIDE 4"x3" REDUCING BUSHING AND EXTEND 3" VENT UP IN WALL TO FULL-SIZE HEADER.
- (P2) REDUCING COMBINATION WITH 3" WASTE STACK, 3" SANITARY CROSS (OR 3" SANITARY TEE), 3" DEEP-SEAL P-TRAP UNDER FLOOR FOR FLOOR DRAIN CONNECTION. PROVIDE 3"x2" REDUCING BUSHING AND 2" VENT STACK IN WALL. EXTEND 2" VENT UP IN WALL TO FULL-SIZE HEADER.
- (P3) REDUCING COMBINATION WITH 2" WASTE/VENT STACK IN WALL FOR LAVATORY/SINK/WATER COOLER ROUGH-IN CONNECTION. EXTEND 2" VENT UP IN WALL TO FULL-SIZE HEADER.
- (P4) 1/2" TYPE "L" COPPER UNDER FLOOR FROM "WATER-SAVER" TRAP PRIMING ASSEMBLY. EXTEND AND CONNECT TO FLOOR DRAIN (FD/TP). RE: DETAIL 'C', SHEET P4.1.
- (P5) SWEEP ELBOW WITH 3" WASTE STACK, 3" SANITARY TEE, 3" DEEP-SEAL P-TRAP UNDER FLOOR AND 3" DRAIN STUB-UP FOR JANITOR/MOP SINK DRAIN CONNECTION. PROVIDE 3"x2" REDUCING BUSHING AND 2" VENT STACK IN WALL TO ABOVE CEILING.
- (P6) 2" WASTE/VENT STACK IN WALL FOR SINK ROUGH-IN CONNECTION. EXTEND 2" SANITARY PIPING THROUGH WALL FRAMING AND CONNECT TO EXISTING WASTE/VENT STACK. FIELD VERIFY EXISTING CONDITIONS.
- (P7) EXTEND NEW 2" SANITARY WASTE AND CONNECT TO EXISTING SANITARY IN THIS AREA. FIELD VERIFY EXISTING CONDITIONS.
- (P8) 4" SANITARY WASTE DOWN IN CHASE TO FLOOR BELOW.
- (P9) VENT PIPING ABOVE CEILING, HIGH THROUGH STRUCTURE ABOVE; 2" UNLESS NOTED OTHERWISE.
- (P10) EXTEND 2" VENT ABOVE CEILING AND CONNECT TO EXISTING VENT PIPING OR VENT-THRU-ROOF.
- (P11) INSPECT EXISTING PLUMBING FIXTURE FOR SERVICEABILITY; NOTIFY ARCHITECT IMMEDIATELY OF ANY UNPREDICTABILITY. CLEAN AND SERVICE EXISTING PLUMBING FIXTURE AT COMPLETION OF PROJECT.

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.




LAND 3 ARCHITECT, INC.
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA 71201-5786
EMA
ENGINEERING & ARCHITECTURE
3714 ANDREWS ROAD, SUITE 200
MONROE, LA 71202
504-335-4000




DRAWN BY: JDK
CHK'D BY: TGS
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED


2ND FLOOR PLAN - WASTE AND VENT



PARTIAL SECOND FLOOR PLAN – WATER AND GAS
SCALE: 1/8" = 1'-0"



PARTIAL SECOND FLOOR PLAN – WATER AND GAS
SCALE: 1/8" = 1'-0"




ENLARGED SECOND FLOOR PLAN – WATER AND GAS
SCALE: 1/4" = 1'-0"

SEE SHEET P3.1 FOR PLUMBING GENERAL NOTES AND CONTRACTORS NOTES.

PLUMBING NOTES:

- (P1) 1 1/4" COLD WATER DOWN IN WALL TO FULL-SIZE HEADER. BRANCH, EXTEND THROUGH WALL FRAMING AND CONNECT 1/2" COLD WATER TO LAVATORY FAUCET THROUGH KEYED ANGLE-STOP SUPPLY, AND 1" COLD WATER TO WATER CLOSET FLUSH VALVE WITH INTEGRAL SERVICE STOP. PROVIDE WATER HAMMER AS REQUIRED.
- (P2) 1/2" HOT WATER DOWN IN CHASE. BRANCH, OFFSET THROUGH WALL FRAMING, EXTEND AND CONNECT TO LAVATORY FAUCET THROUGH KEYED ANGLE-STOP SUPPLY. PROVIDE POINT-OF-USE TEMPERING VALVE (TV); REFERENCE DETAIL "H", SHEET P4.1.
- (P3) 1/2" COLD WATER DOWN IN WALL. BRANCH, EXTEND AND CONNECT TO DRINKING FOUNTAIN/WATER COOLER THROUGH KEYED ANGLE-STOP SUPPLY.
- (P4) 3/4" HOT AND COLD WATER DOWN IN WALL. BRANCH, OFFSET THROUGH WALL FRAMING, EXTEND AND CONNECT TO JANITOR/SERVICE SINK FAUCET WITH INTEGRAL SERVICE STOPS THROUGH 3/4" x 1/2" REDUCERS; BRANCH, OFFSET THROUGH WALL FRAMING, EXTEND AND CONNECT 1/2" HOT AND COLD WATER TO SINK FAUCET THROUGH KEYED ANGLE-STOP SUPPLIES.
- (P5) EXTEND NEW DOMESTIC WATER PIPING ABOVE CONNECT TO EXISTING COLD WATER PIPING OF SUFFICIENT SIZE IN THIS AREA; NEW SIZE AND SERVICE AS NOTED.
- (P6) 1/2" HOT AND COLD WATER DOWN IN WALL. BRANCH, EXTEND AND CONNECT TO SINK FAUCET THROUGH KEYED ANGLE-STOP SUPPLIES. PROVIDE POINT-OF-USE TEMPERING VALVE (TV); REFERENCE DETAIL "H", SHEET P4.1.
- (P7) OFFSET, EXTEND AND CONNECT LOW PRESSURE (OUNCES) GAS BRANCH PIPING TO EQUIPMENT; PROVIDE FULL-PORT BALL VALVE, 12" LONG DRIP LEG WITH CAP, AND UNION PER DETAIL "E", SHEET P4.1, AND TRANSITION TO EPOXY-COATED CORRUGATED FLEXIBLE GAS TUBING FOR CONNECTION. PIPE SIZE AND CFH AS NOTED.
- (P8) EXTEND NEW 1 1/4" GAS AND CONNECT TO EXISTING GAS PIPING IN THIS AREA. FIELD VERIFY EXISTING CONDITIONS.
- (P9) PROVIDE FULL-PORT BALL VALVE, AUTO FLOW CONTROL VALVE, TO HYDRONICS CIRCUIT BALANCING VALVE WITH UNION ENDS, AND SWING CHECK VALVE IN HOT WATER RETURN SUB-LOOP, BALANCE TO 0.5 GPM UNLESS NOTED OTHERWISE. FIELD VERIFY EXISTING CONDITIONS.
- (P10) PROVIDE FULL-PORT BALL VALVE, AUTO FLOW CONTROL VALVE, TO HYDRONICS CIRCUIT BALANCING VALVE WITH UNION ENDS, AND SWING CHECK VALVE IN EXISTING HOT WATER RETURN SUB-LOOP, BALANCE TO 0.25 GPM UNLESS NOTED OTHERWISE. FIELD VERIFY EXISTING CONDITIONS.

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.



LAND 3
ARCHITECT, INC.
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA
71201-5786
EMA
ENGINEERING & ARCHITECTURE
1000 PINEAPPLE DRIVE
SUITE 200
MONROE, LOUISIANA 71201
504-488-4000



DRAWN BY: JDK
CHK'D BY: TGS
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED

PLUMBING
SCHEDULES AND
GENERAL NOTES

PLUMBING LEGEND

SYMBOL	DESCRIPTION
	SANITARY SEWER OR WASTE (SS OR W)
	SANITARY VENT (V)
	DOMESTIC COLD WATER (CW)
	DOMESTIC HOT WATER (HW)
	DOMESTIC HOT WATER RETURN (HWR)
	MEDIUM PRESSURE GAS (1 P.S.I.G. OR GREATER)
	LOW PRESSURE GAS (LESS THAN 1 P.S.I.G.)
	DRAIN PIPE (TYPE "L" HARD COPPER)
	CLEANOUT (CO)
	DOUBLE CLEANOUT (DCO)
	WALL CLEANOUT (WCO)
	FULL PORT BALL VALVE
	GATE VALVE
	LUBRICATED GAS COCK
	UNION
	WALL FAUCET (WF) OR HOSE BIBB (HB)
U/G	UNDERGROUND
U/S	UNDERSLAB
U/F	UNDERFLOOR
U/C	UNDERCOUNTER
VTR	VENT THRU ROOF/VENT TERMINAL
AFF	ABOVE FINISHED FLOOR
FD/(TP)	FLOOR DRAIN (WITH TRAP PRIMER)
FD/(TG)	FLOOR DRAIN (WITH PROSET TRAP GUARD)
FS/(TG)	FLOOR SINK (WITH PROSET TRAP GUARD)
MPG	MEDIUM PRESSURE GAS (1 PSI OR GREATER)
G	LOW PRESSURE GAS (LESS THAN 1 PSI)
FFCO	FINISHED FLOOR CLEANOUT
TWH	TANKLESS WATER HEATER

NOTE: NOT ALL SYMBOLS ARE USED.

MISCELLANEOUS

	NEW CONSTRUCTION
	EXISTING
	EXISTING TO BE REMOVED
	DETAIL NUMBER
	SHEET NUMBER
	RISER NUMBER
	RISER DESIGNATION (RISERS ON SEPARATE SHEET)
	RISER NUMBER
	RISER DESIGNATION (RISERS ON SAME SHEET)

* NOTE - SOME SYMBOLS MAY NOT BE USED.

GENERAL PLUMBING DEMOLITION NOTES:

- CAP ANY EXISTING PLUMBING PIPING NO LONGER IN USE - IN A CONCEALED LOCATION WHERE POSSIBLE - AND ABANDON. DISCONNECT ANY DOMESTIC WATER BRANCH LINES NOT LONGER IN USE AT NEAREST MAIN STILL IN USE, AND CAP. DO NOT LEAVE ANY DEAD LEGS.
- ALL EXISTING PLUMBING PIPING AND FIXTURES NOT DESIGNATED FOR REMOVAL SHALL REMAIN IN PLACE. CONTRACTOR SHALL BE RESPONSIBLE FOR REPAIRING OR REPLACING ANY PIPING/FIXTURES TO REMAIN THAT ARE DAMAGED IN ANY WAY DURING DEMOLITION PHASE.

GENERAL PLUMBING NOTES:

- CONTRACTOR SHALL COORDINATE EXACT PLUMBING FIXTURE TYPE, MOUNTING HEIGHT, ETC. WITH ARCHITECT AND OWNER PRIOR TO ORDER, ROUGH-IN AND INSTALLATION.
- ALL PENETRATIONS THRU FIRE WALLS AND FIRE PARTITIONS SHALL BE FIRE-STOPPED AS SPECIFIED AND AS SET FORTH IN U.L. FIRE RESISTANCE DIRECTORY, VOLUMES I AND II, LATEST EDITION.
- COORDINATE INSTALLATION OF PLUMBING FIXTURE CARRIERS WITH GENERAL CONTRACTOR. BLOCK-OUT STUDS AND/OR CMU BLOCKS WHERE REQUIRED TO CLEAR CARRIER RISERS, FLOOR SUPPORTS AND ARMS. PROVIDE SUPPORT BLOCKING SPANNING WALL FRAMING IN WALLS FOR ANCHORING CARRIERS AS REQUIRED.
- CONTRACTOR SHALL COORDINATE EXACT PLUMBING FIXTURE TYPE, MOUNTING HEIGHT, ETC. WITH ARCHITECT AND OWNER PRIOR TO ORDER, ROUGH-IN AND INSTALLATION.
- CONTRACTOR SHALL FIELD VERIFY EXACT SIZE, DEPTH, LOCATION, INVERT ELEVATION, ETC. OF EXISTING UTILITIES PRIOR TO PLUMBING WORK OF ANY KIND. NOTIFY ARCHITECT OF ANY CONFLICTS IMMEDIATELY.
- SAWCUT/CORE DRILL EXISTING SLAB AS REQUIRED TO INSTALL NEW PLUMBING PIPING UNDERSLAB AND PATCH TO MATCH EXISTING. PRIOR TO ANY SAWCUTTING/CORE DRILLING, CONTRACTOR SHALL FIELD VERIFY WHETHER EXISTING SLAB IS 2-WAY/POST-TENSION. IF EXISTING SLAB IS POST TENSION, THEN CONTACT ARCHITECT IMMEDIATELY AND DO NOT PERFORM ANY SAWCUTTING/CORE DRILLING PRIOR TO CONSULTING WITH A STRUCTURAL ENGINEER.
- UNDER SLAB PIPING AND PLUMBING FIXTURE ROUGH-IN INDICATED IS BASED ON INFORMATION AVAILABLE AT TIME OF DESIGN. COORDINATE EXACT LAYOUT AND ROUGH-IN REQUIREMENTS WITH APPROVED ARCHITECTURAL PLANS AND WITH ARCHITECT AND OWNER PRIOR TO INSTALLATION OF PIPING AND SLAB POUR.
- ALL WASTE PIPING MAINS UNDERSLAB SHALL BE 3" MINIMUM, SLOPED AT 1/8" PER FOOT. PROVIDE 3" x 2" LONG SWEEP REDUCING ELBOWS AND 3" x 3" x 2" COMBINATIONS AT 2" WASTE/VENT STACKS FOR LAVATORIES/SINKS.
- COORDINATE EXACT STACK AND LEADER LOCATIONS WITH FOOTINGS, COLUMNS AND STRUCTURAL FRAMING. RE: STRUCTURAL PLANS.
- COORDINATE EXACT LAYOUT AND ROUGH-IN REQUIREMENTS WITH APPROVED ARCHITECTURAL PLANS AND WITH ARCHITECT AND OWNER PRIOR TO INSTALLATION OF PIPING AND SLAB POUR.
- TRIP LEVERS FOR ACCESSIBLE WATER CLOSETS SHALL BE INSTALLED ON THE WIDE SIDE OF EACH TOILET ROOM/STALL PER ADA REQUIREMENTS.
- NEW VTRs SHALL BE LOCATED A MINIMUM OF 15' FROM ALL HVAC OUTSIDE AIR INTAKES. OUTSIDE AIR INTAKES OF NEW HVAC EQUIP SHALL NOT BE INSTALLED CLOSER THAN 10' FROM EXISTING VTRs STILL IN USE.
- CONFIRM EXACT LOCATION OF ALL REQUIRED ACCESS PANELS AND ACCESS DOORS WITH ARCHITECT PRIOR TO INSTALLATION.
- SLEEVE ALL CONCEALED GAS PIPING ROUTED INSIDE BUILDING (INSIDE WALLS/CHASES, ETC) IN STRICT ACCORDANCE WITH ALL LOCAL AND STATE BUILDING/PLUMBING CODES.
- CONTRACTOR SHALL PROVIDE GAS BRANCH PIPING WITH GAS COCK, DRIP LEG, UNION, REDUCER, EPOXY-COATED CORRUGATED STAINLESS STEEL FLEXIBLE CONNECTOR WITH SWIVEL ENDS AND CONNECT TO EQUIPMENT.
- ALL LAVATORIES AND SINKS SHALL BE PROVIDED WITH HOT WATER SUPPLY TEMPERATURE CONTROL THERMOSTATIC MIXING VALVES WHETHER INDICATED/NOTED ON PLAN OR NOT. PROVIDE MIXING VALVE "MV" WITH 1/2" HOT AND COLD WATER SUPPLY BRANCH PIPING FOR INDIVIDUAL FIXTURES AND MIXING VALVE "MVA" WITH 3/4" HOT AND COLD WATER SUPPLY BRANCH PIPING FOR GROUPED FIXTURES AS SPECIFIED. PROVIDE FULL-PORT BALL SHUT-OFF VALVES AT INLETS.
- PROVIDE CODE-COMPLIANT VENTED SLEEVE FOR ALL NEW GAS PIPING ROUTED UNDER CONCRETE FLOOR SLABS AND INSTALLED IN "CONCEALED" LOCATIONS.
- SLEEVE AND VENT ALL CONCEALED GAS PIPING ROUTED INSIDE BUILDING (INSIDE WALLS/CHASES, ETC) IN STRICT ACCORDANCE WITH ALL LOCAL AND STATE BUILDING/PLUMBING CODES.
- ALL EXPOSED GAS (INTERIOR AND EXTERIOR) SHALL BE PAINTED AFTER CLEANING WITH A WIRE BRUSH AND SOLVENT. PRIME AND PAINT AS SPECIFIED. PIPING EXPOSED TO NORMAL VIEW SHALL BE PAINTED TO MATCH ADJACENT BUILDING FINISHES AND/OR STRUCTURE AS DIRECTED BY ARCHITECT.
- ALL PIPING SHALL BE CONCEALED ABOVE ACCESSIBLE CEILING AND IN WALLS UNLESS INDICATED OTHERWISE. EXPOSED PIPING SHALL BE INSTALLED PARALLEL TO ALL BUILDING LINES AND SHALL BE SECURED IN PLACE WITH 2-HOLE PIPE STRAPS (COPPER FOR COPPER TUBING AND PIPING). PAINT EXPOSED PIPING, HANGERS, ETC AS DIRECTED BY ARCHITECT AND OWNER MATCHING ADJACENT FINISHES.
- AUTOMATIC SPRINKLER SYSTEM MODIFICATIONS SHALL BE IN STRICT ACCORDANCE WITH ALL REQUIREMENTS OF NFPA 13 AND 101.

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.

PLUMBING FIXTURE SCHEDULE

FIXTURE DESIGNATION	FIXTURE TYPE	MANUFACTURER /MODEL	CONNECTIONS		ELEC. DATA	DESCRIPTION	ACCESSORIES
			SUPPLY	WASTE			
WC	FLOOR-MOUNTED FLUSH VALVE WATER CLOSET	AMERICAN STANDARD MADERA FLOWISE 3043	1" CW	4"	--	VITREOUS CHINA, FLUSH VALVE, STANDARD RIM HEIGHT (15"), FLOOR MOUNTED, 1 1/2" TOP SPUD, 1.28 GALLONS PER FLUSH, ELONGATED BOWL, SIPHON JET, 12" ROUGH-IN, FULLY GLAZED TRAP-WAY	CHURCH 295SSCT HEAVY DUTY, WHITE, OPEN-FRONT ELONGATED SEAT WITH SELF-SUSTAINING STAINLESS STEEL CHECK HINGE; SLOAN ROYAL SMO-111-1.28, EXPOSED, SENSOR OPERATED WATER CLOSET FLUSH VALVE, POLISHED CHROME ANGLE-STOP, VACUUM BREAKER ELECTRONIC OVERRIDE; WHITE SNAP-ON BOLT CAPS
WCH	ACCESSIBLE FLOOR-MOUNTED FLUSH VALVE WATER CLOSET	AMERICAN STANDARD MADERA FLOWISE 3043	1" CW	4"	--	VITREOUS CHINA, FLUSH VALVE, STANDARD RIM HEIGHT (15"), FLOOR MOUNTED, 1 1/2" TOP SPUD, 1.28 GALLONS PER FLUSH, ELONGATED BOWL, SIPHON JET, 12" ROUGH-IN, FULLY GLAZED TRAP-WAY	CHURCH 295SSCT HEAVY DUTY, WHITE, OPEN-FRONT ELONGATED SEAT WITH SELF-SUSTAINING STAINLESS STEEL CHECK HINGE; SLOAN ROYAL SMO-111-1.28, EXPOSED, SENSOR OPERATED WATER CLOSET FLUSH VALVE, POLISHED CHROME ANGLE-STOP, VACUUM BREAKER ELECTRONIC OVERRIDE; WHITE SNAP-ON BOLT CAPS
URH	ACCESSIBLE WALL-HUNG URINAL	AMERICAN STANDARD ALLBROOK FLOWISE 6550	3/4" CW	2"	--	VITREOUS CHINA, WALL-HUNG, REAR OUTLET, 0.5 GALLONS PER FLUSH, 3/4" TOP SPUD, SIPHON JET, FLUSHING RIM; MOUNT AT ADA ACCESSIBLE HEIGHT (REFER: ARCHITECTURAL INTERIOR ELEVATIONS)	ZURN Z1222 URINAL CARRIER WITH ADJUSTABLE BEARING PLATES; RECTANGULAR TUBING UPRIGHTS; WELDED BASE FEET; BOLT CAPS; SLOAN-186 SMO-0.5-OR SENSOR OPERATED URINAL FLUSH VALVE, 0.5 GALLONS PER FLUSH, POLISHED CHROME, VACUUM BREAKER, ANGLE-STOP WITH COVER, ELECTRONIC OVERRIDE
CLH	ACCESSIBLE UNDERCOUNTER MOUNTED LAVATORY	AMERICAN STANDARD STUDIO 0618.000	1/2" CW 1/2" HW	2"	--	21 1/8" x 14" x 6" DEEP RECTANGLE, UNDERCOUNTER MOUNT, VITREOUS CHINA, FRONT OVERFLOW, UNGLAZED RIM, WHITE, ADA ACCESSIBLE HEIGHT; MOUNTING KIT, TRUEBRO MOLDED WASTE AND SUPPLY COVERS; COORDINATE CUT OUT AND FAUCET HOLE LOCATION WITH MILLWORK SUPPLIER	DELTA FAUCETS 590-PALGHDF; ELECTRONIC PROXIMITY SENSING TECHNOLOGY; DECK MOUNT, SINGLE HOLE, (4) 'C' BATTERIES, SURFACE MOUNT CONTROL BOX, VANDAL RESISTANT; 0.5 GALLONS PER MINUTE LAMINAR FLOW OUTLET; LEONARD MODEL 170-LF THERMOSTATIC MIXING VALVE; OPEN GRID STRAINER WITH TAIL PIECE; P-TRAP WITH CLEAN OUT FITTING
SK	ACCESSIBLE SELF-RIMMING COUNTER SINK	ELKAY LRADQ211965	1/2" CW 1/2" HW	1 1/2"	--	21" x 19" x 6 1/2" DEEP, SINGLE COMPARTMENT, 18 GAUGE, TYPE 302 STAINLESS STEEL, SELF-RIMMING DROP-IN, FULLY COATED UNDERSIDE, THREE (3) FAUCET HOLE DRILLING, SATIN FINISH, QUICK-CLIP ATTACHMENT	ELKAY LKD2432BH FAUCET WITH 4" WRIST BLADE HANDLES AND HI-ARC GOOSENECK SPOUT; KEYPED ANGLE-STOP SUPPLIES WITH FLEXIBLE RISERS; LK40-35 OFFSET DRAIN WITH DUO STRAINER; 17 GAUGE C.P.B. P-TRAP WITH CLEANOUT; WHITE ADA INSULATION KIT
SKB	BREAKROOM COUNTER SINK	ELKAY DLR-2522-12	1/2" CW 1/2" HW	1 1/2"	--	22" x 19" TYPE 302 STAINLESS STEEL, 18 GAUGE SINGLE COMPARTMENT SINK, COATED UNDERSIDE, FOUR (4) HOLE DRILLING.	LK2433BH TRIM WITH HIGH-ARC GOOSENECK, SPRAY AND 4" WRIST BLADES, LK-35 DRAIN, KEYED ANGLE STOPS, FLEXIBLE RISERS, AND C.P.B. P-TRAP.
MS	TERRAZZO BASIN MOP SINK	FIAT TSB3010	1/2" CW 1/2" HW	3"	--	24" x 24" x 12" DEEP WITH STAINLESS STEEL CAP ON THRESHOLD, 6" DROP FRONT, MSG STAINLESS STEEL WALL GUARDS	KOHLER K-8907 SERVICE SINK FAUCET WITH VACUUM BREAKER, LOOSE KEY STOPS, ADJUSTABLE WALL BRACE, PAIL HOOK, HOT AND COLD LEVER HANDLES ON 8" CENTERS; 3/4" HOSE THREAD ON SPOUT; STAINLESS STEEL STRAINER, 3" OUTLET CONNECTION
JS	JANITORS SINK	FIAT SF-1-F TUF-TUB LAUNDRY TUB	1/2"	1/2"	1 1/2"	20" x 23 7/8" x 33 11/16" MODELED FINE CELLED, STRUCTURAL POLYMER, INTERIALLY MOLDED DRAIN WITH PLATIC STOPPER AND TAIL PIECE NUT, 20 GALLON CAPACITY, 4" LEDGE WITH (2) MOLDED SOAP DISHES, 1" HOLES FOR 4" ON DECK FAUCET	A1 FAUCET, PROVIDE DRAIN ASSEMBLY, C.P.B. P-TRAP AND ANGLE-STOP SUPPLIES WITH FLEXIBLE RISERS
HB	INTERIOR BOXED HOSE BIBB	WOODFORD MODEL B74	3/4" CW	--	--	ANTI-SIPHON CLOSE-COUPLED WALL BOX HYDRANT, NIDEL 34HF VACUUM BREAKER, FLAT DOOR WITH POLISHED CHROME FINISH, 3/4" HOSE THREAD NOZZLE, LOOSE "TEE" KEY, FLUSH WALL BOX	
EWCH	WALL-HUNG BI-LEVEL ACCESSIBLE WATER COOLER	ELKAY LMABFTLBWSSK	1/2" CW	1 1/2"	120V	ALL 304L STAINLESS STEEL VANDAL-RESISTANT BI-LEVEL WALL-HUNG ELECTRIC WATER COOLER WITH BOTTLE FILLING STATION AND FILTER, FRONT AND SIDE PUSH-BUTTON ACTIVATION, 8.0 GPH, 370 WATTS, 120V; MOUNT AT ADA ACCESSIBLE HEIGHT PER ARCHITECTURAL INTERIOR ELEVATIONS	VANDAL-RESISTANT BUBBLER; EZH20 ELECTRONIC BOTTLE FILLER STATION; LKAPREZL APRON; WADE CHAIR CARRIER WITH WALL BRACKET; KEYPED ANGLE-STOP SUPPLY; 17 GAUGE C.P.B. P-TRAP WITH CLEANOUT. PROVIDE (6) SIX SPARE FILTERS
FD	FLOOR DRAIN	ZURN ZN415-BZ1	--	--	--	CAST IRON FLOOR DRAIN; TWO PIECE BODY; DRAINAGE FLANGE, WEEPHOLES, ADJUSTABLE NICKEL BRONZE STRAINER AND VANDAL PROOF TOP ASSEMBLY, 6" TOP, TRAP SEAL DEVICE	
TP	TRAP PRIMER	ZURN Z1021	--	--	--	WATER SAVER LAVATORY/SINK TRAP PRIMER SET WITH C.P.B. P-TRAP, NICKEL BRONZE STRAINER AND VANDAL PROOF HARDWARE	
TG	TRAP GUARD	PROSET	--	--	--	ELASTOMERIC, NORMALLY CLOSED DROP-IN DEVICE TO PREVENT EVAPORATION OF THE TRAP SEAL; OPENS WITH FLUID; SIZE AS APPLICABLE PER PLANS.	
TMV	POINT-OF-USE MIXING VALVE	SYMMONS MODEL 5-110-CK-X	--	--	--	MIXING VALVE FOR SINGLE FIXTURES, 0.5 GPM, MINIMUM FLOW, ALL BRONZE REMOVABLE PISTON AND THERMAL MOTOR, ROUGH BRONZE FINISH WITH COMPRESSION 3/8" INLETS AND OUTLET.	1/2" x 3/8" REDUCERS AND UNION ADAPTORS. PROVIDE AT ALL SINKS AND LAVATORIES.
HWC	HOT WATER CIRCULATOR	GRUNDFOS UP15-55 SFC	HW	--	115/16	CENTRIFUGAL IN-LINE PUMP, ALL BRONZE, 87 W, 5 GPM AT 14 FT. HD, FLANGED 3/4" CONNECTIONS	PROVIDE INTERMATIC 7-DAY PROGRAMMABLE TIME CLOCK FOR PUMP ON-OFF SCHEDULE.
TWH	COMMERCIAL GAS TANKLESS WATER HEATER	NAVLEN NPE-240A2	HW/CW	--	120/16	INDOOR/OUTDOOR WALL-HUNG HIGH EFFICIENCY CONDENSING TANKLESS WATER HEATER, LOW NOx EMISSIONS, 199,900 BTUH, NATURAL GAS 0.95 UEF, MAXIMUM 11.2 GPM FLOW RATE, BUILT-IN DISPLAY CONTROL PANEL	PROVIDE ASME T&P RELIEF VALVE WITH 80 PSI SETPOINT, EXPANSION TANK, NEUTRALIZER KIT, ISOLATION VALVE KIT. PROVIDE INTAKE AND VENT PIPING PER MANUFACTURER'S INSTALLATION INSTRUCTIONS.
WH*	COMMERCIAL ELECTRIC WATER HEATER	A.O. SMITH DURA-POWER DEL-30	HW/CW	--	208/16	30 GALLON SHORT MODEL, 3.0KW DUAL ELEMENT, SIMULTANEOUS OPERATION, 208V/10, 24 GPH RECOVERY AT 100°F RISE	PROVIDE ASME T&P RELIEF VALVE WITH 80 PSI SETPOINT, EXPANSION TANK, AND HEAT TRAP AS REQUIRED
ETWH	ELECTRIC TANKLESS WATER HEATER	EEMAX LAVADVANTAGE SPEX3208T	HW/CW	--	208/16	ABS-UL 94 5VA RATED COVER, 0.2 GPM TURN ON, REPLACEABLE CARTRIDGE ELEMENT, REPLACEABLE FILTER AT INLET, 3/8" COMPRESSION FITTINGS, MAXIMUM 150 PSI.	



* THE MECHANICAL CONTRACTOR SHALL COORDINATE THE EXACT VOLTAGE & PHASE OF EACH AND EVERY EQUIPMENT ITEM WITH THE ELECTRICAL CONTRACTOR, PRIOR TO ORDER. LOCATE TRIP LEVER ON WIDE (APPROACH) SIDE OF ROOM/STALL. COORDINATE WITH ARCHITECTURAL PLANS. SIZE AS NOTED ON PLANS.

ACCEPTABLE MANUFACTURERS:	
WATER CLOSETS, LAVATORIES - KOHLER, AMERICAN STANDARD, ZURN, SLOAN.	LAVATORY/SINK ACCESSORIES (EXCLUDING FAUCETS) - MCGUIRE, MAINLINE, KOHLER, AMERICAN STANDARD, ZURN, DEARBORN, BRASSCRAFT.
CARRIERS - JAY R. SMITH, ZURN, WATTS, JOSAM, WADE, MIFAB.	FAUCETS AND TRIM - CHICAGO, KOHLER, AMERICAN STANDARD, ELKAY, ZURN, T & S BRASS, SPEAKMAN, MOEN, DELTA COMMERCIAL [CAST BRASS BODY].
COUNTER SINKS - ELKAY, KOHLER, AMERICAN STANDARD, JUST.	FLOOR DRAINS, FLOOR SINKS, CLEANOUTS - WADE, JOSAM, JAY R. SMITH, ZURN, MIFAB, WATTS.
	P-TRAP & SUPPLY STOP INSULATION KITS - TRUEBRO, PLUMBEREX.
	WATER HEATER - TAKAGI, NAVLEN, RINNAI.



CONTRACTOR NOTES:

- THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.
- EXISTING PLANS ARE NOT AVAILABLE. EXISTING SANITARY SEWER ARE ASSUMED LOCATIONS BASED ON FIELD OBSERVATIONS. CONTRACTOR SHALL SAWCUT, BREAKOUT AND REMOVE EXISTING CONCRETE SLAB AND EXCAVATE AS REQUIRED TO VERIFY EXACT SIZE, LOCATION, INVERT ELEVATION, ETC. PRIOR TO WORK OF ANY KIND. NOTIFY ARCHITECT/ENGINEER IMMEDIATELY OF SIGNIFICANT DISCREPANCIES DETRIMENTAL TO SCOPE OF WORK.
- EXISTING PIPING UNDERSLAB MAY BE REUSED IN PLACE AS APPLICABLE AND WHERE FEASIBLE TO DO SO.


GAS EQUIPMENT LOAD BREAKDOWN	
EQUIPMENT	CONNECTED GAS LOAD (CFH)
TANKLESS WATER HEATER	199
RTU-1	108
RTU-2	130
RTU-3	260
RTU-4	53
TOTAL	750 CFH
ESTIMATED DISTANCE	324 FEET
DESIGNED LOAD	935 CFH @ 350 FEET




A DETAIL - EXTERIOR CLEANOUTS
NO SCALE




B DETAIL - PIPE SUPPORTS
NO SCALE




C DETAIL - "WATER-SAVER" TRAP PRIMER ASSEMBLY
NO SCALE




D DETAIL - TRAP GUARD
NO SCALE




E DETAIL - GAS CONNECTION
NO SCALE



F DETAIL - GAS PIPE SUPPORT ON ROOF
NO SCALE




G DETAIL - GAS-FIRED TANKLESS WATER HEATER
NO SCALE




- NOTES:
1. THERMOSTATIC MIXING VALVE MUST HAVE BRACKET FOR MOUNTING TO WALL.
 2. PROVIDE RUBBER SPACER BETWEEN WALL AND TMV. WALL ANCHOR SYSTEM MUST BE USED.
 3. STAINLESS STEEL SUPPLY LINES MUST BE KEPT TO MINIMUM LENGTH.

H DETAIL - TEMPERED & COLD SUPPLY LAVATORY
NO SCALE




J ELEVATOR SUMP PUMP
NO SCALE


THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.




A DETAIL - ROOF VENT PIPE
NO SCALE



B DETAIL - PLATFORM MOUNTED WATER HEATER
NOTE: PROVIDE INVERTED U-LOOP HEAT TRAP FOR INLET/OUTLET PIPING.
NO SCALE




C DETAIL - GAS PIPE SUPPORT ON ROOF
NO SCALE




D DETAIL - OPEN-SITE CONDENSATE DRAIN
NO SCALE

OUACHITA PARISH PUBLIC LIBRARY
 MAIN BRANCH RENOVATION
 MONROE, LOUISIANA



LAND 3
 ARCHITECT, INC.
 A PROFESSIONAL CORPORATION
 1900 STUBBS AVENUE
 MONROE, LA
 71201-5786
EMA
 ENGINEERING & ARCHITECTURE
 3441 STEVENS ROAD, SUITE 200
 SHREVEPORT, LOUISIANA 71206
 504-425-4000



DRAWN BY: JDK
 CHK'D BY: TGS
 JOB # 1963
 DATE: 08/2024
 COPYRIGHT PROTECTED

PLUMBING
 DETAILS AND
 RISERS




P4.2



THE CONTRACTOR SHALL BE REQUIRED
 TO VISIT THE SITE TO FIELD VERIFY
 EXISTING CONDITIONS PRIOR TO
 SUBMITTING A PROPOSAL.

SEE SHEET P3.1 FOR PLUMBING GENERAL
 NOTES AND CONTRACTORS NOTES.

FIRE PROTECTION NOTES:



- FP1** CONTRACTOR SHALL MODIFY EXISTING SPRINKLER SYSTEM PIPING AND HEADS IN STRICT ACCORDANCE WITH NFPA 13, NFPA 101, AND REQUIREMENTS OF STATE FIRE MARSHAL, CITY OF MONROE FIRE PREVENTION BUREAU, AND INSURANCE CARRIER AS REQUIRED TO FACILITATE SCOPE OF RENOVATION. RE: ARCHITECTURAL PLANS. MODIFICATION SHALL INCLUDE, BUT NOT BE LIMITED TO, EXTENSION, RELOCATION, REMOVAL AND/OR REPLACEMENT OF EXISTING PIPING AND HEADS. FIELD VERIFY EXISTING CONDITIONS PRIOR TO WORK. ALL SPRINKLER HEADS SHALL BE NEW, LOCATED IN THE CENTER OF EACH CEILING TILE AND SHALL BE WHITE POLYESTER-COATED SEMI-RECESSED TYPE WITH WHITE ESCUTCHEONS IN ALL WHITE GRID CEILING SYSTEMS. SPRINKLER HEADS SHALL BE SEMI-RECESSED BRASS WITH ESCUTCHEON PLATES FIELD PAINTED TO MATCH CEILING FINISH AS DIRECTED BY ARCHITECT IN ALL NOTED CEILING AREAS. COORDINATE WITH ARCHITECT PRIOR TO MATERIAL ORDER, ROUGH-IN, INSTALLATION AND CONNECTION. ALL PIPING, SPRINKLER HEADS, AND ACCESSORIES SHALL BE RELOCATED AS REQUIRED TO FACILITATE NEW HVAC WORK (RE: SHEET M1.1), AND NEW WORK OF OTHER TRADES. SUBMIT SHOP DRAWINGS, REVIEW FEE, REVIEW APPLICATION, AND HYDRAULIC CALCULATIONS TO LOCAL FIRE DEPARTMENT HAVING JURISDICTION AND ENGINEER. ALL NEW SPRINKLER HEADS SHALL BE SEMI-RECESSED EQUAL TO TYCO TYP-L.
- FP2** UNDER ALTERNATE BID, MODIFY/REPLACE EXISTING SEMI-RECESSED SPRINKLER HEADS IN EXISTING CEILING THAT IS TO REMAIN WITH CHROME-PLATED SURFACE MOUNT SPRINKLER HEADS EQUAL TO TYCO TYP-L.
- FP3** CONTRACTOR SHALL PROVIDE SPRINKLER SYSTEM PIPING AND HEADS FOR TREE CANOPY IN STRICT ACCORDANCE WITH NFPA 13, NFPA 101, AND REQUIREMENTS OF STATE FIRE MARSHAL, CITY OF MONROE FIRE PREVENTION BUREAU, AND INSURANCE CARRIER AS REQUIRED.
- FP4** UNDER ADD ALTERNATE PROVIDE THE FOLLOWING FOR ROOM 172 (REFERENCE ARCHITECTURAL PLANS AND SPECIFICATIONS FOR ADD ALTERNATES):
 - A. PROVIDE A COMPLETE NORVEC 1320 FIRE SUPPRESSION SYSTEM FOR ROOM 209. NORVEC 1320 FIRE SUPPRESSION SYSTEM LAYOUT INDICATED ON THESE DOCUMENTS IS IS PRELIMINARY. FINAL SYSTEM DESIGN, LAYOUT, SHALL BE PROVIDED BY FIRE SPRINKLER CONTRACTOR IN ACCORDANCE WITH NFPA 2001 AND NFPA 75 RE: SPECIFICATIONS. COORDINATE EXACT EQUIPMENT LAYOUT, CLEARANCES AND ALL OTHER REQUIREMENTS W/ ARCH AND OWNER PRIOR TO INSTALLATION. REFERENCE SECTION 21.2200 FOR ADDITIONAL INFORMATION.
 - B. CLEAN AGENT SUPPRESSION SYSTEM SHALL UTILIZE A CLEAN AGENT WITH AN OZONE DEPLETION POTENTIAL OF ZERO (OPD = 0) AND AT TOTAL GLOBAL WARMING POTENTIAL OF ONE OR LESS (GWP <= 1). ACCEPTABLE AGENTS: NORVEC 1320.
 - C. PROVIDE A/V HORN/STROBE OUTSIDE OF SERVER ROOM ENTRANCE DOORS TO PROVIDE OCCUPANT NOTIFICATION OF CLEAN AGENT SYSTEM OPERATION.
 - D. PROVIDE COMPLETE INTERFACE BETWEEN CLEAN AGENT SYSTEM AND BUILDING FIRE ALARM SYSTEMS. ACTIVATION OF SYSTEM SHALL NOTIFY FIRE ALARM SYSTEM.
- FP5** CONTRACTOR SHALL RAISE EXISTING FIRE SPRINKLER MAIN TO 6'-8" ABOVE FINISH FLOOR TO BOTTOM OF PIPE. FIELD VERIFY EXISTING CONDITIONS.

-  **BASE BID**
 SEE NOTE FP1
 29,200 SQUARE FEET
-  **ALTERNATE**
 SEE NOTE FP2
 16,600 SQUARE FEET
-  **BASE BID**
 SEE NOTE FP1
ALTERNATE: CLEAN AGENT
 SEE NOTE FP3
 531 SQUARE FEET



FIRST FLOOR PLAN - FIRE PROTECTION

SCALE: 1/16" = 1'-0"



SECOND FLOOR PLAN - FIRE PROTECTION


SCALE: 1/16" = 1'-0"

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.

MECHANICAL DEMOLITION NOTES:

--- EXISTING TO REMAIN.
 -x-x- EXISTING TO BE REMOVED.

- (MD1) EXISTING MINI-SPLIT CEILING CASSETTE AND ASSOCIATED HEAT PUMP (ON ROOF), PIPING, CONTROLS, AND POWER TO REMAIN. PROTECT DURING DEMOLITION AND NEW CONSTRUCTION.
- (MD2) EXISTING ROOFTOP UNIT, PIPING, CONTROLS, AND POWER TO REMAIN. PROTECT DURING DEMOLITION AND NEW CONSTRUCTION.
- (MD3) DISCONNECT, REMOVE, AND DISCARD EXISTING EXHAUST FAN AND ASSOCIATED DUCTWORK AND EXHAUST LOUVER. PATCH WALL AS DIRECTED BY THE ARCHITECT.
- (MD4) EXISTING MINI SPLIT AND ASSOCIATED HEAT PUMP, PIPING, CONTROLS, AND POWER TO REMAIN. PROTECT DURING DEMOLITION AND NEW CONSTRUCTION.
- (MD5) EXISTING TRANSFER DUCT AND AIR DEVICES TO REMAIN. PROTECT DURING DEMOLITION AND NEW CONSTRUCTION.
- (MD6) DISCONNECT, REMOVE, AND DISCARD EXISTING ALL HVAC EQUIPMENT AND ASSOCIATED DUCTWORK, PIPING, POWER, CONTROLS, AND AIR DEVICES IN THIS AREA.
- (MD7) DISCONNECT, REMOVE, AND DISCARD DUCTWORK AND AIR DEVICES SERVING THESE OFFICES.
- (MD8) DISCONNECT, REMOVE, AND DISCARD EXISTING UNIT HEATER AND ASSOCIATED PIPING, AIR DEVICES, DUCT, AND CONTROLS AND POWER.
- (MD9) DISCONNECT, DISCARD, AND REMOVE EXISTING OUTSIDE AIR WALL LOUVER ABOVE DOOR. PATCH WALL AS DIRECTED BY ARCHITECT.
- (MD10) DISCONNECT, REMOVE, AND DISCARD SUPPLY AND RETURN AIR DUCTWORK AND AIR DEVICES ASSOCIATED WITH EXISTING RTU.
- (MD11) EXISTING CONCENTRIC DIFFUSER SYSTEM TO REMAIN. PROTECT DURING DEMOLITION AND NEW CONSTRUCTION.
- (MD12) DISCONNECT, REMOVE, AND DISCARD EXISTING CONCENTRIC DIFFUSER SYSTEM AND ANY SUPPLY DUCTWORK AND AIR DEVICES SERVED BY UNIT.
- (MD13) DISCONNECT, REMOVE, AND DISCARD EXISTING SUPPLY AIR DUCTWORK AND ASSOCIATED AIR DEVICES.
- (MD14) DISCONNECT, REMOVE, AND DISCARD EXISTING AIR DEVICE AND ASSOCIATED BRANCH DUCT BACK TO SUPPLY TRUNK. CAP AND SEAL UNUSED OPENING IN TRUNK DUCT.
- (MD15) EXISTING SUPPLY AIR TRUNK DUCT TO REMAIN. PATCH AND SEAL ANY UNUSED OPENINGS IN DUCT.




FIRST FLOOR PLAN DEMOLITION - HVAC
 SCALE: 1/16" = 1'-0"

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.

MECHANICAL DEMOLITION NOTES:


- EXISTING TO REMAIN.
- x-x-x- EXISTING TO BE REMOVED.

- (MD1) DISCONNECT, REMOVE, AND DISCARD EXISTING AIR HANDLING UNIT AND ASSOCIATED CONDENSING UNIT, PIPING, DUCTWORK, AIR DEVICES, CONTROLS, AND POWER. PATCH WALLS, ROOF, ETC AFFECTED BY DEMOLITION. RETURN PLENUM TO REMAIN. PROTECT PLENUM DURING DEMOLITION AND NEW CONSTRUCTION.
- (MD2) EXISTING HORIZONTAL AIR HANDLING UNIT AND ASSOCIATED CONDENSING UNIT, PIPING, SUPPLY AIR DUCTWORK, RETURN PLENUM, CONTROLS, AND POWER TO REMAIN. PROTECT DURING DEMOLITION AND NEW CONSTRUCTION. DISCONNECT AND REMOVE ASSOCIATED RETURN AIR DUCTWORK AND AIR DEVICES CONNECTED TO EXISTING RETURN PLENUM AND OUTSIDE AIR DUCTWORK. PATCH WALL AS DIRECTED BY ARCHITECT.
- (MD3) DISCONNECT, REMOVE, AND DISCARD EXISTING ROOFTOP UNIT, PIPING, AIR DEVICES, DUCTWORK, CONTROLS, AND POWER. RETAIN ROOF CURB FOR RE-USE. PROTECT CURB DURING DEMOLITION AND NEW CONSTRUCTION. THE AREA SERVED BY THE ROOFTOP UNIT IS OUTLINED ON THIS SHEET.
- (MD4) DISCONNECT, REMOVE, AND DISCARD EXISTING OUTSIDE AIR HANDLING UNIT AND ASSOCIATED CONDENSING UNIT, DUCTWORK, PIPING, POWER, AND CONTROLS.
- (MD5) EXISTING OUTSIDE AIR DUCT UP TO ROOF AND ASSOCIATED INTAKE HOOD TO REMAIN. PROTECT DURING DEMOLITION AND NEW CONSTRUCTION.




SECOND FLOOR PLAN DEMOLITION – HVAC
 SCALE: 1/16" = 1'-0"

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.



- MECHANICAL NOTES:**
- (M1) 10"Ø EXHAUST DUCT UP THROUGH FLAT ROOF AND INSULATED METAL ROOF CURB TO NOTED GREENHECK GRS-10 SPUN ALUMINUM GRAVITY VENTILATOR WITH ALUMINUM BIRDSCREEN. PREP, PRIME, AND PAINT VENTILATOR AND HOOD TO MATCH ROOF PANELS. TRANSITION IN VERTICAL FROM EXHAUST FAN CURB CONNECTION SIZE AS REQUIRED. RE: DETAIL "D" ON SHEET M3.2.
 - (M2) 12"Ø EXHAUST DUCT UP THROUGH FLAT ROOF AND INSULATED METAL ROOF CURB TO NOTED GREENHECK GRS-12 SPUN ALUMINUM GRAVITY VENTILATOR WITH ALUMINUM BIRDSCREEN. PREP, PRIME, AND PAINT VENTILATOR AND HOOD TO MATCH ROOF PANELS. TRANSITION IN VERTICAL FROM EXHAUST FAN CURB CONNECTION SIZE AS REQUIRED. RE: DETAIL "D" ON SHEET M3.2.
 - (M3) 16"Ø OUTSIDE AIR DUCT DOWN THROUGH FLAT ROOF AND INSULATED METAL ROOF CURB TO NOTED GREENHECK GRS-16 SPUN ALUMINUM GRAVITY VENTILATOR WITH ALUMINUM BIRDSCREEN. PREP, PRIME, AND PAINT VENTILATOR AND HOOD TO MATCH ROOF PANELS. TRANSITION IN VERTICAL FROM EXHAUST FAN CURB CONNECTION SIZE AS REQUIRED. RE: DETAIL "D" ON SHEET M3.2.
 - (M4) LOW PRESSURE (OUNCES) GAS PIPING DOWN THROUGH ROOF WITH AWI SERIES PIPE VAULT, PIPE SEAL, CURB CAP AND ROOF CURB; PIPE SIZE AS NOTED.
 - (M5) ALL GAS PIPING WITH SUPPORTS, PIPE CLAMPS, ETC. SHALL BE PREPPED, PRIMED AND PAINTED AS SPECIFIED. GAS PIPING EXPOSED TO VIEW SHALL BE PAINTED TO MATCH BUILDING FINISHES. PROVIDE (2) COATS MINIMUM OF EACH PRIMER AND FINISH OIL-BASED ENAMEL PAINT.
 - (M6) TYPE "L" HARD COPPER CONDENSATE DRAIN PIPING FROM ROOFTOP UNIT. EXTEND AND TERMINATE OPEN-SIGHT AT ROOF DRAIN. PIPING SHALL BE LOCATED AND INSTALLED SUCH THAT NORMAL RAIN WATER FLOW INTO AND THROUGH ROOF DRAIN IS NOT OBSTRUCTED. PROVIDE PIPE SUPPORTS AS DETAILED AND AT SPECIFIED INTERVALS.
- PLUMBING NOTES:**
- (P1) ALL GAS PIPING WITH SUPPORTS, PIPE CLAMPS, ETC. SHALL BE PREPPED, PRIMED AND PAINTED AS SPECIFIED. GAS PIPING EXPOSED TO VIEW SHALL BE PAINTED TO MATCH BUILDING FINISHES. PROVIDE (2) COATS MINIMUM OF EACH PRIMER AND FINISH OIL-BASED ENAMEL PAINT.
 - (P2) TYPE "L" HARD COPPER CONDENSATE DRAIN PIPING FROM ROOFTOP UNIT. EXTEND AND TERMINATE OPEN-SIGHT AT ROOF DRAIN. PIPING SHALL BE LOCATED AND INSTALLED SUCH THAT NORMAL RAIN WATER FLOW INTO AND THROUGH ROOF DRAIN IS NOT OBSTRUCTED. PROVIDE PIPE SUPPORTS AS DETAILED AND AT SPECIFIED INTERVALS.
 - (P3) ROUTE GAS PIPING ACROSS ROOF AS NOTED. PROVIDE PIPING SUPPORTS AS DETAILED, SPACED AS RECOMMENDED BY MANUFACTURER. REFERENCE DETAIL "C", SHEET P4.2.
 - (P4) EXTEND NEW CONDENSATE DRAIN PIPING AND TERMINATE AT NEAREST VENT-THRU-ROOF.
 - (P5) EXISTING RTU AND ASSOCIATED GAS PIPING, CONDENSATE PIPING, ETC. TO REMAIN. PROTECT DURING DEMOLITION AND NEW CONSTRUCTION.
 - (P6) PROVIDE VENT EXTENSION AS REQUIRED TO MAINTAIN REQUIRED CLEARANCE FROM ROOFTOP UNIT OUTSIDE AIR INTAKE. FIELD VERIFY EXITING CONDITIONS.

ROOF PLAN - MECHANICAL PLUMBING
 SCALE: 1/16" = 1'-0"




DRAWN BY:	JDK
CHK'D BY:	TGS
JOB #	1963
DATE:	08/2024
COPYRIGHT PROTECTED	

ROOF PLAN -
 MECHANICAL
 PLUMBING

MP1.1


THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.



- HVAC NOTES:**
- EXISTING TO REMAIN.
 - (H1) COORDINATE THE EXACT LOCATION OF THERMOSTAT AND MOUNTING REQUIREMENTS WITH THE OWNER PRIOR TO MATERIAL ORDER ROUGH-IN AND INSTALLATION.
 - (H2) ACUTHERM THERMAFUSER TF-HC THERMALLY POWERED VARIABLE AIR VOLUME DIFFUSER WITH INDIVIDUAL HEATING AND COOLING THERMAL ELEMENTS (NO SUBSTITUTIONS; SF-HC EQUIVALENT ARE NOT ACCEPTABLE); AIRFLOW AS NOTED; 10% NECK UNLESS NOTED OTHERWISE. ADJUST COOLING ELEMENT FOR 72°F AND HEATING ELEMENT FOR 70°F.
 - (H3) PROVIDE FLEXIBLE DUCT CONNECTIONS AT EFS, RTUS, AND AHUS.
 - (H4) 14" EXHAUST DUCT UP TO EXHAUST CAP ON ROOF EQUAL TO GREENHECK GRSR-10; TRANSITION IN VERTICAL FROM EXHAUST FAN CURB CONNECTION SIZE AS REQUIRED. RE: DETAIL "D" ON SHEET M3.2. REFER TO SHEET MP.1.1 FOR EXACT LOCATION.
 - (H5) INTERLOCK EXHAUST FAN WITH ROOM LIGHT SWITCH. RE: ELECTRICAL.
 - (H6) PROVIDE INTERNALLY LINED SUPPLY AND RETURN DUCT DROPS FULL SIZE OF RTU OPENINGS. OFFSET IN CURB AND STRUCTURE AS REQUIRED AND TRANSITION TO DUCT SIZE INDICATED ON DRAWING.
 - (H7) EXTEND NOTED SIZE SUPPLY/RETURN DUCT DOWN TO LOWEST ELEVATION POSSIBLE ABOVE LOW CEILING.
 - (H8) ADJUSTABLE SPLITTEE WITH DOUBLE-THICKNESS TURNING VANES AND MANUAL VOLUME CONTROL DAMPERS. SPLIT RATIO AS NOTED. TRANSITION OFF EACH SPLIT TO DUCT SIZE NOTED.
 - (H9) ALL DUCTS PENETRATING THIS WALL AND SERVING THE AREA WITH LOWER, 9FT CEILING MUST DROP TO RIGHT ABOVE THE CEILING BEFORE PENETRATING THE WALL. REFER TO ARCHITECTURAL PLANS FOR AREAS WITH 9FT CEILING ALONG THIS WALL.
 - (H10) ROUTE MAIN TRUNK (SUPPLY AND RETURN) ABOVE HIGH CEILING.
 - (H11) PROVIDE TRANSFER DUCT FULL SIZE OF 14/14" GRILLE. PROVIDE TWO (2) TYPE "G4" RETURN GRILLES. MOUNT AS HIGH AS POSSIBLE BENEATH CEILING.
 - (H12) EXISTING SUPPLY AIR TRUNK DUCT TO REMAIN. CONNECT NEW BRANCH DUCTS TO EXISTING DUCT, AS INDICATED. SEAL ANY UNUSED OPENING IN DUCT.
 - (H13) CONNECT S/A DUCT TO EXISTING DUCT TRUNK/TAP FROM NOTED ERTU.
 - (H14) IN-LINE EXHAUST FAN FOR FREEZE PROTECTION OF CEILING SPACE. PLACE THERMOSTAT ON ROOF STRUCTURE ABOVE CEILING AND INTERLOCK WITH FAN. AIR WILL BE DISTRIBUTED BACK OUT INTO SPACE BELOW CEILING AT NEAREST 24/12 RETURN FILTER GRILL (DIFFUSER G3). REFERENCE DETAIL "P", SHEET M3.3.
 - (H15) SEE SHEET M1.2 FOR CONTINUATION.
 - (H16) THERMOSTAT FOR NOTED IN-LINE EXHAUST FAN. MOUNT THERMOSTAT ABOVE CEILING AND ON EXTERIOR WALL WITH A MICARTA BASE. PLACE CEILING TAB ON NEAREST CEILING T-BAR TO MARK LOCATION OF THERMOSTAT.
 - (H17) ROUTE DUCT AS LOW AS POSSIBLE ABOVE LOW CEILING.
 - (H18) COORDINATE THE EXACT MOUNTING HEIGHT AND LOCATION OF THE ELECTRIC UNIT HEATER WITH THE ARCHITECT PRIOR TO ROUGH-IN. PROVIDE ALL MOUNTING HARDWARE REQUIRED. INSTALLATION SHALL BE AS REQUIRED BY THE MANUFACTURER'S INSTALLATION INSTRUCTIONS AND IN ACCORDANCE WITH ALL APPLICABLE BUILDING CODES.
 - (H19) MOUNT SMOKE DETECTOR ABOVE CEILING. INTERLOCK WITH EXISTING FIRE ALARM SYSTEM. SHUT DOWN IN-LINE EXHAUST FANS FOR FREEZE PROTECTION WHEN SMOKE IS DETECTED IN CEILING SPACE.

PARTIAL FIRST FLOOR PLAN - HVAC
 SCALE: 1/8" = 1'-0"

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.



PARTIAL FIRST FLOOR PLAN - HVAC

SCALE: 1/8" = 1'-0"

HVAC NOTES:


- (H1) --- EXISTING TO REMAIN
- (H2) COORDINATE THE EXACT LOCATION OF THERMOSTAT/CONTROL AND MOUNTING REQUIREMENTS WITH THE OWNER PRIOR TO MATERIAL ORDER ROUGH-IN AND INSTALLATION.
- (H3) THERMOSTAT FOR IN-LINE EXHAUST FAN. MOUNT THERMOSTAT ABOVE CEILING AND ON EXTERIOR WALL WITH A MICARTA BASE. PLACE CEILING TAB ON NEAREST CEILING T-BAR TO MARK LOCATION OF THERMOSTAT.
- (H4) PACKAGED DEHUMIDIFIER - SANTA FE OASIS 105 MODEL 4041850, 13.2 GALLON WATER REMOVAL AT 80°F & 60% RH, 280 CFM ADJUSTABLE BLOWER AT UP TO 1.0" WG, MERV-13 FILTERS, 45 dBA AVERAGE SOUND LEVEL, 115V/1Ø 5.0A, 9' CORD WITH TYPE B GROUNDED PLUG, 3/4" THREADED FEMALE NPT WITH 8' DIRECT GRAVITY DRAIN HOSE, R410A REFRIGERANT. SYSTEM SHALL INCLUDE ON-BOARD DIGITAL CONTROLS, AUTO-RESTART, VARIABLE SPEED DIRECT DRIVE FAN, DEW POINT TEMPERATURE CUT-OUT, ECCO CORROSION RESISTANT COIL, INTEGRATED SECONDARY DRAIN PAN WITH DEDICATED FLOAT SWITCH PORT AND MOLDED BASE WITH INTEGRATED HANDLES. INSTALL AND CONNECT IN STRICT ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS, MAINTAINING ALL REQUIRED AIRFLOW AND ACCESS CLEARANCES. PROVIDE MANUFACTURER'S CONDENSATE PUMP; PROVIDE LITTLE GIANT OR EQUAL CONDENSATE PUMP AS REQUIRED IF EXISTING CONDITION DICTATE GREATER LIFE IS REQUIRED. MOUNT HIGH ON WALL BELOW CEILING. COORDINATE THE EXACT LOCATION AND MOUNTING REQUIREMENTS WITH THE ARCHITECT PRIOR TO INSTALLATION. EXTEND FULL SIZE PUMPED CONDENSATE DRAIN PIPING AND TERMINATE OPEN-SIGHT AT HUB DRAIN ABOVE CEILING AT EWC. RE: PLUMBING PLANS.
- (H5) EXHAUST DUCT UP TO EXHAUST HOOD ON ROOF EQUAL TO GREENHECK GRSR WITH BIRDSCREEN AND FACTORY CURB. PAINT CURB AS DIRECTED BY ARCHITECT.
- (H6) INTERLOCK EXHAUST FAN WITH ROOM LIGHT SWITCH. RE: ELECTRICAL.
- (H7) PROVIDE INTERNALLY LINED SUPPLY AND RETURN DUCT FULL SIZE OF RTU OPENINGS. OFFSET IN CURB AND STRUCTURE AS REQUIRED AND TRANSITION TO DUCT SIZE INDICATED ON DRAWING.
- (H8) EXISTING DUCTWORK AND AIR DIFFUSER LOCATIONS TO REMAIN. FIELD VERIFY EXACT LOCATION. REFER TO SHEET MD.1 FOR APPROXIMATE APPLICABLE ZONE.
- (H9) ADJUSTABLE SPLITTER TEE WITH DOUBLE-THICKNESS TURNING VANES AND MANUAL VOLUME CONTROL DAMPER; SPLIT RATIO AS NOTED. TRANSITION OFF EACH SPLIT TO DUCT SIZE NOTED.

- (H9) ALL DUCT PENETRATING THIS WALL AND SERVING THE AREA WITH LOWER, 9FT CEILING MUST DROP TO RIGHT ABOVE THE CEILING BEFORE PENETRATING THE WALL. REFER TO ARCHITECTURAL PLANS FOR AREAS WITH 9FT CEILING ALONG THIS WALL.
- (H10) IN-LINE EXHAUST FAN FOR FREEZE PROTECTION OF CEILING SPACE. PLACE THERMOSTAT ON ROOF STRUCTURE ABOVE CEILING AND INTERLOCK WITH FAN. AIR WILL BE DISTRIBUTED BACK INTO SPACE BELOW CEILING AT NEAREST 24/12 RETURN FILTER GRILLE (DIFFUSER G3). REFERENCE DETAIL "P", SHEET M3.3.
- (H11) ACUTHERM THERMAFUSER TF-HC THERMALLY POWERED VARIABLE AIR VOLUME DIFFUSER WITH INDIVIDUAL HEATING AND COOLING THERMAL ELEMENTS (NO SUBSTITUTIONS; SF-HC EQUIVALENT ARE NOT ACCEPTABLE); AIRFLOW AS NOTED; 12" NECK UNLESS NOTED OTHERWISE. ADJUST COOLING ELEMENT FOR 72°F AND HEATING ELEMENT FOR 70°F.
- (H12) PROVIDE DRAINABLE BLADE LOUVER EQUAL TO RUSKIN ELF6375DX, EXTRUDED ALUMINUM, MILL FINISH, FRONT BLADE STATIONARY, DRAINABLE, 0.081" THICK. PROVIDE BIRDSCREEN, BLADE AND JAMB SEALS, CLIP ANGLES AND EXTENDED SILL. FACTORY APPLIED KYNAR FINISH TO MATCH PAINT CHIP (FURNISHED BY OWNER/ARCHITECT). COORDINATE EXACT ELEVATION WITH ARCHITECT. TRANSITION ASSOCIATED OUTSIDE AIR DUCT FULL SIZE OF LOUVER. LOUVER SIZE AS INDICATED. SLOPE BOTTOM OF DUCT AT LOUVER DOWN SO THAT ANY WATER ENTRAINMENT DRAINS OUT OF THE BUILDING.
- (H13) MOUNT SMOKE DETECTOR ABOVE CEILING. INTERLOCK WITH FIRE ALARM SYSTEM. SHUT DOWN IN-LINE EXHAUST FANS FOR FREEZE PROTECTION WHEN SMOKE IS DETECTED IN CEILING SPACE.
- (H14) WALL MOUNT MINI-SPLIT FAN COIL UNIT ON WALL AT APPROXIMATELY 7"-6" AFF TO BOTTOM, INSTALL IN STRICT ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS. EXTEND 3/4" TYPE "L" COPPER TUBING FROM INTEGRAL CONDENSATE PUMP, ALONG WALL AND RISE TO ABOVE CEILING; TERMINATE OPEN-SIGHT AT HUB DRAIN ABOVE CEILING AT EWC. RE: PLUMBING PLANS. INSTALL REFRIGERANT PIPING AND CONDENSATE PIPING ENCLOSED IN PAINTED RIGID METAL CONDUIT. CORE-DRILL, SLEEVE AND SEAL CMU BLOCK WALLS AS REQUIRED FOR PIPING INSTALLATION; MAXIMUM PENETRATION SIZE ALLOWED IS 2 1/2" DIAMETER.


- (H15) MINI-SPLIT 2x2 ROUND-FLOW CEILING CASSETTE FAN COIL UNIT; UNIT DESIGNATION AS NOTED. PROVIDE FRAMED CEILING OPENING WITH FULL PERIMETER SUPPORT FRAME SECURED TO LAY-IN CEILING GRID AND INDEPENDENTLY SUPPORTED FROM ROOF STRUCTURE/FRAMING ABOVE. INSTALL FCU IN STRICT ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS. COORDINATE REQUIRED CEILING OPENING AND FRAMING WITH GENERAL CONTRACTOR AND CEILING SUB-CONTRACTOR. EXTEND 3/4" TYPE "L" HARD COPPER CONDENSATE DRAIN PIPING FROM INTEGRAL CONDENSATE PUMP, ABOVE LAY-IN CEILING; EXPOSED TUBING/PIPING IS NOT ACCEPTABLE.
- (H16) PROVIDE CONCENTRIC DIFFUSER SYSTEM EQUAL TO RUSKIN 510, ANODIZED ALUMINUM DIFFUSER FRAME, ALUMINUM RETURN AIR EGG CRATE, ANTI-SWEAT GASKET, MOLDED FIBERGLASS CORE, INSULATED SHEET METAL DIFFUSER BOX, 4-WAY DISTRIBUTION, FULLY INSULATED. EXTEND SUPPLY AND RETURN DUCTS DOWN FROM THE UNIT, FULL SIZE OF UNIT OPENING, AND TRANSITION AND CONNECT TO CONCENTRIC DIFFUSER SYSTEM CONNECTIONS. BALANCE TO 750 CFM THRU CONCENTRIC DIFFUSER; 400 CFM SHALL BE SUPPLIED TO MEETING ROOM.
- (H17) SEE SHEET M1.1 FOR CONTINUATION.
- (H18) PROVIDE 20/20 TYPE "G4" GRILLE BELOW DOOR FOR UNIT RETURN.

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.


- HVAC NOTES:**
- (H1) COORDINATE THE EXACT LOCATION OF THERMOSTAT WITH THE ARCHITECT PRIOR TO ROUGH-IN.
 - (H2) PROVIDE FIRE DAMPERS AS REQUIRED FOR ALL DUCT PENETRATIONS OF THE MECHANICAL DUCT CHASE. RE: ARCHITECTURAL DRAWINGS FOR RATED WALLS/FLOORS.
 - (H3) PROVIDE FLEXIBLE DUCT CONNECTIONS AT EFs AND AHUs.
 - (H4) EXHAUST/OUTSIDE AIR DUCT UP TO HOOD ON ROOF EQUAL TO GREENHECK GRSR/L, THROAT SIZE TO MATCH DUCT SIZE INDICATED ON DRAWING. PROVIDE FACTORY CURB AND BIRDSCREEN. PAINT CURB AS DIRECTED BY THE ARCHITECT.
 - (H5) INTERLOCK EXHAUST FAN WITH ROOM LIGHT SWITCH. RE: ELECTRICAL.
 - (H6) ALL FLEX DUCT MUST BE ROUTED THROUGH WEB OF BAR JOISTS. S/A AND R/A DUCT TRUNKS MUST BE BETWEEN BAR JOISTS AND CLOSE TO ROOF DECK
 - (H7) PROVIDE MANUFACTURER'S RECOMMENDED ROOF MOUNTED COMBINATION COMBUSTION AIR/FLUE CAP FOR FURNACE UNIT. PROVIDE MANUFACTURER'S RECOMMENDED DUCT SIZE FROM UNIT FLUE AND COMBUSTION AIR CONNECTION TO MANUFACTURER'S COMBINATION ROOF CAP. VENT PIPE MATERIAL SHALL BE POLYPROPYLENE AND THE INSTALLATION SHALL BE COMPLIANT WITH THE MECHANICAL/GAS CODE AND WITH THE MANUFACTURER'S INSTALLATION INSTRUCTIONS.
 - (H8) REFERENCE PLUMBING PLANS FOR TYPE "L" HARD COPPER CONDENSATE DRAIN PIPING.
 - (H9) PROVIDE CEILING-MOUNTED FAN-FORCED HEATER EQUAL TO QMARK EFF1500, 1500 WATTS, WITH WALL MOUNTED THERMOSTAT.
 - (H10) EXTEND R/A DUCT DOWN IN CHASE AND CONNECT TO TOP OF TOF 14/12 R/A DUCT.
 - (H11) EXTEND 10/8 R/A DUCT INTO CHASE, THEN TURN UP AND CONNECT TO BOTTOM OF 14/12 R/A DUCT.
 - (H12) PROVIDE TYPE "G4" GRILLE MOUNTED WITH BOTTOM OF GRILLE AT 12" AFF. SIZE AS INDICATED ON DRAWING.
 - (H13) MOUNT NEW RTU-5 ON EXISTING ROOF CURB. PROVIDE CURB ADAPTER AS REQUIRED. CONNECT TO EXISTING PIPING AND POWER RETAINED FROM DEMOLITION.
 - (H14) EXTEND OUTSIDE/RETURN AIR DOWN AND CONNECT TO RETURN AIR PLENUM.



PARTIAL SECOND FLOOR PLAN - HVAC
 SCALE: 1/8" = 1'-0"




PARTIAL SECOND FLOOR PLAN - HVAC
 SCALE: 1/8" = 1'-0"




(A) DETAIL - GYP. BOARD LINED PLENUM (METAL STUD CONSTRUCTION)
 NO SCALE


THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.



A **DETAIL – ELECTRIC UNIT HEATER**
NO SCALE



B **DETAIL – AIR HANDLING UNIT
CONDENSATE DRAIN CONNECTION**
NO SCALE
P₁ UNIT INTERNAL STATIC PRESSURE +1"
(INCLUDING DIRTY FILTERS)



C **DETAIL – EXHAUST FAN (IN-LINE)**
NO SCALE

HVAC GENERAL NOTES:

- ALL DUCTWORK SIZES SHOWN ARE INSIDE FREE AREA DIMENSIONS.
- ALL AIR DEVICES SHALL BE INDEPENDENTLY SUPPORTED FROM STRUCTURE ABOVE WITH CEILING TIE WIRES AND CONCEALED FASTENERS.
- PROVIDE NECESSARY OFFSETS TO MAINTAIN MINIMUM 15'-0" DISTANCE BETWEEN OUTSIDE AIR INTAKES AND PLUMBING VENTS, AND EXHAUST AIR OUTLETS. VERIFY EXACT LOCATIONS WITH ARCHITECT AND ENGINEER PRIOR TO MATERIAL ORDER AND INSTALLATION.
- PROVIDE FLEXIBLE DUCT CONNECTIONS AT ALL ROOFTOP UNITS (RTU), HORIZONTAL AND VERTICAL FURNACE AIR HANDLING UNITS (FAHU), AND EXHAUST FANS (EF).
- ALL DUCTWORK AND EQUIPMENT SHALL BE INSTALLED AT HIGHEST ELEVATION ACHIEVABLE (TYP). COORDINATE DUCT ROUTING WITH NEW AND EXISTING STRUCTURE, X-BRACING, FRAME WALL BRACING, LIGHT FIXTURES, ETC.
- ALL FLEXIBLE DUCT SHALL BE FULLY EXTENDED, FREE OF KINKS, NO LONGER THAN 5'-0" AND SAME SIZE AS DIFFUSER NECK. BRANCH DUCTS AND TAKE-OFFS SHALL BE THE SIZE SAME AS DIFFUSER NECKS UNLESS SPECIFICALLY NOTED OTHERWISE. PROVIDE RECTANGULAR TO ROUND TRANSITIONS OR ADAPTORS AT DIFFUSER NECKS WHERE REQUIRED BY SPECIFIC AIR DEVICE MANUFACTURER. SQUARE NECK SIZE WITH ROUND ADAPTER SHALL BE SELECTED FOR AN NC LEVEL OF 25 OR LESS AT DESIGN AIRFLOW.
- THIS CONTRACTOR SHALL PROVIDE HVAC SYSTEMS IN STRICT ACCORDANCE WITH APPLICABLE EDITIONS OF NFPA 101 AND NFPA 90A.
- CONTRACTOR SHALL FIELD VERIFY EXACT SIZE, LOCATION, ETC. OF STRUCTURAL FRAMING PRIOR TO UNIT AND DUCT INSTALLATION, MATERIAL ORDER AND DUCTWORK FABRICATION. NOTIFY ARCHITECT/ENGINEER IMMEDIATELY OF SIGNIFICANT DISCREPANCIES AND CONFLICTS.
- THE INSIDE OF ALL BRANCH DUCTS AND DUCT DROPS TO GRILLES AND DIFFUSERS SHALL BE PAINTED WITH TWO COATS OF FLAT BLACK ENAMEL PAINT SUCH THAT NO "RAW" GALVANIZED STEEL FINISH IS VISIBLE THROUGH THE AIR DEVICE FACE.
- ALL RECTANGULAR DUCT ELBOWS AND SPLITTER TEES SHALL INCLUDE DOUBLE THICKNESS TURNING VANES, ANCHORED TO DUCT PER SMACNA GUIDELINES.
- PROVIDE FULL SIZE INTERNALLY LINED DUCT DROPS TO ALL RETURN AIR GRILLES AND EXHAUST GRILLES. PREP, PRIME AND PAINT ALL EXPOSED INTERIOR SURFACES FLAT BLACK.
- CONDENSATE DRAIN PIPING SHALL BE TYPE "L" HARD COPPER WITH COPPER DWV TEE FITTINGS AND THREADED CAPS (FOR CLEANOUT) AT ALL CHANGES OF DIRECTION AND AT END OF RUNS. PIPING SHALL BE TERMINATED OPEN-SIGHT AT HUB-DRAINS WITH ELONGATED FUNNELS AS INDICATED AND/OR NOTED ON PLAN. PROVIDE REDUCERS AND UNIONS AT CONNECTIONS TO EQUIPMENT. PROVIDE PPH OR ERICO/CADDY PIPE SUPPORTS AS DETAILED.
- MANUAL VOLUME DAMPERS ABOVE RIGID INACCESSIBLE CEILINGS SHALL BE ALUMINUM YOUNG MODEL 820-1200 (RECTANGULAR) AND 5020-1200 (ROUND) OPPOSED BLADE WITH WORM GEAR SELF-LOCKING REGULATOR, FS FLEX SHAFT AND 301-FS CUP CONNECTOR WITH PRIMED COVER PLATES. (PAINT TO MATCH ADJACENT CEILING FINISHES). COORDINATE EXACT CEILING TYPE IN EACH AREA WITH ARCHITECTURAL REFLECTED CEILING PLAN.
- CONTRACTOR SHALL INSTALL ALL CEILING EXHAUST FANS, CEILING CASSETTE FAN-COIL UNITS, ZONE HEAT RECOVERY BRANCH SELECTOR BOXES, AND HORIZONTAL AIR HANDLING UNITS WITH ASSOCIATED DUCTWORK, PIPING AND ACCESSORIES ABOVE CEILING, SUCH THAT A MINIMUM OF 48" CLEAR SPACE IS AVAILABLE FOR SERVICE, CLEANING, FILTER CHANGES AND ROUTINE MAINTENANCE.
- COORDINATE EXACT LOCATIONS OF CEILING AIR DEVICES WITH ARCHITECTURAL REFLECTED CEILING PLANS. AIR DEVICES SMALLER THAN FULL GRID SPACING SHALL BE CENTERED IN TILES AND INSTALLED WITH SURFACE MOUNT FRAMES AND CONCEALED FASTENERS.
- ALL EXPOSED DUCTWORK SHALL BE SPIRAL-SEAM DOUBLE-WALL WITH "PAINT-GRIP" GALVANIZED STEEL OUTER WALL, PERFORATED INNER WALL AND FACTORY LINED (1" THICK LINER). PAINT DUCT SUPPORTS, ETC TO MATCH ADJACENT BUILDING FINISHES AND STRUCTURE WITH MINIMUM (2) COATS PRIMER AND (2) FINISH COATS OIL-BASED ENAMEL PAINT. SILVER UNLESS DIRECTED OTHERWISE BY ARCHITECT.
- ALL RECTANGULAR RETURN, SUPPLY AND OUTSIDE AIR DUCTWORK SHALL BE INTERNALLY LINED WITH MINIMUM 1" THICK ACOUSTIC DUCT LINER. ALL CONCEALED RIGID ROUND DUCT SHALL BE WRAPPED WITH MINIMUM 2" THICK DUCT THREE QUARTER POUND DENSITY DUCT WRAP AS SPECIFIED. ALL SUPPLY AIR DUCTWORK SHALL BE EXTERNALLY WRAPPED IN ADDITION TO INTERNALLY-LINED.
- ALL FLEXIBLE DUCT ABOVE CEILINGS 9'-0" AFF AND HIGHER, SHALL BE SECURED TO BRANCH DUCTS AND AIR DEVICES WITH STAINLESS STEEL WORM SCREW DUCT CLAMPS; SET CLAMP SCREW DRIVES WITH BLUE LOCITITE AFTER TIGHTENING TO PROPER TORQUE.

MINI-SPLIT HEAT PUMP SYSTEM SCHEDULE

INDOOR UNIT				
MARK		MS-1	MS-2	
LOCATION		OUTDOOR SPACE 154	CLIMATE CNTRL STORAGE 172	
TYPE		CLG RECESSED	WALL-MOUNT	
FAN				
AIRFLOW				
COOLING	CFM	275-448	395-754	
TOTAL CAPACITY	MBH	20	24	
HEATING	CFM	275-448	395-754	
TOTAL CAPACITY	MBH	18	27.3	
ELECTRICAL INDOOR UNIT				
MANUFACTURER		NOTES 1,2 "DAIKIN"	NOTES 1,2 "DAIKIN"	
MODEL NO		FFQ18Q2VJU	FTXC24AXVJU	
OUTDOOR UNIT				
MARK		MSHP-1	MSHP-1	
LOCATION		ROOF	ROOF	
NOMINAL CAPACITY	TON	1.5	2	
REFRIGERANT		R-32	R-32	
ELECTRICAL OUTDOOR UNIT				
VOLTS/PHASE		208/1	208/1	
MCA	AMP	16.4	16.4	
OCPD	AMP	20	20	
MANUFACTURER		"DAIKIN"	"DAIKIN"	
MODEL NO		RXC18AXVJU	RXC24AXVJU	
REMARKS		1,2,3,4	1,2,3,4	


THE MECHANICAL CONTRACTOR SHALL COORDINATE THE EXACT VOLTAGE & PHASE OF EACH AND EVERY EQUIPMENT ITEM WITH THE ELECTRICAL CONTRACTOR, PRIOR TO ORDER.

- NOTES:
- INDOOR UNIT ELECTRICALLY FED FROM OUTDOOR UNIT.
 - WALL MOUNTED UNIT. COORDINATE EXACT MOUNTING LOCATION WITH ARCHITECT PRIOR TO INSTALLATION.
 - MANUFACTURER PROVIDED CONDENSATE PUMP.
 - PROVIDE LOW AMBIENT KITS.

OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA



LAND 3
ARCHITECT, INC.
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA
71201-5786
EMA
ENGINEERING
SOLUTIONS
1000 PINEAPPLE BLVD SUITE 100
MONROE, LA 71201
504-488-4000
www.ema-la.com



DRAWN BY: JDK
CHK'D BY: TGS
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED

HVAC
DETAILS

M3.3

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.

AIR DISTRIBUTION DEVICE SCHEDULE						
TYPE	DESCRIPTION	MOUNTING	MANUFACTURER CATALOG NO.	MATERIAL	FINISH	ACCESSORIES/REMARKS
D1	CEILING SUPPLY DIFFUSER	CEILING LAY-IN	TITUS TMS	ALUMINUM	BAKED WHITE ENAMEL	24/24 FULLY LOUVERED FACE; NECK SIZE AS INDICATED
D2	CEILING SUPPLY DIFFUSER	CEILING LAY-IN	TITUS TMS	ALUMINUM	BAKED WHITE ENAMEL	12/12 FULLY LOUVERED FACE; NECK SIZE AS INDICATED
D3	SIDEWALL SUPPLY GRILLE	SURFACE SIDEWALL	TITUS 300FL	ALUMINUM	BAKED WHITE ENAMEL	DOUBLE DEFLECTION; 1/2" BLADE SPACING; SIZE AS INDICATED
G1	CEILING RETURN/EXHAUST	CEILING LAY-IN	TITUS 50FF	ALUMINUM	BAKED WHITE ENAMEL	24/24 PANEL; 1/2" x 1/2" x 1/2" EGG CRATE CORE; 1" FILTER FRAME; OBD
G2	CEILING RETURN/EXHAUST GRILLE	CEILING LAY-IN	TITUS 50FF	ALUMINUM	BAKED WHITE ENAMEL	12/12 PANEL; 1/2" x 1/2" x 1/2" EGG CRATE CORE; 1" FILTER FRAME; OBD
G3	CEILING FILTER RETURN GRILLE	CEILING LAY-IN	TITUS 50FF	ALUMINUM	BAKED WHITE ENAMEL	24/12 PANEL; 1/2" x 1/2" x 1/2" EGG CRATE CORE; 1" FILTER FRAME; OBD
G4	CEILING FILTER RETURN GRILLE	WALL SURFACE	TITUS 350FL	ALUMINUM	BAKED WHITE ENAMEL	24/12 PANEL; 1/2" x 1/2" x 1/2" EGG CRATE CORE; 1" FILTER FRAME; OBD

NOTE: COORDINATE EXACT CEILING/WALL TYPE AND MOUNTING REQUIREMENTS WITH ARCHITECTURAL PLANS.

AIR PURIFICATION SCHEDULE					
TAG	S/A FLOW	EQUAL TO GPS MODEL	GPS QUANTITY	VOLTAGE	MOUNTING LOCATION
-	0-2400	FC-24	1	24VAC	SUPPLY FAN
-	2401-4800	FC-48	1	24VAC	SUPPLY FAN
-	4801-9600	FC-48	2	24VAC	SUPPLY FAN

NOTES:

- BASIS OF DESIGN IS GLOBAL PLASMA SOLUTIONS. APPROVED EQUALS BY PHENOMENAL AIRE, AIRGENICS AND BIOXGEN SUBJECT TO SPECIFICATION.
- MOUNT BI-POLAR ION GENERATOR WHERE INDICATED ON SCHEDULE.
- IF CONTRACTOR SUBSTITUTES BASIS OF DESIGN WITH ANOTHER MANUFACTURER, CONTRACTOR SHALL COORDINATE ALL ELECTRICAL.
- BI-POLAR IONIZATION SYSTEMS REQUIRING PERISHABLE GLASS TUBES ARE NOT ACCEPTABLE.
- ALL MANUFACTURERS MUST PASS UL-867-2007 OZONE CHAMBER TESTING BY EITHER UL OR ETL.
- PROVIDE IN ALL NEW FAHUs AND RTUs.

FAN SCHEDULE										
FAN NO.	SERVES MOUNT	CFM	EXT. S.P.	RPM	H.P. (WATTS)	VOLTS PHASE	EQUAL TO MFG./PART NO.	SONES	DRIVE	REMARKS
1,2	TLTS CLG	120	0.5"	1225	(32)	115/1	GREENHECK SP-A390-VG	1.4	DIRECT	PROVIDE W/DISCONNECT, BACKDRAFT DAMPER, WHITE CEILING GRILLE, FAN MOTOR MOUNTED SPEED CONTROLLER
3 THRU 9	JAN/TLTS CLG	80	0.3"	1470	(80)	115/1	GREENHECK SP-B110	1.1	DIRECT	PROVIDE WITH BACKDRAFT DAMPER; ISOLATION KIT; CEILING GRILLE; DISCONNECT; SPEED CONTROLLER
10,11,19,20	MEETING ROOMS 118,119,180 IN-LINE CLG	950	1.0"	1310	(321)	115/1	GREENHECK CSP-A1300	4.6	DIRECT	PROVIDE WITH BACKDRAFT DAMPER; ISOLATION KIT; DISCONNECT; SPEED CONTROLLER
12,13,16,17	YOUNG ADULT'S AND CHILDREN IN-LINE CLG	1000	1.0"	1310	(321)	115/1	GREENHECK CSP-A1300	4.6	DIRECT	PROVIDE WITH BACKDRAFT DAMPER; ISOLATION KIT; DISCONNECT; SPEED CONTROLLER
14,15	CORRIDOR 148 AND ROOM 156 IN-LINE CLG	825	1.14"	1310	(321)	115/1	GREENHECK CSP-A1300	4.5	DIRECT	PROVIDE WITH BACKDRAFT DAMPER; ISOLATION KIT; DISCONNECT; SPEED CONTROLLER
18,21	BOOK DROP AND OFFICES 165 IN-LINE CLG	600	1.0"	1070	(186)	115/1	GREENHECK CSP-A1050	3.9	DIRECT	PROVIDE WITH BACKDRAFT DAMPER; ISOLATION KIT; DISCONNECT; SPEED CONTROLLER
VF-1	COVERED OUTDOOR SPACE 154 SUSPENDED	24,758	-	143 (MAX)	137.24 (MAX)	120/1	HUNTER COMMERCIAL MODEL TRAK 76286	<54 dBA	DIRECT	8 FT. DIAMETER; 4 AIRFOILS WITH CLEAR ANODIZED FINISH; GEARLESS DIRECT DRIVE EC MOTOR; WIRED WALL CONTROL WITH DIGITAL DISPLAY AND TOUCHSCREEN; EXTENDED TUBE MOUNT ; 2 YEAR WARRANTY (MINIMUM); MATTE BLACK MOTOR WITH BLACK TRIM
22	TOILET CEILING	480	0.5"	1346	(145)	115/1	GREENHECK CSP-A510-VG	1.3	DIRECT	PROVIDE WITH BACKDRAFT DAMPER; ISOLATION KIT; CEILING GRILLE; DISCONNECT; SPEED CONTROLLER
23	TOILET CEILING	240	0.5"	1273	(49)	115/1	GREENHECK CSP-A390-VG	1.5	DIRECT	PROVIDE WITH BACKDRAFT DAMPER; ISOLATION KIT; CEILING GRILLE; DISCONNECT; SPEED CONTROLLER

THE MECHANICAL CONTRACTOR SHALL COORDINATE THE EXACT VOLTAGE & PHASE OF EACH AND EVERY EQUIPMENT ITEM WITH THE ELECTRICAL CONTRACTOR, PRIOR TO ORDER.

NOTE: REFERENCE PLANS FOR EXACT QUANTITIES.

ROOFTOP UNIT SCHEDULE																
RTU NO.	EVAPORATOR DATA						HEAT EXCHANGER DATA				OUTSIDE AIR CFM	OUTSIDE AIR TEMP	EER (EER2)	POWER SUPPLY	EST WEIGHT (LBS)	LENNOX MODEL NO.
	CFM	FAN H.P.	EXT. S.P.	E.A.T. (DB/WB)	L.A.T. (DB/WB)	TOT. CAP. (MBH)	SENS. CAP. (MBH)	INFLT (MBH)	OUTFLT (MBH)							
1	1850	1	0.5	78.1/64.4	52.6/52.6	57.7	46.0	65/53	52/43	300	100	(12.5)	208/3	778	LGT060H5E	
2	2900	3.75	0.7	77.9/64.3	56.5/54.1	84.9	64.4	130/84	104/67	430	100	12.3	208/3	1264	LGT092H5E	
3	6700	5.0	1.2	77.7/64.2	56.2/54.2	213.1	162.8	260/85	211/69	1000	100	12	208/3	2806	LGT210H5M	
4	1150	0.5	0.5	78.4/64.6	55.6/54.2	34.2	27.3	65/53	52/43	200	100	(13.5)	208/3	800	LGT036H5E	
5	1540	1	.06	76.8/63.7	57.1/53.9	45.2	35.2	65/53	52/43	230	100	(13)	208/3	800	LGT048H5E	

NOTES:

- PROVIDE 5-YEAR COMPRESSOR PARTS WARRANTY; INCLUDING REFRIGERANT, PARTS & LABOR - NON PRORATED; 10 YEAR HEAT EXCHANGER WARRANTY.
- PROVIDE WITH FULLY PROGRAMMABLE THERMOSTAT WITH 2-STAGE HEATING AND 2-STAGE COOLING AND AUTOMATIC COOLING/HEATING CHANGEOVER.
- ALL COMPONENTS OF EACH HVAC SYSTEM SHALL BE PRODUCTS OF THE SAME MANUFACTURER, AND SHALL BE PERFORMANCE MATCHED WITH PUBLISHED PERFORMANCE RATINGS. HVAC SYSTEMS WITH COMPONENTS FROM DIFFERENT MANUFACTURERS, EVEN SUBSIDIARIES OF THE SAME COMPANY, WILL NOT BE ACCEPTED.
- PROVIDE LOW AMBIENT CONTROL, CONDENSER HAIL GUARD, HINGED ACCESS PANELS.
- PROVIDE TWO (2) COMPLETE SETS OF 2" MERV 8 FILTERS FOR EACH RTU.
- UNITS SHALL BE TWO-STAGE WITH MULTI-SPEED FAN CONTROL TO ADJUST FAN SPEED TO NOT MORE THAN 65% OF FULL AIRFLOW BASED ON ACTIVE COMPRESSOR STAGES.
- SCHEDULED COOLING CAPACITIES ARE NET.
- PROVIDE LOW VOLTAGE AND SINGLE PHASE PROTECTION; PROVIDE HEAVY DUTY DISCONNECT SWITCHES--SEE ELECTRICAL PLANS FOR SIZE AND TYPE.
- PROVIDE FACTORY FABRICATED 14" TALL STRUCTURAL INSULATED ROOF CURBS. ROOF CURB BOTTOMS SHALL MATCH PITCH OF ROOF AND UNIT SHALL BE LEVEL.

OUTDOOR DESIGN CONDITIONS
SUMMER: 100DB/78WB
WINTER: 20"

HIGH-EFFICIENCY 2-STAGE AIR CONDITIONING UNIT SCHEDULE (FAHU)														
FUR/CU No.	BLOWER DATA				COOLING DATA*				HEATING DATA*		COND. DATA		OUTSIDE AIR (CFM)	LENNOX MODEL EQUAL TO
	CFM	EXT. S.P.	HP	VOLTS/Ø	TOTAL MBH	SENS MBH	EAT (DB/WB)	LAT (DB/WB)	INPUT HI/LOW	OUTPUT HI/LOW	VOLTS/Ø	SEER		
1,4	1150	0.6"	1/2	115/1	33.7	28.6	79.0/65.0	54.0/54.0	44/29	42/28	208/3	16.5	200	ML296UH045XV36B FURNACE CX35-36B-6F-20 COIL ML18XC2-036-233 CONDENSING UNIT
3	1560	0.6"	3/4	115/1	45.4	38.0	78.4/64.6	53.5/53.5	88/57	84/55	208/3	16.0	230	ML296UH090XV48C FURNACE CX35-49C-6F-20 COIL SSB048H4543Y CONDENSING UNIT
2	780	0.5"	1/2	115/1	21.1	17.3	77.8/64.2	54.9/54.2	44/29	42/28	208/1	15.5	150	ML296UH045XV36B FURNACE CX35-18/24B-6F-20 COIL ML18XC2-024-230 CONDENSING UNIT

THE MECHANICAL CONTRACTOR SHALL COORDINATE THE EXACT VOLTAGE & PHASE OF EACH AND EVERY EQUIPMENT ITEM WITH THE ELECTRICAL CONTRACTOR, PRIOR TO ORDER.

DESIGN CONDITIONS: SUMMER - 99F/77F, WINTER - 20F

- HEATING DATA TAKEN AT ARI CONDITIONS (LOW 70/17 AND HIGH 70/47)
- EXTERNAL STATIC PRESSURE DOES NOT INCLUDE FILTER, HEATER, WET COIL, AND ANY OTHER PRESSURE DROPS INTERNAL TO THE UNIT.
- PROVIDE SINGLE POINT POWER CONNECTION WITH AUTO TRANSFORMER TO BLOWER MOTOR.
- MULTISTAGE AIR VOLUME CONTROL.
- MINIMUM TWO(2) STAGE COOLING AND TWO(2) STAGE HEATING.
- PROVIDE & INSTALL DEHUMIDIFICATION SYSTEM AND PIPING KIT.
- PROVIDE 5 YEAR COMPRESSOR WARRANTY, INCLUDING REFRIGERANT, PARTS AND LABOR-NON PRORATED; 20 YEAR HEAT EXCHANGER WARRANTY.
- TOUCHSCREEN, 7-DAY PROGRAMMABLE THERMOSTAT.

EXISTING SYSTEMS BALANCE SCHEDULE			
TAG	S/A	R/A	O/A
ERTU-1	3900	3310	590
ERTU-2	3900	3310	590
ERTU-3	3820	3230	590
ERTU-4	3900	3310	590
ERTU-5	3900	3310	590
ERTU-6	3900	3310	590
EAHU-1	1900	1600	300

NOTE: THE CONTRACTOR SHALL THOROUGHLY CLEAN AND SERVICE EXISTING ROOFTOP UNITS AND AHUs, INCLUDING BUT NOT LIMITED TO CLEANING OF COILS, BRUSHING AND COMBING COIL FINS, CHARGING REFRIGERANT, LUBRICATING ALL BEARINGS, REPLACING FILTERS, FAN BELTS, ETC. REBALANCE ROOFTOP UNITS AND FAHUs TO THE AIRFLOWS INDICATED IN THE SCHEDULE ABOVE.

ELECTRIC UNIT HEATER SCHEDULE									
EUH NO.	SERVES	CFM	FAN HP	ΔT	KW	STAGES	POWER SUPPLY	WEIGHT (LBS)	EQUAL TO
1	MECH. 112	350	1/100	45	5.0	2	208V/1Ø	27	QMARK MUH05-81


THE MECHANICAL CONTRACTOR SHALL COORDINATE THE EXACT VOLTAGE & PHASE OF EACH AND EVERY EQUIPMENT ITEM WITH THE ELECTRICAL CONTRACTOR, PRIOR TO ORDER.

- PROVIDE WALL MOUNTED THERMOSTAT WITH SUMMER FAN OPERATION. CONFIRM LOCATION WITH OWNER AND ARCHITECT.
- MOUNT UNIT HEATER PER MANUFACTURER'S INSTRUCTIONS.

MECHANICAL LEGEND	
SYMBOL	DESCRIPTION
	SUPPLY AIR DIFFUSER OR DUCT
	RETURN AIR GRILLE, REGISTER OR DUCT
	EXHAUST AIR GRILLE, REGISTER OR DUCT
	ADJUSTABLE SPLITTER TEE W/TURNING VANES (S/A ONLY)
	DUCT TRANSITION - CONCENTRIC, ECCENTRIC
	FLEXIBLE DUCT
	LINED DUCTWORK
	ELBOW W/DOUBLE THICKNESS VANES
	MANUAL VOLUME DAMPER
	THERMOSTAT
	NIGHT SETBACK THERMOSTAT
	OVERRIDE TIMER
	FIRE DAMPER - HORIZONTAL AIR FLOW
	FIRE DAMPER - VERTICAL AIR FLOW
	REFRIGERANT LIQUID
	REFRIGERANT SUCTION
	DRAIN LINE
	GAS LINE
	CONNECT TO EXISTING
	CONDENSING UNIT
	ABOVE FINISHED FLOOR
	UNDERGROUND
	ROOF DRAIN
	ROOF TOP UNIT
	OPPOSED BLADE DAMPER
	EXHAUST FAN
	MINI-SPLIT
	RADIANT HEATER
	ELECTRIC UNIT HEATER
	FURNACE AIR HANDLING UNIT
	AIR HANDLING UNIT
	MINI-SPLIT HEAT PUMP

NOTE: NOT ALL SYMBOLS USED.

OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA



LAND 3
ARCHITECT, INC.
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA
71201-5786




DRAWN BY: JDK
CHK'D BY: TGS
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED

HVAC
SCHEDULES


M3.1

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.


THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.




A DETAIL – DIFFUSER CONNECTION
 NO SCALE




B DETAIL – DUCT TAKE-OFFS
 NO SCALE




C DETAIL – CEILING MOUNTED EXHAUST FAN
 NO SCALE




D DETAIL – RETURN/EXHAUST GRILLE
 NO SCALE




E DETAIL – ROOFTOP UNIT PIPING
 (PACKAGED AIR HANDLING UNIT SIMILAR)
 NO SCALE





F DETAIL – TYPICAL ROOF TOP UNIT MOUNTING
 NO SCALE



G DETAIL – CONDENSING UNIT ON ROOF
 NO SCALE



H DETAIL – INTAKE/EXHAUST HOOD
 NO SCALE



FIRST FLOOR PLAN DEMOLITION - ELECTRICAL

SCALE: 1/16" = 1'-0"


ELECTRICAL DEMOLITION NOTES

—X—X—X EXISTING TO BE REMOVED
 ——— EXISTING TO REMAIN


- ED1 DISCONNECT AND REMOVE THE EXISTING F/A SYSTEM IN IT'S ENTIRETY.
- ED2 DISCONNECT AND REMOVE EXISTING SOFFIT LIGHTING FIXTURE AND CONDUCTORS/CONDUIT TO SOURCE.
- ED3 DISCONNECT AND REMOVE EXISTING LIGHTING FIXTURE AND RETAIN CIRCUIT FOR RE-USE.
- ED4 DISCONNECT AND REMOVE EXISTING EMERGENCY LIGHTING FIXTURE. RETAIN EXISTING CONDUCTORS FOR RE-USE.
- ED5 EXISTING RECEPTACLE TO REMAIN. PROTECT DURING DEMOLITION AND NEW CONSTRUCTION.
- ED6 DISCONNECT AND REMOVE EXISTING EXIT SIGN/EMERGENCY FIXTURE AND CONDUCTORS/CONDUIT TO SOURCE.
- ED7 DISCONNECT AND REMOVE EXISTING RECEPTACLE AND CONDUCTORS/CONDUIT TO SOURCE. WHERE RECEPTACLE IS BEING REMOVED FROM WALL THAT IS TO REMAIN, CONDUIT AND BACK BOX MAY REMAIN IN WALL. REMOVE CONDUCTORS TO SOURCE AND PATCH WALL AS DIRECTED BY THE ARCHITECT.
- ED8 DISCONNECT AND REMOVE EXISTING LIGHTING SWITCH.
- ED9 EXISTING CAMERAS AND ASSOCIATED CONDUCTORS/CONDUIT ARE TO REMAIN. PROTECT DURING DEMOLITION AND NEW CONSTRUCTION. WHERE DEMOLITION AND NEW CONSTRUCTION INDICATED ON ARCHITECTURAL DRAWINGS INTERRUPT EXISTING CAMERAS, THIS CONTRACTOR SHALL RELOCATE CAMERA AS DIRECTED BY THE ARCHITECT.
- ED10 CONTRACTOR SHALL REPAIR/REPLACE AND FEED THRU BRANCH CIRCUIT WIRING DAMAGED OR INTERRUPTED BY DEMOLITION.
- ED11 EXISTING 208Y/120V, 3φ, 4W, 1600A SWITCHBOARD TO REMAIN. PROTECT DURING DEMOLITION AND NEW CONSTRUCTION.
- ED12 EXISTING PANELBOARD TO REMAIN. PROTECT DURING DEMOLITION AND NEW CONSTRUCTION.
- ED13 PROVIDE ELECTRICAL DEMOLITION ASSOCIATED WITH MECHANICAL DEMOLITION. RE: MECHANICAL DEMOLITION PLANS.
- ED14 PROVIDE DEMOLITION OF POWER/DATA RECEPTACLES AND ANY OTHER ELECTRICAL DEVICES IN WALLS BEING DEMOLISHED WHETHER INDICATED ON THIS DRAWING OR NOT.
- ED15 EXISTING WALLPACK TO REMAIN. PROTECT DURING DEMOLITION AND NEW CONSTRUCTION.
- ED16 RETROFIT EXISTING SOFFIT LIGHT FIXTURE WITH LED EQUIVALENT LAMPS WITH EQUIVALENT LUMEN OUTPUT. COLOR TEMPERATURE SHALL BE 4000° K. RETAIN EXISTING CIRCUIT(S) FOR RE-USE. REFERENCE NEW WORK ON OTHER SHEETS FOR REQUIRED CONTROLS.
- ED17 EXISTING AUTOMATIC TRANSFER SWITCH TO REMAIN. PROTECT DURING DEMOLITION AND NEW CONSTRUCTION.
- ED18 EXISTING GENERATOR TO REMAIN. PROTECT DURING DEMOLITION AND NEW CONSTRUCTION.
- ED19 WHERE LIGHT SWITCH IS BEING REMOVED FROM A WALL THAT IS TO REMAIN, AND WHERE A NEW LIGHT SWITCH IS INDICATED IN THE SAME LOCATION, REUSE THE EXISTING BACKBOX AND CONDUIT TO ACCOMMODATE NEW SWITCH. RE: NEW WORK ON SHEETS E1.3 AND E1.4.
- ED20 WHERE LIGHT SWITCH IS BEING REMOVED AND WHERE A NEW SWITCH IS NOT INDICATED TO BE INSTALLED IN THE SAME LOCATION, BACKBOX AND CONDUIT IN WALL SHALL REMAIN AND WALL SHALL BE PATCHED AS DIRECTED BY THE ARCHITECT. REMOVE EXISTING CONDUCTORS TO SOURCE.
- ED21 DISCONNECT AND REMOVE ALL EXISTING CEILING MOUNTED SPEAKERS, WHETHER INDICATED ON DRAWINGS OR NOT, AND ASSOCIATED CONDUCTORS TO SOURCE. FIELD VERIFY EXACT QUANTITY AND LOCATION OF ALL SPEAKERS.
- ED22 DISCONNECT AND REMOVE EXISTING LIGHTING FIXTURES AT FLAG POLES. RETAIN EXISTING CIRCUITS FOR RE-USE.
- ED23 PROVIDE ELECTRICAL DEMOLITION ASSOCIATED WITH DEMOLITION OF EXISTING ELEVATOR. REFERENCE ARCHITECTURAL DRAWINGS AND VERIFY EXACT REQUIREMENTS.
- ED24 DISCONNECT AND REMOVE EXISTING DATA/POWER OUTLET AND RETAIN FOR RELOCATION TO NEW LOCATION AND MOUNTING HEIGHT. RE: NEW WORK ON SHEET E1.2. RETAIN CIRCUIT FOR RE-USE.

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.

OUACHITA PARISH PUBLIC LIBRARY
 MAIN BRANCH RENOVATION
 MONROE, LOUISIANA



LAND 3
 ARCHITECT, INC.
 A PROFESSIONAL CORPORATION
 1900 STUBBS AVENUE
 MONROE, LA
 71201-5786



DRAWN BY:	JDK
CHK'D BY:	TGS
JOB #	1963
DATE:	08/2024
COPYRIGHT PROTECTED	



1ST FLOOR PLAN
 DEMOLITION -
 ELECTRICAL

ED1.1

ELECTRICAL DEMOLITION NOTES

-X-X-X- EXISTING TO BE REMOVED
 _____ EXISTING TO REMAIN


- ED1 DISCONNECT AND REMOVE THE EXISTING F/A SYSTEM IN IT'S ENTIRETY.
- ED2 DISCONNECT AND REMOVE EXISTING LIGHTING FIXTURE AND RETAIN CIRCUIT FOR RE-USE.
- ED3 EXISTING RECEPTACLE TO REMAIN. PROTECT DURING DEMOLITION AND NEW CONSTRUCTION.
- ED4 DISCONNECT AND REMOVE EXISTING RECEPTACLE AND CONDUCTORS/CONDUIT TO SOURCE. WHERE RECEPTACLE IS BEING REMOVED FROM WALL THAT IS TO REMAIN, CONDUIT AND BACK BOX MAY REMAIN IN WALL. REMOVE CONDUCTORS TO SOURCE AND PATCH WALL AS DIRECTED BY THE ARCHITECT.
- ED5 DISCONNECT AND REMOVE EXISTING LIGHTING SWITCH.
- ED6 EXISTING CAMERAS AND ASSOCIATED CONDUCTORS/CONDUIT ARE TO REMAIN. PROTECT DURING DEMOLITION AND NEW CONSTRUCTION. WHERE DEMOLITION AND NEW CONSTRUCTION INDICATED ON ARCHITECTURAL DRAWINGS INTERRUPT EXISTING CAMERAS, THIS CONTRACTOR SHALL RELOCATE CAMERA AS DIRECTED BY THE ARCHITECT.
- ED7 CONTRACTOR SHALL REPAIR/REPLACE AND FEED THRU BRANCH CIRCUIT WIRING DAMAGED OR INTERRUPTED BY DEMOLITION.
- ED8 PROVIDE ELECTRICAL DEMOLITION ASSOCIATED WITH MECHANICAL DEMOLITION. RE: MECHANICAL DEMOLITION PLANS.
- ED9 PROVIDE DEMOLITION OF POWER/DATA RECEPTACLES AND ANY OTHER ELECTRICAL DEVICES IN WALLS BEING DEMOLISHED WHETHER INDICATED ON THIS DRAWING OR NOT. REFERENCE ARCHITECTURAL DRAWINGS.
- ED10 WHERE LIGHT SWITCH IS BEING REMOVED FROM A WALL THAT IS TO REMAIN, AND WHERE A NEW LIGHT SWITCH IS INDICATED IN THE SAME LOCATION, REUSE THE EXISTING BACKBOX AND CONDUIT TO ACCOMMODATE NEW SWITCH. RE: NEW WORK ON SHEET E2.2.
- ED11 WHERE LIGHT SWITCH IS BEING REMOVED AND WHERE A NEW SWITCH IS NOT INDICATED TO BE INSTALLED IN THE SAME LOCATION, BACKBOX AND CONDUIT IN WALL SHALL REMAIN AND WALL SHALL BE PATCHED AS DIRECTED BY THE ARCHITECT. REMOVE EXISTING CONDUCTORS TO SOURCE.
- ED12 DISCONNECT AND REMOVE ALL EXISTING CEILING MOUNTED SPEAKERS, WHETHER INDICATED ON DRAWINGS OR NOT, AND ASSOCIATED CONDUCTORS TO SOURCE. FIELD VERIFY EXACT QUANTITY AND LOCATION OF ALL SPEAKERS.



SECOND FLOOR PLAN DEMOLITION – ELECTRICAL


SCALE: 1/16" = 1'-0"

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.



ELECTRICAL NOTES:

- EXISTING TO REMAIN
- NEW CONSTRUCTION
- E1 COORDINATE THE EXACT REQUIREMENTS OF LAPTOP CHARGER WITH THE ARCHITECT AND OWNER PRIOR TO ROUGH-IN. ADJUST CIRCUIT AS REQUIRED.
- E2 REUSE EXISTING POWER THAT PREVIOUSLY SERVED THE FIRE ALARM PANEL AND CONNECT TO NEW FIRE ALARM PANEL.
- E3 PROVIDE POWER FOR MOTORIZED PROJECTOR SCREENS. COORDINATE THE EXACT REQUIREMENTS WITH ARCHITECTURAL PLANS AND SPECIFICATIONS.
- E4 EXTEND NEW CONDUIT AND CONDUCTORS AND CONNECT TO CIRCUIT INDICATED AT EXISTING JUNCTION BOX ABOVE CEILING AT COLUMN.
- E5 SAWCUT SLAB TO WALL FOR UNDERSLAB CONDUIT RUN.
- E6 COORDINATE THE EXACT LOCATION AND MOUNTING HEIGHT OF RECEPTACLES FOR MONITOR WITH ARCHITECTURAL PLANS PRIOR TO ROUGH-IN.
- E7 EXTEND CONDUCTORS AND CONDUIT FROM NEW RECEPTACLE AND CONNECT TO EXISTING RECEPTACLE CIRCUIT.
- E8 PROVIDE ALL FLOW AND TAMPER CONNECTIONS REQUIRED BY FIRE SPRINKLER RISER.
- E9 CONNECT TO ROOM LIGHTING CIRCUIT AND INTERLOCK WITH ROOM LIGHT SWITCH.
- E10 EXTEND 3#10, 3/4" C AND CONNECT TO NEW 3P-20A BREAKER 208V PANEL WITH SUFFICIENT SPACE AND CAPACITY.




PARTIAL FIRST FLOOR PLAN - POWER

SCALE: 1/8" = 1'-0"

- E11 PROVIDE ROUGH-IN FOR SCREEN CONTROL. PROVIDE 3/4" C FROM BACKBOX AND STUB UP ABOVE ACCESSIBLE CEILING. PROVIDE NYLON PULL STRING.
- E12 PROVIDE FOUR (4) PORTS AND FOUR (4) CABLES AT OUTLET.
- E13 PROVIDE THREE (3) PORTS AND THREE (3) CABLES AT OUTLET.
- E14 PROVIDE SIX (6) PORTS AND SIX (6) CABLES AT OUTLET.
- E15 PROVIDE PROVISIONS FOR ACCESS CONTROL. RE: SECURE ENTRY DOOR ELEVATION - SECURITY ROUGH-IN ON SHEET E3.3.
- E16 EXTEND 3#12, 1/2" C TO NEW 1P-20A BREAKER IN EXISTING 120V PANEL WITH SUFFICIENT SPACE AND CAPACITY.
- E17 COORDINATE THE EXACT REQUIREMENTS OF AUTOMATIC DOOR WITH ARCHITECTURAL PLANS AND SPECS PRIOR TO ROUGH-IN.
- E18 ROUTE DATA AND POWER CIRCUITS SERVING AREA 105 DOWN IN COLUMN AND AROUND MILLWORK. SAWCUTTING IN THIS AREA SHALL NOT BE ACCEPTABLE.

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.



PARTIAL FIRST FLOOR PLAN - POWER

SCALE: 1/8" = 1'-0"

ELECTRICAL NOTES:

--- EXISTING TO REMAIN
 - - - NEW CONSTRUCTION

- (E1) COORDINATE THE EXACT LOCATION OF BOOK MOBILE RECEPTACLE WITH ARCHITECT PRIOR TO ROUGH-IN.
- (E2) EXTEND 3#12-1/2"C TO NEW 1P-20A BREAKER IN EXISTING PANEL "F".
- (E3) COORDINATE THE EXACT LOCATION AND MOUNTING HEIGHT OF RECEPTACLES FOR MONITOR WITH ARCHITECTURAL PLANS PRIOR TO ROUGH-IN.
- (E4) PROVIDE GFI BREAKER.
- (E5) CONNECT TO ROOM LIGHTING CIRCUIT AND INTERLOCK WITH LIGHT SWITCH. RE: MECHANICAL DRAWINGS AND PROVIDE ALL ELECTRICAL REQUIREMENTS.
- (E6) EXTEND NEW CONDUIT CONDUCTORS AND CONNECT TO CIRCUIT INDICATED AT EXISTING JUNCTION BOX ABOVE CEILING AT COLUMN.
- (E7) EXTEND NEW CONDUIT AND CONDUCTORS AND CONNECT TO NEW 1P-20A BREAKER IN EXISTING PANEL "F".
- (E8) EXTEND NEW CONDUIT AND CONDUCTORS AND CONNECT TO NEW 2P-50A BREAKER IN EXISTING PANEL "F".
- (E9) EXTEND NEW CONDUIT AND CONDUCTORS AND CONNECT TO NEW 3P-40A BREAKER IN EXISTING PANEL "F".
- (E10) INSTALL RECEPTACLE RETAINED FROM DEMOLITION. EXTEND CONDUIT AND CONDUCTORS AND CONNECT TO EXISTING CIRCUIT RETAIN FROM DEMOLITION.


- (E11) PROVIDE PROVISIONS FOR ACCESS CONTROL. RE: SECURE ENTRY DOOR ELEVATION - SECURITY ROUGH-IN ON SHEET E3.3.
- (E12) PROVIDE PROVISIONS FOR ACCESS CONTROL AT ELEVATOR. COORDINATE EXACT REQUIREMENTS WITH THE ELEVATOR PROVIDER AND WITH ARCHITECTURAL SPECIFICATIONS.
- (E13) COORDINATE EXACT LOCATION OF HAND DRYER WITH ARCHITECT PRIOR TO ROUGH-IN. EXTEND 3#12, 1/2"C TO NEW 1P-20A BREAKER IN EXISTING 120V PANEL WITH SUFFICIENT SPACE AND CAPACITY.
- (E14) COORDINATE THE EXACT LOCATION OF THE DEHUMIDIFIER WITH THE OWNER AND ARCHITECT PRIOR TO ROUGH-IN OF RECEPTACLE.
- (E15) EXTEND 3#12, 1/2"C TO NEW 1P-20A BREAKER IN EXISTING 120V PANEL WITH SUFFICIENT SPACE AND CAPACITY.
- (E16) PROVIDE FOUR (4) PORTS AND FOUR (4) CABLES AT OUTLET.
- (E17) PROVIDE SIX (6) PORTS AND SIX (6) CABLES AT OUTLET.
- (E18) PROVIDE THREE (3) PORTS AND THREE (3) CABLES AT OUTLET.
- (E19) PROVIDE A STRUCTURE MOUNTED CORD REEL. CORD REEL SHALL HAVE A 20A DUPLEX RECEPTACLE PENDANT OUTLET, BALL STOP, #12 AWG, AND 30' CORD LENGTH. CORD REEL SHALL BE REELCRAFT #L45451237A OR EQUAL.

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.


SEE ELEVATOR DETAIL (SHEET E3.2) FOR POWER REQUIREMENTS

MATCHLINE

MATCHLINE




LAND 3
 ARCHITECT, INC.
 A PROFESSIONAL CORPORATION
 1900 STUBBS AVENUE
 MONROE, LA
 71201-5786
EMA
 ENGINEERING & ARCHITECTURE
 5001 STEVENS ROAD, SUITE 200
 SHREVEPORT, LOUISIANA 71272
 504-633-8000



DRAWN BY: JDK
 CHK'D BY: TGS
 JOB # 1963
 DATE: 08/2024
 COPYRIGHT PROTECTED

PARTIAL 1ST FLOOR
 PLAN - LIGHTING

E1.3




ELECTRICAL NOTES:


- EXISTING TO REMAIN
- NEW CONSTRUCTION
- (E1) EXTEND AND CONNECT TO EXISTING CIRCUIT RETAINED FROM DEMOLITION THAT PREVIOUSLY SERVED EMERGENCY LIGHTS IN THIS VICINITY.
- (E2) EXTEND AND CONNECT TO EXISTING LIGHTING CIRCUIT RETAINED FROM DEMOLITION, THAT IS DEDICATED TO LIGHTING LOADS ONLY; OR EXTEND AND CONNECT TO NEW OR UNUSED 1P-20A BREAKER IN EXISTING 120V PANEL WITH SUFFICIENT SPACE AND CAPACITY.
- (E3) REINSTALL EXISTING LIGHTING SWITCH THAT PREVIOUSLY CONTROLLED LIGHTING FIXTURES IN MAIN LIBRARY AREA. EXTEND AND CONNECT CONDUCTORS AS REQUIRED FOR A COMPLETE AND OPERATIONAL SYSTEM
- (E4) EXTEND AND CONNECT TO EXISTING LIGHTING CIRCUIT.
- (E5) PROVIDE FIXTURE AS DIRECTED BY THE ARCHITECT.
- (E6) CONNECT TO EXISTING POWER. ROUTE CIRCUITS THRU CONTACTOR.
- (E7) PROVIDE A WALL MOUNT VACANCY SENSOR, LUTRON MAESTRO OR EQUAL.
- (E8) REFERENCE GENERAL LIGHTING NOTES ON SHEET E3.2.
- (E9) SWITCHING AND OCCUPANCY SENSORS ARE INDICATED AS LINE VOLTAGE FOR ILLUSTRATION ONLY. ALL CONTROLS, OCCUPANCY SENSORS, POWER PACKS, ETC. SHALL BE LOW VOLTAGE. CONTRACTOR SHALL PROVIDE LIGHTING CONTROL SHOP DRAWINGS WITH LIGHTING FIXTURE SUBMITTAL PACKAGE INDICATION ALL COMPONENTS, WIRING DIAGRAM, ETC. REFER TO SPECIFICATIONS FOR ADDITIONAL INFORMATION.

PARTIAL FIRST FLOOR PLAN - LIGHTING
 SCALE: 1/8" = 1'-0"

(E10) NEW FIXTURE WITH NO CIRCUITING INDICATED IS A "ONE-FOR-ONE" REPLACEMENT AND SHALL BE RECONNECTED TO EXISTING CIRCUIT RETAINED FROM DEMOLITION. CONNECT TO EXISTING OR RELOCATED LIGHT SWITCH THAT PREVIOUSLY CONTROLLED LIGHTING FIXTURES.




THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.




PARTIAL FIRST FLOOR PLAN - LIGHTING
 SCALE: 1/8" = 1'-0"

- ELECTRICAL NOTES:**
- EXISTING TO REMAIN
 - NEW CONSTRUCTION
 - (E1) EXTEND AND CONNECT TO EXISTING LIGHTING CIRCUIT RETAINED FROM DEMOLITION, THAT IS DEDICATED TO LIGHTING LOADS ONLY; OR EXTEND AND CONNECT TO NEW OR UNUSED 1P-20A BREAKER IN EXISTING 120V PANEL WITH SUFFICIENT SPACE AND CAPACITY. FIELD VERIFY.
 - (E2) SWITCH ROWS 1, 2, & 3 TOGETHER, AND ROWS 4, 5, & 6 TOGETHER.
 - (E3) PROVIDE FIXTURE AS DIRECTED BY THE ARCHITECT.
 - (E4) CONNECT TO EXISTING POWER. ROUTE CIRCUITS THRU CONTACTOR.
 - (E5) CONNECT TO EXISTING POWER. PROVIDE A WALL MOUNT VACANCY SENSOR, LUTRON MAESTRO OR EQUAL.
 - (E6) SWITCH ROWS 1&2 TOGETHER, AND ROWS 3&4 TOGETHER.
 - (E7) REFERENCE GENERAL LIGHTING NOTES ON SHEET E3.2.
 - (E8) SWITCHING AND OCCUPANCY SENSORS ARE INDICATED AS LINE VOLTAGE FOR ILLUSTRATION ONLY. ALL CONTROLS, OCCUPANCY SENSORS, POWER PACKS, ETC. SHALL BE LOW VOLTAGE. CONTRACTOR SHALL PROVIDE LIGHTING CONTROL SHOP DRAWINGS WITH LIGHTING FIXTURE SUBMITTAL PACKAGE INDICATION ALL COMPONENTS, WIRING DIAGRAM, ETC. REFER TO SPECIFICATIONS FOR ADDITIONAL INFORMATION.
 - (E9) CONNECT TO EXISTING EXTERIOR LIGHTING FIXTURE CIRCUIT.

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.




PARTIAL SECOND FLOOR PLAN - POWER
 SCALE: 1/8" = 1'-0"




PARTIAL SECOND FLOOR PLAN - POWER
 SCALE: 1/8" = 1'-0"

- ELECTRICAL NOTES:**
- EXISTING TO REMAIN
 - NEW CONSTRUCTION
 - (E1) EXTEND AND CONNECT TO EXISTING 120V CIRCUIT RETAINED FROM DEMOLITION WITH NO OTHER CONNECTED LOADS; OR EXTEND AND CONNECT TO NEW OR UNUSED 1P-20A BREAKER IN EXISTING 120V PANEL WITH SUFFICIENT SPACE AND CAPACITY.
 - (E2) COORDINATE THE EXACT LOCATION AND MOUNTING HEIGHT OF RECEPTACLES FOR MONITOR WITH ARCHITECTURAL PLANS PRIOR TO ROUGH-IN.
 - (E3) PROVIDE 4#xx,x"C TO FUSED DISCONNECT IN xxx.
 - (E4) REFERENCE GENERAL ELECTRICAL NOTES ON SHEET E3.2.
 - (E5) PROVIDE SIX (6) PORTS AND SIX (6) CABLES AT DATA OUTLET.
 - (E6) PROVIDE FOUR (4) PORTS AND FOUR (4) CABLES AT DATA OUTLET.

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.



PARTIAL SECOND FLOOR PLAN - LIGHTING
 SCALE: 1/8" = 1'-0"




PARTIAL SECOND FLOOR PLAN - LIGHTING
 SCALE: 1/8" = 1'-0"

ELECTRICAL NOTES:

- EXISTING TO REMAIN
 - - - - NEW CONSTRUCTION
- (E1) EXTEND AND CONNECT TO EXISTING LIGHTING CIRCUIT RETAINED FROM DEMOLITION, THAT IS DEDICATED TO LIGHTING LOADS ONLY; OR EXTEND AND CONNECT TO NEW OR UNUSED 1P-20A BREAKER IN EXISTING 120V PANEL WITH SUFFICIENT SPACE AND CAPACITY.
- (E2) PROVIDE A WALL MOUNT VACANCY SENSOR, LUTRON MAESTRO OR EQUAL.
- (E3) CORRIDOR LIGHTING FIXTURES SHALL BE ON ONE CIRCUIT. REFERENCE OTHER PARTIAL SECOND FLOOR PLAN ON THIS SHEET FOR CONTINUATION.
- (E4) REFERENCE GENERAL LIGHTING NOTES ON SHEET E3.2.
- (E5) SWITCHING AND OCCUPANCY SENSORS ARE INDICATED AS LINE VOLTAGE FOR ILLUSTRATION ONLY. ALL CONTROLS, OCCUPANCY SENSORS, POWER PACKS, ETC. SHALL BE LOW VOLTAGE. CONTRACTOR SHALL PROVIDE LIGHTING CONTROL SHOP DRAWINGS WITH LIGHTING FIXTURE SUBMITTAL PACKAGE INDICATION ALL COMPONENTS, WIRING DIAGRAM, ETC. REFER TO SPECIFICATIONS FOR ADDITIONAL INFORMATION.

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.



LIGHTING FIXTURE SCHEDULE						
MARK	TYPE	MOUNTING	MANUFACTURER CATALOG NO.	LAMPS QTY & TYPE	DESCRIPTION	ALTERNATE MANUFACTURER
C1	4' LED STRIP LIGHT	CEILING SUSPENDED/SURFACE	LITHONIA ZL1NL485000LFSTMVOLT35K	LED 3500K	FIXED OUTPUT; LENSED 44W CAP 0-10V WIRES FOR NON-DIMMED FIXTURES.	
LA1	2x4 LED TROFFER FLAT PANEL	CEILING RECESSED GRID	LITHONIA EPANL 2X4 4000LM 80CRI 35K MIN1 MVOLT	LED 3500K 31 WATTS	ACRYLIC LENS; 4000 LUMENS; 0-10V DIMMING TO 1%	
LA2	2x4 LED TROFFER FLAT PANEL	CEILING RECESSED GRID	LITHONIA EPANL 2X4 4800LM 80CRI 35K MIN1 MVOLT	LED 3500K 45 WATTS	ACRYLIC LENS; 4800 LUMENS; 0-10V DIMMING TO 1%	
LA3	2x4 LED TROFFER FLAT PANEL	CEILING RECESSED GRID	LITHONIA EPANL 2X4 6000LM 80CRI 35K MIN1 MVOLT	LED 3500K 55 WATTS	ACRYLIC LENS; 6000 LUMENS; 0-10V DIMMING TO 1%	
LB1	2x2 LED TROFFER FLAT PANEL	CEILING RECESSED GRID	LITHONIA EPANL 2X2 2000LM 80CRI 35K MIN1 MVOLT	LED 3500K 16 WATTS	ACRYLIC LENS; 2000 LUMENS; 0-10V DIMMING TO 1%	
LD1	LED 6" DOWNLIGHT	CEILING RECESSED GRID	GOTHAM IVO6S D 20LM 35K 80CRI MD MIN1 MVOLT	LED 3500K 17.5 WATTS	0-10V DIMMING; 2000 LUMENS; BAR HANGERS; DIFFUSE LENS; WET LOCATION; 0-10V DIMMING TO 1%	
LD2	LED 8" DOWNLIGHT	CEILING RECESSED GRID	GOTHAM EV08 40/ AR MD LSS 120 GZ1	LED 4000K 47.1 WATTS	0-10V DIMMING; 3000 LUMENS; BAR HANGERS; DIFFUSE LENS; WET LOCATION; 0-10V DIMMING TO 1%	
LF1	4' LED LINEAR	CEILING SUSPENDED	HP-4-P-D-S-835-F-SSA-120-SC	LED 3500K 3.6WATTS/FT	428L/FT FINISH BY ARCHITECT	
LF2	SUSPENDED TRIANGLE	CEILING SUSPENDED	POLP-TRI-ULO-LED-80-4200-35-UNV-D1-RDB	LED 3500K	4200 LUMENS FINISH BY ARCHITECT	
LF3	4' LED LINEAR	CEILING SUSPENDED	POLW-Y-ULO-LED-80-1500-35-UNV-D1-RDB-1-DMB	LED 3500K 3.6WATTS/FT	428L/FT FINISH BY ARCHITECT	
LF4	LED "Y"	WALL SURFACE	POLW-Y-ULO-LED-80-1500-35-UNV-D1-RDB-1-DMB	LED 3500K 3.6WATTS/FT	428L/FT FINISH BY ARCHITECT	
LGFE	WET LOCATION LED	CEILING RECESSED GRID	LITHONIA DMW2L243000LMACL MDMVOLT35K80CRI	LED 3500K	3,000 LUMENS; WET LOCATION; ACRYLIC LENS	
R1	5' PENDANT LED ARCHITECTURAL RING	PENDANT	AXIS SKPE-10005-SL 60/40-CIR-400-80-35-SO-UNV-DP	LED 3500K	DIRECT/INDIRECT RING PENDANT; COLOR AND FINISH AS SELECTED BY ARCHITECT; DIMMABLE	
R2	4' PENDANT LED ARCHITECTURAL RING	PENDANT	AXIS SKPE-10004-SL 60/40-CIR-400-80-35-SO-UNV-DP	LED 3500K	DIRECT/INDIRECT RING PENDANT; COLOR AND FINISH AS SELECTED BY ARCHITECT; DIMMABLE	
R3	3' PENDANT LED ARCHITECTURAL RING	PENDANT	AXIS SKPE-10003-SL 60/40-CIR-400-80-35-SO-UNV-DP	LED 3500K	DIRECT/INDIRECT RING PENDANT; COLOR AND FINISH AS SELECTED BY ARCHITECT; DIMMABLE	
S1	DIRECT/INDIRECT WALL SCONCE	WALL SURFACE	GOTHAM IC04UDWC 40/ 25 AR LSS 45D	LED 4000K	DIRECT/INDIRECT; 45° BEAM ANGLE; WET LISTED AND IP66 RATED; COLOR & FINISH AS SELECTED BY ARCHITECT	
SF1	FLAG FLOOD LIGHT	STANCHION	LITHONIA DSXF3 LED 6 P2 40K 70CRI MSP MVOLT UBV DDBXD	LED 4000K 169 WATTS	18,603 LUMENS; WET LOCATION; NEMA TYPE 4X4; STANCHION MOUNT; TOP MOUNTED VISOR; COLOR & FINISH AS SELECTED BY ARCHITECT	
SF2	FACADE FLOOD LIGHT	ROOF	LITHONIA DSXF LED P3 40K 70CRI HMF MVOLT DDBXD	LED 4000K 100 WATTS	10,487 LUMENS; WET LOCATION; NEMA TYPE 6X4; COLOR & FINISH AS SELECTED BY ARCHITECT	
W1	WALL PACK	WALL SURFACE	KIM WD14D4E3560L 4KUVDB	LED 4000K 65 WATTS	WET LOCATION; 5000L COLOR & FINISH AS SELECTED BY ARCHITECT	
WW1	WALL WASH	CEILING RECESSED	GOTHAM IVO6S WW 15LM 35K 80CRI MIN1 MVOLT	LED 3500K 13.3 WATTS	1500 LUMENS; 0-10V DIMMING TO 1%; COLOR & FINISH AS SELECTED BY ARCHITECT	
X1	EXIT SIGN-DIE CAST UNIVERSAL	CEILING/WALL	EELP CA1RAASD	LED	NICAD BATTERY, PLATE ARROWS AS REQUIRED; CAST ALUMINUM HOUSING; SELF DIAGN.	
X2	EXIT SIGN-DIE CAST DOUBLE FACE	CEILING/WALL	EELP CA2RAASD	LED	NICAD BATTERY, PLATE ARROWS AS REQUIRED; CAST ALUMINUM HOUSING; SELF DIAGN.	

NOTES:


- CONTRACTOR SHALL SUBMIT FULL RANGE OF FINISHES FOR ALL FIXTURES TO ARCHITECT. ALL FINISHES ARE SELECTED BY ARCHITECT. ANY AND ALL COSTS ASSOCIATED WITH CUSTOM FINISHES SHALL BE THE RESPONSIBILITY OF CONTRACTOR.
- ALL FIXTURES SHALL BE RATED FOR 120/277V UNLESS NOTED OTHERWISE.
- ALL INTERIOR LIGHTING FIXTURES SHALL BE 3500K UNLESS NOTED OTHERWISE. ALL EXTERIOR LIGHTING FIXTURES SHALL BE 4000K UNLESS NOTED OTHERWISE.
- VERIFY MOUNTING OF ALL FIXTURES WITH ARCHITECTURAL REFLECTED CEILING PLAN. PROVIDE FLANGE KITS FOR GYPSUM CEILINGS AND SLOPE CEILING ADAPTER KITS WHERE MOUNTING IN SLOPED CEILINGS.
- VERIFY EXACT MOUNTING HEIGHTS WITH EXTERIOR ELEVATIONS AND WALL FINISHES. EXTERIOR LIGHTING FIXTURES SHALL BE CENTERED ON WALL PANELS, JOINTS, ETC. AND NOT ON RIBS, PROTRUSIONS, ETC. ADJUST LOCATIONS AS REQUIRED.
- ALL CROSS HATCHED LIGHTING FIXTURES AND FIXTURES DENOTED WITH AN "E" ON PLANS SHALL CONTAIN A 1400 LUMEN, 90 MINUTE MINIMUM, SELF DIAGNOSTIC BATTERY CONNECTED TO UNSWITCHED CONDUCTORS, UNLESS NOTED OTHERWISE.
- ALL LIGHT FIXTURES SHALL HAVE A MINIMUM WARRANTY OF 5 YEARS.

EXTERIOR LIGHTING CONTROL:

- PHOTOCELL AUTOMATICALLY TURNS ON/OFF LIGHTING AS A FUNCTION OF AVAILABLE DAYLIGHT.
- BUILDING FACADE/LANDSCAPE LIGHTING SHALL BE ON/OFF AS FUNCTION OF DAWN/DUSK AND NOT EARLIER THAN 1 HOUR BEFORE BUSINESS OPENING AND 1 HOUR AFTER BUILDING CLOSING TIME PER 7-DAY TIMECLOCK AS CHOSEN BY OWNER.
- FLAG LIGHTING FIXTURES SHALL BE CONTROLLED SUCH THAT LIGHT FIXTURES SHALL BE "ON" DURING HOURS OF DARKNESS.

ELECTRICAL LEGEND	
SYMBOL	DESCRIPTION
	CONDUIT IN WALL OR ABOVE CEILING
	CONDUIT UNDER FLOOR OR UNDERGROUND
	ARROW INDICATES HOMERUN, TICKMARKS: NEUTRAL, PHASE, GROUND
	POWER PANEL
	SPECIAL PANEL
	JUNCTION BOX; FLUSH FLOOR JUNCTION BOX
	DISCONNECT SWITCH; FUSED; NONFUSED
	TELE/DATA OUTLET ; ABOVE COUNTER
	DATA OUTLET MTD TO STRUCTURE AB CLG
	2 POLE; 3 WIRE RECEPTACLE
	DUPLEX RECEPT; ABOVE COUNTER
	WEATHERPROOF; GROUND FAULT
	QUAD PLEX RECEPTACLE
	RAISED FLOOR MOUNTED RECEPTACLE, DATA
	GANGED FLOOR BOX
	SINGLE POLE SWITCH; 3-WAY; 4-WAY
	PILOT LIGHT; DIMMER; KEYED SWITCH
	AFF ; C
	ABOVE FINISHED FLOOR; CEILING MOUNTED
	FIRE ALARM SYSTEM PULL STATION
	FIRE ALARM SYSTEM SPEAKER/VISUAL SIGNAL
	FIRE ALARM SYSTEM VISUAL SIGNAL
	FIRE ALARM SYSTEM SMOKE DETECTOR
	FIRE ALARM SYSTEM HEAT DETECTOR
	FIRE ALARM SYSTEM DUCT MOUNTED SMOKE DETECTOR
	FIRE ALARM SYSTEM DOOR HOLDER
	PUSH BUTTON
	CEILING INTERCOM SPEAKER
	WALL MOUNTED INTERCOM SPEAKER/HORN
	CATV OUTLET
	MOTOR
	MOTOR TOGGLE SWITCH
	FLOW AND TAMPER SWITCHES
	OCCUPANCY SENSOR, CEILING MOUNTED
	FARA FIRE ALARM REMOTE ANNUNCIATOR
	FACP FIRE ALARM CONTROL PANEL
	MOTORIZED DAMPER
	WIRELESS ACCESS POINT
	SOUND SYSTEM CEILING SPEAKER

NOTE: SOME SYMBOLS MAY NOT BE USED.



OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA



LAND 3
ARCHITECT, INC.
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA
71201-5786
EMA
REGISTERED PROFESSIONAL ENGINEER
LICENSE NO. 10225


BRADLEY M. SMOAK
Lic# 96 No. 41725
PROFESSIONAL ENGINEER
ELECTRICAL ENGINEERING

DRAWN BY: JDK
CHK'D BY: TGS
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED


ELECTRICAL
SCHEDULES

E3.1

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.




A TRACTION ELEVATOR
NO SCALE




EZ PATH IS U.L. TESTED AND CERTIFIED IN ACCORDANCE WITH ASTM E814 (U.L.1479) AND CAN/ULC-S115. SYSTEMS ARE AVAILABLE FOR COMMON FLOOR AND WALL CONSTRUCTIONS WITH RATINGS UP TO AND INCLUDING 4 HOURS.

B RATED WALL PENETRATIONS FOR CONDUIT
NO SCALE



C DETAIL - GROUNDING SYSTEM
NO SCALE

- NOTES:**
- GROUNDING CONDUCTORS ARE TO BE IN COMPLIANCE WITH NEC 2020-ARTICLE 250. REFER TO ELECTRICAL RISER DIAGRAM.
 - ISOLATED GROUNDING (WHERE SPECIFIED) AND EQUIPMENT GROUNDING CONDUCTORS SHALL BE SIZED IN ACCORDANCE WITH TABLE 250-122 OF NEC 2020.
 - GROUNDING ELECTRODE CONDUCTOR SHALL BE SIZED IN ACCORDANCE WITH TABLE 250-66 OF NEC 2020 BASED ON SERVICE ENTRANCE CONDUCTORS OR CONDUCTORS OF SEPARATELY DERIVED SYSTEM (SECONDARY CONDUCTORS).
 - GROUNDING AND GROUNDED CONDUCTORS SHALL BE RUN IN CONDUIT WITH FEEDER/BRANCH CIRCUIT CONDUCTORS.



ELECTRICAL RISER
NO SCALE

GENERAL NOTES:

- CONTRACTOR SHALL BE RESPONSIBLE FOR MAKING ALL ELECTRICAL INSTALLATIONS IN COMPLIANCE WITH ALL CURRENT ELECTRICAL CODES FOR ANY WORK PERFORMED ON EXISTING EQUIPMENT OR INSTALLATIONS.
- DRAWINGS ARE SCHEMATIC IN NATURE AND REPRESENT THE INTENT AND GENERAL SCOPE OF WORK. REVIEW ALL CONTRACT DOCUMENTS (PLANS, SPECIFICATIONS, ADDENDUMS, ETC) FOR ANY REQUIREMENTS THAT MAY NOT BE CALLED OUT ON THE PLANS.
- MAINTAIN AN EQUIVALENT FIRE-RESISTANCE RATING USING AN APPROVED FIRESTOPPING METHOD OF ANY PENETRATION THROUGH A FIRE-RATED WALL, PARTITION, FLOOR, OR CEILING.
- SEE "TYPICAL DEVICE MOUNTING HEIGHT" DETAIL FOR REQUIRED MOUNTING HEIGHTS. COORDINATE ALL MOUNTING HEIGHTS WITH ARCHITECT AND/OR OWNER.
- COORDINATE EXACT LOCATIONS OF ALL CEILING MOUNTED EQUIPMENT WITH ARCHITECTURAL REFLECTED CEILING PLAN.
- FIELD VERIFY THE LOCATION OF ALL EXISTING ELECTRICAL, TELEPHONE, DATA, AND CATV LINES AND POLES PRIOR TO BID AND WORK OF ANY KIND. COORDINATE AS REQUIRED.
- PROVIDE CONDUCTORS FOR BRANCH CIRCUITS AND FEEDERS SIZED FOR A VOLTAGE DROP OF 3% OR LESS.
- ALL WORK SHALL BE PERFORMED IN STRICT ACCORDANCE WITH THE LATEST APPLICABLE EDITION OF THE NATIONAL ELECTRICAL CODE (NEC).
- CONTRACTOR SHALL PROVIDE ALL WORK, MATERIALS, ETC FOR A COMPLETE AND FULLY FUNCTION SYSTEM WHETHER SPECIFICALLY INDICATED ON PLANS AND SPECIFICATIONS OR NOT.
- GROUNDING CONDUCTOR INSTALLATION SHALL COMPLY WITH THE LATEST APPLICABLE EDITION OF THE NEC ARTICLE 250.
- ISOLATED GROUNDING (WHERE SPECIFIED) AND EQUIPMENT GROUNDING CONDUCTORS SHALL BE SIZED IN ACCORDANCE WITH TABLE 250-122 OF THE LATEST APPLICABLE EDITION OF THE NEC.
- GROUNDING ELECTRODE CONDUCTOR SHALL BE SIZED IN ACCORDANCE WITH TABLE 250-66 OF THE LATEST APPLICABLE EDITION OF THE NEC BASED ON SERVICE ENTRANCE CONDUCTOR OR CONDUCTORS OF SEPARATELY DERIVED SYSTEM.
- GROUNDING AND GROUNDING CONDUCTORS SHALL BE RUN IN CONDUIT WITH FEEDER CONDUCTORS.
- CONTRACTOR SHALL INCLUDE ALL PERMITS AND ASSOCIATED FEES IN BID.
- ALL REQUIRED EQUIPMENT TESTING SHALL BE COMPLETE AND APPROVED PRIOR TO ENERGIZING ANY EQUIPMENT.
- COORDINATE VOLTAGE OF ALL EQUIPMENT WITH MECHANICAL CONTRACTOR PRIOR TO BID OR ROUGH-IN.
- PROVIDE SURGE PROTECTIVE DEVICE(S) AS REQUIRED FOR ALL SPECIAL SYSTEMS INCLUDING, BUT NOT LIMITED TO, ACCESS CONTROL, SECURITY, FIRE ALARM, TELECOMMUNICATION ETC. COORDINATE EXACT REQUIREMENTS WITH ARCHITECT AND OWNER.
- PROVIDE PULL STRING IN ALL EMPTY CONDUITS.


GENERAL POWER NOTES:

- COORDINATE EXACT LOCATION OF ALL DEVICES WITH ARCHITECTURAL ELEVATIONS PRIOR TO ROUGH IN.
- CONTRACTOR SHALL COORDINATE THE EXACT LOCATION AND REQUIREMENTS OF ALL EQUIPMENT WITH EQUIPMENT PROVIDER PRIOR TO ROUGH-IN OR BID. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL ELECTRICAL REQUIREMENTS REQUIRED BY EQUIPMENT PROVIDER AND/OR EQUIPMENT DRAWINGS. PROVIDE A COMPLETE AND OPERATIONAL SYSTEM.
- ELECTRICAL CONTRACTOR SHALL COORDINATE THE EXACT ELECTRICAL REQUIREMENTS OF ALL MECHANICAL EQUIPMENT WITH MECHANICAL CONTRACTOR PRIOR TO ROUGH IN. ADJUST CIRCUITS AS REQUIRED.
- REFER TO MECHANICAL PLANS FOR CONTROL OF EXHAUST FANS, ETC. PROVIDE ALL ELECTRICAL REQUIREMENTS.
- CONTRACTOR SHALL BE RESPONSIBLE FOR MAKING ALL ELECTRICAL INSTALLATIONS IN COMPLIANCE WITH ALL CURRENT ELECTRICAL CODES FOR ALL WORK.
- CONTRACTOR SHALL PROVIDE A FIRE ALARM SYSTEM IN STRICT COMPLIANCE WITH NFPA 72 AND 101. CONTRACTOR SHALL BE RESPONSIBLE FOR A COMPLETE AND OPERATIONAL SYSTEM. PROVIDE ALL DEVICES PER NFPA CODES BASED UPON OCCUPANCY OF BUILDING, WHETHER INDICATED ON PLANS OR NOT.
- ALL RECEPTACLES INSTALLED IN BATHROOMS, KITCHENS, GARAGES, LAUNDRY AREAS AND OUTDOORS SHALL BE GFCI RATED.
- COORDINATE EXACT LOCATION, TYPE, AND QUANTITY OF ALL FLOOR BOXES WITH ARCHITECT AND OWNER PRIOR TO ROUGH-IN OR CUTTING/PATCHING AND/OR POURING SLAB.


GENERAL LIGHTING NOTES:

- COORDINATE EXACT LOCATIONS OF ALL LIGHTING FIXTURES WITH ARCHITECTURAL REFLECTED CEILING PLANS AND ELEVATIONS. COORDINATE WITH AIR SUPPLY/RETURN LOCATIONS AND OTHER CEILING MOUNTED DEVICES.
- ALL EXIT/EMERGENCY FIXTURES SHALL BE CONNECTED TO UNSWITCHED CONDUCTORS.
- ALL CROSS-HATCHED FIXTURES SHALL HAVE A 90-MINUTE, 1400 LUMEN, SELF-DIAGNOSTIC BATTERY PACK, BODINE OR EQUAL, CONNECTED TO UNSWITCHED CONDUCTORS.

OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
MONROE, LOUISIANA



LAND 3
ARCHITECT, INC.
A PROFESSIONAL CORPORATION
1900 STUBBS AVENUE
MONROE, LA
71201-5786
EMA
ELECTRICAL MECHANICAL ARCHITECTS
1000 STEVENS ROAD, SUITE 200
SHREVEPORT, LOUISIANA 71201
504-633-4000





DRAWN BY: JKD
CHK'D BY: TGS
JOB # 1963
DATE: 08/2024
COPYRIGHT PROTECTED

ELECTRICAL
DETAILS

E3.2

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.



PAIR ASSIGNMENTS

1. BLUE-WHITE/WHITE-BLUE
2. WHITE-ORANGE/ORANGE-WHITE
3. WHITE-GREEN/GREEN-WHITE
4. WHITE-BROWN/BROWN-WHITE


EIA/TIA 568-B WIRING PLAN

- NOTES:
1. JACK WIRING IS SHOWN WITH COLOR CODE AND PINOUT INSTALLER SHALL CONNECT STATION WIRE TO TERMINALS AT REAR OF JACK TO ENSURE THIS CONFIGURATION.
 2. SEE PAIR ASSIGNMENT TABLE.
 3. ANSI/TIA 568-B CATEGORY 6 CABLE OR OTM APPROVED EQUAL.

TELEPHONE/DATA/CATV RISER



- NOTES:
1. REFER TO TYPICAL FACEPLATE DETAIL THIS SHEET.
 2. ALL TERMINATIONS SHALL BE TESTED IN ACCORDANCE WITH EIA/TIA 568 STANDARDS AND TEST RESULTS PROVIDED TO OWNER. TERMINATION SHALL BE LABELED ON EACH END WITH ROOM NUMBER IT SERVES.
 3. ALL EQUIPMENT RACKS, METALLIC CONDUITS, ETC. SHALL BE BONDED TO COPPER GROUND BAR WITH A #6 AWG GREEN COPPER CONDUCTOR.
 4. RACK LAYOUT IS FOR ILLUSTRATION PURPOSES ONLY.
 5. EXTEND NEW FIBER IN NEW CONDUIT FROM EXISTING CONDUIT ENTRY INTO BUILDING, AND TERMINATE AT NEW WIRE MANAGEMENT RACK IN NEW LOCATION IN BUILDING.
 6. PROVIDE PATCH PANELS TO ACCOMMODATE QUANTITY OF PORTS PER PLANS PLUS 25% ADDITIONAL CAPACITY.

CABLE COLOR CODING	
DATA #1, #2	BLUE
COPY MACHINES	YELLOW
WIRELESS ACCESS	GRAY
ACCESS CONTROL	ORANGE



TELEPHONE/DATA TYPICAL FACEPLATE

- NOTE:
1. ALL JUNCTION BOXES SHALL BE 4" X 4" X 2 1/8" WITH A 1-GANG PLASTER RING.
 2. ALL DATA OUTLETS INDICATED ON PLANS SHALL HAVE 2 PORTS AND CABLES UNLESS NOTED OTHERWISE; SEE DRAWINGS FOR OUTLETS REQUIRING MORE THAN 2 PORTS/CABLES PER OUTLET.



SECURE ENTRY DOOR ELEVATION - SECURITY ROUGH-IN

THE CONTRACTOR SHALL BE REQUIRED TO VISIT THE SITE TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTING A PROPOSAL.

OUACHITA PARISH PUBLIC LIBRARY
MAIN BRANCH RENOVATION
 MONROE, LOUISIANA

LAND 3
 Architect

LAND 3
 ARCHITECT, INC.
 A PROFESSIONAL CORPORATION
 1900 STUBBS AVENUE
 MONROE, LA
 71201-5786
EMA
 ENGINEERING & ARCHITECTURE
 3441 STEVENS ROAD, SUITE 200
 SHREVEPORT, LOUISIANA 71204
 504-636-4000

STATE OF LOUISIANA
 BRADLEY M. SMOAK
 License No. 41725
 PROFESSIONAL
 ENGINEER
 ELECTRICAL ENGINEERING

DRAWN BY: JDK
 CHK'D BY: TGS
 JOB # 1963
 DATE: 08/2024
 COPYRIGHT PROTECTED

ELECTRICAL
 DETAILS

E3.3